

MPE ESTIMATION

FCC ID: 2AWUA-EP01T

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)		
300MHz1.5GHz	F/1500	30		
1.5GHz100GHz	1.0	30		

Note: F= Frequency in MHz

2, Estimation Result

WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm²)
2.4G WIFI	13.75	13±1(14)	25.119	3	1.9953	0.00998
5.2G WIFI	13.69	13±1(14)	25.119	3	1.9953	0.00998
5.8G WIFI	11.54	11±1(12)	15.849	3	1.9953	0.00629

$$Pd = \frac{Pout * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK2003030950-1E/2E/3E, antenna gain=3dBi

simultaneously MPE

 $2.4G \text{ WIFI MPE}_{(max)} = 0.00998 \text{ (mW/cm}^2)$

5G WIFI MPE $_{(max)}$ = 0.00998 (mW/cm²)

simultaneously MPE=0.00998+0.00998=0.01996(mW/cm²)

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01996 mW/cm² which is< 1.0mW/cm², RF Exposure testing is not required.

