

## RF Exposure Exemption

Applicant : Verkada Inc.  
Product Name : Alarm Console  
Trade Name : Verkada  
Model Number : BC82-HW  
Applicable Standard : 47 CFR § 2.1091  
Received Date : Jan. 18, 2023  
Issue Date : Apr. 06, 2023

### Issued by

Approved By : \_\_\_\_\_

Eurofins E&E Wireless Taiwan Co., Ltd.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 334025, Taiwan (R.O.C.)  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

**Note:**

- 1.The test results are valid only for samples provided by customers and under the test conditions described in this report.
- 2.This report shall not be reproduced except in full, without the written approval of Eurofins E&E Wireless Taiwan Co., Ltd.
- 3.The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

**Revision History**

Rev.	Issued Date	Revisions	Revised By
00	Apr. 06, 2023	Initial Issue	Nicole Chu

# Contents

1.	General Information .....	4
2.	Description of Equipment under Test (EUT) .....	5
3.	RF Exposure Limit .....	6
4.	RF Exposure Assessment.....	7
5.	Maximum Conducted Power .....	9
6.	Result .....	9
7.	Conclusion.....	9

## 1. General Information

### 1.1 Reference Applicable Standard

Standard	Description	Version
IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	1992
47 CFR § 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.	-
47 CFR § 1.1310	Radiofrequency radiation exposure limits.	-

### 1.2 Testing Location

Site Name: Site Name: Eurofins E&E Wireless Taiwan Co., Ltd.

Site Address:  No. 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan (R.O.C.)

Site Address:  No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan (R.O.C.)

## 2. Description of Equipment under Test (EUT)

Applicant	Verkada Inc. 405 E. 4th Ave. San Mateo CA 94401 United States
Product Name	Alarm Console
Trade Name	Verkada
Model Number	BC82-HW
FCC ID	2AWUU6075001
Frequency Range	Sub-G SRD : 915.0 - 915.7 MHz WLAN 2.4 GHz Band : 2412 - 2462 MHz WLAN 5.2 GHz Band : 5180 - 5240 MHz WLAN 5.2 GHz Band : 5260 - 5320 MHz WLAN 5.6 GHz Band : 5470 - 5725 MHz WLAN 5.8 GHz Band : 5745 - 5825 MHz Bluetooth : 2402 - 2480 MHz
Supported Modulations	Sub-G SRD : OQPSK
	WLAN 2.4 GHz : 802.11b / g / n HT20 / HT40 / VHT20 / VHT40
	WLAN 5 GHz : 802.11a / n / ac HT20 / HT40 / VHT20 / VHT40 / VHT80
Antenn information	Refer to Antenna spec "Antenna_Performance_Test_Report-V001-20230302"
Use Distance	20 cm

**Note:**

The above information of DUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 3. RF Exposure Limit

For devices that operate at larger distances from persons, where there are minimal RF coupling interactions between a device and the user or nearby persons, RF exposure compliance using maximum permissible exposure (MPE) limits is applied. The limits for MPE is listed as below:

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824 / f	2.19 / f	(180 / f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F / 1,500	30
1,500-100,000	-	-	1.0	30
Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1,842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1,500	-	-	F / 300	6
1,500-100,000	-	-	5	6


f = frequency in MHz. \* = Plane-wave equivalent power density.

## 4. RF Exposure Assessment

### 4.1 Exemption Evaluation

Exemption evaluation was performed according to the appendix A and B in KDB447498 D04.

The General Sequence for Determination of Procedure demonstrated in Figure A.1 of KDB447498 D04 was applied.



## 4.2 Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons."

Exposure evaluation

$$S_{eirp} = \frac{EIRP}{4\pi d^2} = \frac{PG}{4\pi d^2} \left( W / m^2 \right)$$

Where

S: is the input power (W);

G: is the antenna gain;

d : is the distance between antennas and evaluation point (m).



## 5. Maximum Conducted Power

Band	Frequency Range (MHz)	Max Conducted Power ( dBm)	TX Status
Sub-G SRD	915 - 915.7	18.46	SISO
WLAN 2.4 GHz	2412 - 2462	17.08	SISO
WLAN 5.2 GHz	5180 - 5240	14.14	SISO
WLAN 5.3 GHz	5260 - 5320	14.28	SISO
WLAN 5.6 GHz	5470 - 5725	14.26	SISO
WLAN 5.8 GHz	5725 - 5825	14.20	SISO
Bluetooth	2402 - 2480	1.30	SISO

## 6. Result

Band	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (mW)	ANT Gain (dBi)	ERP (W)	<§1.1307(b)(3)(i)(C)> Exemption Minimum Distance (m)	<§1.1307(b)(3)(i)(C)> Exemption Threshold ERP (W)	§1.1307(b)(3)(i)(C)> Exemption considerations
Sub-G SRD	915 - 915.7	18.46	70.15	1.60	0.062	0.052	0.469	Qualified
WLAN 2.4 GHz	2412 - 2462	17.08	51.05	2.70	0.058	0.020	0.768	Qualified
WLAN 5.2 GHz	5180 - 5240	14.14	25.94	2.81	0.030	0.009	0.768	Qualified
WLAN 5.3 GHz	5260 - 5320	14.28	26.79	2.81	0.031	0.009	0.768	Qualified
WLAN 5.6 GHz	5470 - 5725	14.26	26.67	2.81	0.031	0.009	0.768	Qualified
WLAN 5.8 GHz	5725 - 5825	14.20	26.30	2.81	0.031	0.008	0.768	Qualified
Bluetooth	2402 - 2480	1.30	1.35	2.70	0.002	0.020	0.768	Qualified

Note:

This device is qualified for exemption under §1.1307(b)(3)(i)(C).

TER: 0.21

## 7. Conclusion

The result shows that this device is qualified for MPE-Based Exemption in KDB447498. Therefore, MPE testing is not required.

---END---