



## RF exposure

FCC ID : 2AWVMPIXX1826N

According to FCC part 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in § 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Average time
(A) Limits for Occupational / Control Exposures				
300 – 1 500	--	--	f/300	6
1 500 - 100000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300 – 1 500	--	--	f/1500	6
1 500 – 100 000	--	--	<u>1</u>	<u>30</u>

f= frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \times G) / (4 \times \pi \times R^2)$

Where,

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### Tune-up

Frequency (MHz)		2 412 MHz ~ 2 462 MHz	
Tune-up Average Power	2 412	8.0 dBm (±2.0dB)	Max. : 10 dBm
	2 437	8.0 dBm (±2.0dB)	Max. : 10 dBm
	2 462	8.0 dBm (±20dB)	Max. : 10 dBm

### Results

Operation mode	Frequency (MHz)	Average maximum output power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11n_HT20	2 412	10.0	2.27	0.002 70	1
	2 437	10.0	2.27	0.002 85	1
	2 462	10.0	2.27	0.002 77	1