

## RF Exposure Evaluation for FCC ID: 2AWWH-CINSTAW-A

Refer user manual this device is a Camera, and this device was designed used in Mobile devices that the minimum distance between human's body is **20cm**. Based on the 47CFR 2.1091, this device belongs to Mobile device. The definition of the category as following:

### Mobile Derives:

CFR Title 47 §2.1091(b)

(b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

### FCC KDB 447498 D01 General RF Exposure Guidance v06 Limit

Devices operating in standalone mobile exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance  $\geq 20$  cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When the categorical exclusion provision of § 2.1091(c) applies, the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to FCC Part 1.1307, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission’s guidelines.

Limits for General Population/ Uncontrolled Exposure			
Frequency Range (MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength (H)(A/m)	Power Density (S)(mW/cm <sup>2</sup> )
0.3-1.34	614	1.63	(100)*
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*
30-300	27.5	0.073	0.2
300-1500			f/1500
1500-100,000			1.0

**MPE calculation formula**

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density

P = output power (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Separation distance between radiator and human body (cm)

**Test data**

Bluetooth			
Mode	GFSK (BLE)		
	Low Channel	Middle Channel	High Channel
Peak Power (dBm)	1.57	2.45	<b>2.61</b>

Note: This report listed the worst case peak power value, please refer to RF test report for more details.

2.4G WIFI			
Mode	802.11b	802.11g	802.11n20
Peak Power (dBm)	14.89	<b>20.12</b>	18.95

Note: This report listed the worst case peak power value, please refer to RF test report for more details.

5G WIFI						
Mode	U-NII-1					
	802.11a	802.11n20	802.11n40	802.11ac20	802.11ac40	802.11ac80
Conducted Power (dBm)	8.58	8.96	7.41	<b>9.48</b>	8.17	8.26
Mode	U-NII-3					
	802.11a	802.11n20	802.11n40	802.11ac20	802.11ac40	802.11ac80
Conducted Power (dBm)	7.13	7.29	6.83	<b>8.32</b>	7.53	7.29

Note: This report listed the worst case peak power value, please refer to RF test report for more details.

**Turn-up power**

Mode		Range (dBm)
Bluetooth		1.00-3.00
2.4G WIFI		14.50-20.50
5G WIFI	U-NII-1	7.00-10.00
	U-NII-3	5.50-8.50

**Test result**

Evolution mode	Maximum peak output power (dBm)	Antenna Gain (typical) (dBi):	Total Power (mw)	Distance (cm)	Limit of Power Density (mW/cm <sup>2</sup> )	Power Density (mW/cm <sup>2</sup> )	Verdict
Bluetooth	3.00	-1.18	1.52	20	1	0.0003	Pass
2.4G WIFI	20.50	-1.18	85.51	20	1	0.0170	Pass
5G WIFI	U-NII-1	10.00	17.78	20	1	0.0035	Pass
	U-NII-3	8.50	13.93	20	1	0.0028	Pass

**Note:**

1. The Camera work frequency range used is 2400 MHz ~ 2483.5 MHz, 5150 MHz ~ 5250 MHz and 5725 MHz ~ 5850 MHz, the result close to the limit by the above formula, so we select 2445MHz to calculate the exclusion power threshold.
2. More power list please refer to RF test report.

**Conclusion:**

RF exposure Evaluation Results: **Compliance**

## Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the laboratory.
6. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--