

EXPRESS LUCK INDUSTRIAL (SHENZHEN) LIMITED

Modular Transmitter Approval Request

Federal Communications Commission
 Equipment Authorization Branch
 7435 Oakland Mills Road
 Columbia, MD 21046

Company name: EXPRESS LUCK INDUSTRIAL (SHENZHEN) LIMITED

FCC ID: 2AWY6-ELMT7638BUN

Gentlemen,

In accordance with 47CFR 15.212 Modular Transmitters and KDB 996369 D01 'Module Certification Guide v01r04'.

FCC ID :2AWY6-ELMT7638BUN,

has been examined against the following requirements.

Requirement per 15.212 and KDB 996369 D01 'Modular Certification Guide v01r04'	Explanation from Grantee (do not write yes/no, but explain why product complies/how it is achieved)
The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly	The module has its own RF shielding.
The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal	The modular has buffered data inputs, it is integrated in chip
The module must contain power supply regulation on the module	The modular has buffered data inputs, it is integrated in chip
The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b)	Antenna is independent fixed
The module must demonstrate compliance in a stand-alone configuration	All power lines derived from the host device are regulated before energizing other circuits internal
The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements)	The label is independent fixed
The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee	compliant with all applicable FCC rules. Detail instructions are given in the Users Manual
The module must comply with RF exposure requirements	approved to comply with the applicable RFexposure requirement, please see the MPE evaluation with 20cm as the distance restriction.

Name: ZilongLai

Date: 9/7/2021

Title: Manage

Signature of applicant:

Zilong Lai