

**Ear Technology Corporation**

# MPE ASSESSMENT REPORT

**Report Type:**

FCC MPE assessment report

**Model:**

PDQ1TEF

**REPORT NUMBER:**

201001453SHA-003

**ISSUE DATE:**

Nov 25, 2020

**DOCUMENT CONTROL NUMBER:**

TTRFFCCMPE-02\_V1 © 2018 Intertek



**Applicant:** Ear Technology Corporation  
106E Watauga Ave Johnson City, TN 37601 USA

**Manufacturer:** Xiamen Forsound Hearing Technology Co.,Ltd  
4th Floor, Factory One, No. 158 Tianfeng Road, Jimei, Xiamen, Fujian,  
361021 China

**Manufacturing site:** Xiamen Forsound Hearing Technology Co.,Ltd  
4th Floor, Factory One, No. 158 Tianfeng Road, Jimei, Xiamen, Fujian,  
361021 China

**FCC ID:** 2AX37-PDQ1TEF

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:

**FCC PART 1 SECTION 1.1310**

**PREPARED BY:** **REVIEWED BY:**

*Teddy Yin*

---

Project Engineer  
Teddy Yin

*Daniel Zhao*

---

Reviewer  
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## Revision History

Report No.	Version	Description	Issued Date
201001453SHA-003	Rev. 01	Initial issue of report	Nov 25, 2020

## Measurement result summary

TEST ITEM	FCC REFERANCE	TEST RESULT	NOTE
RF Exposure	1.1310	Pass	-

Notes: 1: NA =Not Applicable

2. Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	UV Dryer
Type/Model:	PDQ1TEF
Description of EUT:	EUT is a dryer with wireless charge function. The worst data is listed in the report.
Rating:	DC 12V, 3A Wireless charge output: DC 5V/1A, DC 9V/1.1A, USB output: DC 5V/2A Adaptor: SAW36-120-3000U Input: 100-240V~, 50/60Hz, 1.3A Output: DC 12V, 3000mA
Category of EUT:	Class B
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	Oct 29, 2020
Date of test:	Oct 30~Nov 10, 2020

### 1.2 Technical Specification

Frequency Range:	110kHz – 205kHz
------------------	-----------------

**TEST REPORT**

**1.3 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

## 2 TEST SPECIFICATIONS

### 2.1 Standards or specification

FCC PART 1 SECTION 1.1310  
KDB 680106 D01 RF Exposure Wireless Charging App v03

### 2.2 Mode of operation during the test

Within this test report, EUT was tested under all modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used. The worst data was listed in the report.

### 2.3 Test peripherals list

Item No.	Name	Band and Model	Description
1	Wireless load	/	100% power level
2	Wireless load	/	50% power level
3	Wireless load	/	0% power level

### 2.4 Record of climatic conditions

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)
RF Exposure	22°C	55% RH	101

**2.5 Instrument list**

Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Exposure Level Tester	Narda	NBM-550	EC 6113	2020-11-20
<input checked="" type="checkbox"/>	Field sensor & Field meter	Narda	EF 0391	EC 6113	2020-12-26



**TEST REPORT**

**3 RF Exposure Assessment**

Test result: Pass

**3.1 Assessment Limit**

Reference: 47 CFR §1.1310, KDB 680106


Limits for General Population/Uncontrolled Exposure

Frequency range [MHz]	Electric field strength [V/m]	Magnetic field strength [A/m]	Power density [mW/cm <sup>2</sup> ]	Averaging time [minutes]
0.1 – 0.3	614	1.63	*100	30
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f <sup>2</sup>	30
30 – 300	27.5	0.073	0.2	30
300 – 1 500	-	-	f/1500	30
1 500 – 100 000	-	-	1.0	30

Limits for Occupational/Controlled Exposure

Frequency range [MHz]	Electric field strength [V/m]	Magnetic field strength [A/m]	Power density [mW/cm <sup>2</sup> ]	Averaging time [minutes]
0.1 – 0.3	614	1.63	*100	6
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30 – 300	61.4	0.163	1.0	6
300 – 1 500	-	-	f/300	6
1 500 – 100 000	-	-	5	6

**3.2 Assessment Configuration**



### 3.3 Assessment Results

Test result of Magnetic Field Strength:

Test Position	Test distance (cm)	Test result (A/m)	Limit (A/m)	Result (Pass/Fail)
A: Right	15	0.0011	1.63 *0.5	Pass
B: Left	15	0.0013	1.63 *0.5	Pass
C: Front	15	0.0008	1.63 *0.5	Pass
D: Back	15	0.0011	1.63 *0.5	Pass
E: Top	20	0.0018	1.63 *0.5	Pass

Test result of Electric Field Strength:

Test Position	Test distance (cm)	Test result (V/m)	Limit (V/m)	Result (Pass/Fail)
A: Right	15	0.46	614 *0.5	Pass
B: Left	15	0.47	614 *0.5	Pass
C: Front	15	0.32	614 *0.5	Pass
D: Back	15	0.49	614 *0.5	Pass
E: Top	20	0.54	614 *0.5	Pass

\*\*\*\*\* END \*\*\*\*\*