

# FCC ID : 2AX5J-RAP2200EV2

## 1. RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

Limits for Maximum Permissible Exposure (MPE).

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

**Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$**

Where

$P_d$  = Power density in mW/cm<sup>2</sup>.

$P_{out}$  = output power to antenna in mW.

$G$  = Numeric gain of the antenna relative to isotropic antenna.

$\pi$  = 3.1416.

$R$  = distance between observation point and center of the radiator in 20cm.

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna, power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## 2. EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product	Wireless Access Point
Model Number	RG-RAP2200(E)
Power Supply	DC 48V by POE adapter DC 12V by Power adapter
Temperature Range	0°C ~ 40°C

IEEE 802.11 WLAN Mode Supported	802.11b 802.11g 802.11n(20MHz channel bandwidth) 802.11n(40MHz channel bandwidth)
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n
Operating Frequency Range	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11b/g/n(HT40)
Number of Channels	11 channels for 802.11b/g/n(HT20) 7 Channels for 802.11n(HT40)
Antenna Type	Integrated Antenna
Antenna Gain	ANT1: 3.79dBi, ANT2: 3.79dBi

Wifi Type	UNII-1: 5150MHz-5250MHz Band UNII-2A: with 5250MHz-5350MHz Band UNII-2C: with 5470MHz-5725MHz Band UNII-3 with 5725MHz-5850MHz Band
WLAN Supported	802.11a 802.11n(20MHz channel bandwidth) 802.11n(40MHz channel bandwidth) 802.11ac(20MHz channel bandwidth) 802.11ac(40MHz channel bandwidth) 802.11ac(80MHz channel bandwidth)
Modulation	OFDM
Frequency Range	UNII-1: 5150MHz-5250MHz Band
	5180-5240MHz for 802.11a 5180-5240MHz for 802.11n(HT20) 5180-5240MHz for 802.11ac(HT20) 5190-5230MHz for 802.11n(HT40) 5190-5230MHz for 802.11ac(HT40) 5210MHz for 802.11ac(HT80)
	UNII-2A: with 5250MHz-5350MHz Band
	5260-5320MHz for 802.11a 5260-5320MHz for 802.11n(HT20) 5260-5320MHz for 802.11ac(HT20)

	5270-5310MHz for 802.11n(HT40) 5270-5310MHz for 802.11ac(HT40) 5290MHz for 802.11ac(HT80)
	UNII-2C: with 5470MHz-5725MHz Band
	5500-5700MHz for 802.11a 5500-5700MHz for 802.11n(HT20) 5500-5700MHz for 802.11ac(HT20) 5510-5670MHz for 802.11n(HT40) 5510-5670MHz for 802.11ac(HT40) 5530-5610MHz for 802.11ac(HT80)
	UNII-3 with 5725MHz-5850MHz Band
	5745-5825MHz for 802.11a 5745-5825MHz for 802.11n(HT20) 5745-5825MHz for 802.11ac(HT20) 5755-5795MHz for 802.11n(HT40) 5755-5795MHz for 802.11ac(HT40) 5775MHz for 802.11ac(HT80)
<b>TPC Function</b>	Applicable
<b>Antenna Type</b>	Integrated Antenna
<b>Antenna Gain</b>	ANT1: 4.67dBi, ANT2: 4.67dBi

### 3. Measurement Result

Below mode can't transmit simultaneously.

Mode	Max Conducted Power (dBm)	Antenna gain (dBi)	Antenna Gain Numeric	R (cm)	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
2.4G WIFI	17.93	3.79	2.39	20	0.030	1
5G WIFI	21.61	4.67	2.93	20	0.084	1

**Note:** All the modes are tested, only the worst data are described in the table.

----- The End -----