


TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\105
Memo: 11AC20MIMO 5500

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5431.06	46.84	4.24	32.90	-30.93	53.05	74.00	20.95	PK	Horizontal
2	5460.00	43.60	4.25	32.90	-30.92	49.83	68.20	18.37	PK	Horizontal
3	5470.00	45.02	4.26	32.90	-30.91	51.27	68.20	16.93	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5431.06	41.05	4.24	32.90	-30.93	47.26	54.00	6.74	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\106
Memo: 11AC20MIMO 5500

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5430.28	47.27	4.24	32.90	-30.93	53.48	74.00	20.52	PK	Vertical
2	5460.00	44.83	4.25	32.90	-30.92	51.06	68.20	17.14	PK	Vertical
3	5470.00	45.87	4.26	32.90	-30.91	52.12	68.20	16.08	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5430.28	41.72	4.24	32.90	-30.93	47.93	54.00	6.07	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\107
Memo: 11AX20MIMO 5500

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5433.29	47.11	4.24	32.90	-30.93	53.32	74.00	20.68	PK	Horizontal
2	5460.00	44.82	4.25	32.90	-30.92	51.05	68.20	17.15	PK	Horizontal
3	5470.00	48.17	4.26	32.90	-30.91	54.42	68.20	13.78	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5433.29	41.86	4.24	32.90	-30.93	48.07	54.00	5.93	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\108
Memo: 11AX20MIMO 5500

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5445.45	47.26	4.25	32.90	-30.92	53.49	74.00	20.51	PK	Vertical
2	5460.00	45.37	4.25	32.90	-30.92	51.60	68.20	16.60	PK	Vertical
3	5470.00	45.12	4.26	32.90	-30.91	51.37	68.20	16.83	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5445.45	40.51	4.25	32.90	-30.92	46.74	54.00	7.26	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-11 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\109
Memo: 11BE20MIMO 5500

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5443.62	47.14	6.79	32.90	-30.92	55.91	74.00	18.09	PK	Horizontal
2	5460.00	44.83	6.82	32.90	-30.92	53.63	68.20	14.57	PK	Horizontal
3	5470.00	43.87	6.84	32.90	-30.91	52.70	68.20	15.50	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5443.62	35.28	6.79	32.90	-30.92	44.05	54.00	9.95	AV	Horizontal
2	5460.00	34.82	6.82	32.90	-30.92	43.62	54.00	10.38	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-11 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\110
Memo: 11BE20MIMO 5500

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5421.27	47.20	6.75	32.90	-30.93	55.92	74.00	18.08	PK	Vertical
2	5460.00	44.73	6.82	32.90	-30.92	53.53	68.20	14.67	PK	Vertical
3	5470.00	45.40	6.84	32.90	-30.91	54.23	68.20	13.97	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5421.27	35.29	6.75	32.90	-30.93	44.01	54.00	9.99	AV	Vertical
2	5460.00	34.72	6.82	32.90	-30.92	43.52	54.00	10.48	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\111
Memo: 11BE20MIMO 5500 RU38+RU1

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5444.38	47.95	6.79	32.90	-30.92	56.72	74.00	17.28	PK	Horizontal
2	5460.00	44.47	6.82	32.90	-30.92	53.27	68.20	14.93	PK	Horizontal
3	5470.00	43.84	6.84	32.90	-30.91	52.67	68.20	15.53	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5444.38	35.22	6.79	32.90	-30.92	43.99	54.00	10.01	AV	Horizontal
2	5460.00	34.82	6.82	32.90	-30.92	43.62	54.00	10.38	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\112
Memo: 11BE20MIMO 5500 RU38+RU1

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5443.90	46.97	6.79	32.90	-30.92	55.74	74.00	18.26	PK	Vertical
2	5460.00	44.47	6.82	32.90	-30.92	53.27	68.20	14.93	PK	Vertical
3	5470.00	44.98	6.84	32.90	-30.91	53.81	68.20	14.39	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5443.90	35.71	6.79	32.90	-30.92	44.48	54.00	9.52	AV	Vertical
2	5460.00	34.26	6.82	32.90	-30.92	43.06	54.00	10.94	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\113
Memo: 11AX20MIMO 5500 RU38+RU1

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5433.62	47.44	6.77	32.90	-30.93	56.18	74.00	17.82	PK	Horizontal
2	5460.00	46.10	6.82	32.90	-30.92	54.90	68.20	13.30	PK	Horizontal
3	5470.00	45.51	6.84	32.90	-30.91	54.34	68.20	13.86	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5433.62	35.29	6.77	32.90	-30.93	44.03	54.00	9.97	AV	Horizontal
2	5460.00	34.95	6.82	32.90	-30.92	43.75	54.00	10.25	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\114
Memo: 11AX20MIMO 5500 RU38+RU1

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5441.80	47.78	6.79	32.90	-30.92	56.55	74.00	17.45	PK	Vertical
2	5460.00	42.97	6.82	32.90	-30.92	51.77	68.20	16.43	PK	Vertical
3	5470.00	45.05	6.84	32.90	-30.91	53.88	68.20	14.32	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5441.80	35.45	6.79	32.90	-30.92	44.22	54.00	9.78	AV	Vertical
2	5460.00	35.61	6.82	32.90	-30.92	44.41	54.00	9.59	AV	Vertical

Note:


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\115
Memo: 11N40MIMO 5510

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5429.96	46.17	4.24	32.90	-30.93	52.38	74.00	21.62	PK	Horizontal
2	5460.00	42.49	4.25	32.90	-30.92	48.72	68.20	19.48	PK	Horizontal
3	5470.00	43.29	4.26	32.90	-30.91	49.54	68.20	18.66	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5429.96	40.08	4.24	32.90	-30.93	46.29	54.00	7.71	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\116
Memo: 11N40MIMO 5510

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5453.06	47.13	4.25	32.90	-30.92	53.36	74.00	20.64	PK	Vertical
2	5460.00	43.79	4.25	32.90	-30.92	50.02	68.20	18.18	PK	Vertical
3	5470.00	48.08	4.26	32.90	-30.91	54.33	68.20	13.87	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5453.06	40.44	4.25	32.90	-30.92	46.67	54.00	7.33	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\117
Memo: 11AC40MIMO 5510

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.67	46.30	4.25	32.90	-30.92	52.53	74.00	21.47	PK	Horizontal
2	5460.00	42.91	4.25	32.90	-30.92	49.14	68.20	19.06	PK	Horizontal
3	5470.00	43.06	4.26	32.90	-30.91	49.31	68.20	18.89	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.67	40.71	4.25	32.90	-30.92	46.94	54.00	7.06	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\118
Memo: 11AC40MIMO 5510

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5455.57	46.37	4.25	32.90	-30.92	52.60	74.00	21.40	PK	Vertical
2	5460.00	44.55	4.25	32.90	-30.92	50.78	68.20	17.42	PK	Vertical
3	5470.00	43.78	4.26	32.90	-30.91	50.03	68.20	18.17	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5455.57	41.08	4.25	32.90	-30.92	47.31	54.00	6.69	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\119
Memo: 11AX40MIMO 5510

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5434.77	45.78	4.25	32.90	-30.93	52.00	74.00	22.00	PK	Horizontal
2	5460.00	43.90	4.25	32.90	-30.92	50.13	68.20	18.07	PK	Horizontal
3	5470.00	43.10	4.26	32.90	-30.91	49.35	68.20	18.85	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5434.77	41.52	4.25	32.90	-30.93	47.74	54.00	6.26	AV	Horizontal

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\120
Memo: 11AX40MIMO 5510

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5442.48	47.39	4.25	32.90	-30.92	53.62	74.00	20.38	PK	Vertical
2	5460.00	42.68	4.25	32.90	-30.92	48.91	68.20	19.29	PK	Vertical
3	5470.00	42.79	4.26	32.90	-30.91	49.04	68.20	19.16	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5442.48	40.66	4.25	32.90	-30.92	46.89	54.00	7.11	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\121
Memo: 11BE40MIMO 5510

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5444.00	45.92	6.79	32.90	-30.92	54.69	74.00	19.31	PK	Horizontal
2	5460.00	42.78	6.82	32.90	-30.92	51.58	68.20	16.62	PK	Horizontal
3	5470.00	43.77	6.84	32.90	-30.91	52.60	68.20	15.60	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5444.00	34.99	6.79	32.90	-30.92	43.76	54.00	10.24	AV	Horizontal
2	5460.00	35.08	6.82	32.90	-30.92	43.88	54.00	10.12	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\122
Memo: 11BE40MIMO 5510

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5451.28	46.44	6.80	32.90	-30.92	55.22	74.00	18.78	PK	Vertical
2	5460.00	43.08	6.82	32.90	-30.92	51.88	68.20	16.32	PK	Vertical
3	5470.00	43.30	6.84	32.90	-30.91	52.13	68.20	16.07	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5451.28	35.73	6.80	32.90	-30.92	44.51	54.00	9.49	AV	Vertical
2	5460.00	35.29	6.82	32.90	-30.92	44.09	54.00	9.91	AV	Vertical


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\123
Memo: 11AX40MIMO 5510 RU53+RU4

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5431.66	46.70	6.77	32.90	-30.93	55.44	74.00	18.56	PK	Horizontal
2	5460.00	43.05	6.82	32.90	-30.92	51.85	68.20	16.35	PK	Horizontal
3	5470.00	44.19	6.84	32.90	-30.91	53.02	68.20	15.18	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5431.66	35.39	6.77	32.90	-30.93	44.13	54.00	9.87	AV	Horizontal
2	5460.00	35.68	6.82	32.90	-30.92	44.48	54.00	9.52	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\124
Memo: 11AX40MIMO 5510 RU53+RU4

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5429.60	46.93	6.76	32.90	-30.93	55.66	74.00	18.34	PK	Vertical
2	5460.00	44.01	6.82	32.90	-30.92	52.81	68.20	15.39	PK	Vertical
3	5470.00	44.44	6.84	32.90	-30.91	53.27	68.20	14.93	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5429.60	35.29	6.76	32.90	-30.93	44.02	54.00	9.98	AV	Vertical
2	5460.00	35.63	6.82	32.90	-30.92	44.43	54.00	9.57	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\125
Memo: 11BE40MIMO 5510 RU53+RU4

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5441.10	45.94	6.78	32.90	-30.92	54.70	74.00	19.30	PK	Horizontal
2	5460.00	42.54	6.82	32.90	-30.92	51.34	68.20	16.86	PK	Horizontal
3	5470.00	43.09	6.84	32.90	-30.91	51.92	68.20	16.28	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5441.10	35.64	6.78	32.90	-30.92	44.40	54.00	9.60	AV	Horizontal
2	5460.00	35.18	6.82	32.90	-30.92	43.98	54.00	10.02	AV	Horizontal


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\126
Memo: 11BE40MIMO 5510 RU53+RU4

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5432.89	46.64	6.77	32.90	-30.93	55.38	74.00	18.62	PK	Vertical
2	5460.00	43.19	6.82	32.90	-30.92	51.99	68.20	16.21	PK	Vertical
3	5470.00	44.56	6.84	32.90	-30.91	53.39	68.20	14.81	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5432.89	35.72	6.77	32.90	-30.93	44.46	54.00	9.54	AV	Vertical
2	5460.00	35.16	6.82	32.90	-30.92	43.96	54.00	10.04	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\127
Memo: 11AC80MIMO 5530

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5456.11	48.09	4.25	32.90	-30.92	54.32	74.00	19.68	PK	Horizontal
2	5460.00	43.77	4.25	32.90	-30.92	50.00	68.20	18.20	PK	Horizontal
3	5470.00	46.40	4.26	32.90	-30.91	52.65	68.20	15.55	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5456.11	42.15	4.25	32.90	-30.92	48.38	54.00	5.62	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\128
Memo: 11AC80MIMO 5530

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5457.02	49.06	4.25	32.90	-30.92	55.29	74.00	18.71	PK	Vertical
2	5460.00	46.70	4.25	32.90	-30.92	52.93	68.20	15.27	PK	Vertical
3	5470.00	47.60	4.26	32.90	-30.91	53.85	68.20	14.35	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5457.02	42.36	4.25	32.90	-30.92	48.59	54.00	5.41	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\129
Memo: 11AX80MIMO 5530

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5440.64	45.87	4.25	32.90	-30.92	52.10	74.00	21.90	PK	Horizontal
2	5460.00	43.50	4.25	32.90	-30.92	49.73	68.20	18.47	PK	Horizontal
3	5470.00	43.24	4.26	32.90	-30.91	49.49	68.20	18.71	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5440.64	41.85	4.25	32.90	-30.92	48.08	54.00	5.92	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\130
Memo: 11AX80MIMO 5530

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5458.75	47.00	4.25	32.90	-30.92	53.23	74.00	20.77	PK	Vertical
2	5460.00	43.25	4.25	32.90	-30.92	49.48	68.20	18.72	PK	Vertical
3	5470.00	43.60	4.26	32.90	-30.91	49.85	68.20	18.35	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5458.75	41.11	4.25	32.90	-30.92	47.34	54.00	6.66	AV	Vertical


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\131
Memo: 11BE80MIMO 5530

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5419.10	46.30	6.74	32.90	-30.93	55.01	74.00	18.99	PK	Horizontal
2	5460.00	45.95	6.82	32.90	-30.92	54.75	68.20	13.45	PK	Horizontal
3	5470.00	43.79	6.84	32.90	-30.91	52.62	68.20	15.58	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5419.10	34.62	6.74	32.90	-30.93	43.33	54.00	10.67	AV	Horizontal
2	5460.00	34.88	6.82	32.90	-30.92	43.68	54.00	10.32	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\132
Memo: 11BE80MIMO 5530

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5435.78	45.98	6.77	32.90	-30.93	54.72	74.00	19.28	PK	Vertical
2	5460.00	43.64	6.82	32.90	-30.92	52.44	68.20	15.76	PK	Vertical
3	5470.00	44.40	6.84	32.90	-30.91	53.23	68.20	14.97	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5435.78	35.06	6.77	32.90	-30.93	43.80	54.00	10.20	AV	Vertical
2	5460.00	35.08	6.82	32.90	-30.92	43.88	54.00	10.12	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\133
Memo: 11AX80MIMO 5530 RU65+RU63

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5411.30	47.17	6.73	32.90	-30.94	55.86	74.00	18.14	PK	Horizontal
2	5460.00	43.99	6.82	32.90	-30.92	52.79	68.20	15.41	PK	Horizontal
3	5470.00	44.90	6.84	32.90	-30.91	53.73	68.20	14.47	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5411.30	34.71	6.73	32.90	-30.94	43.40	54.00	10.60	AV	Horizontal
2	5460.00	34.19	6.82	32.90	-30.92	42.99	54.00	11.01	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\134
Memo: 11AX80MIMO 5530 RU65+RU63

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5416.31	46.76	6.74	32.90	-30.93	55.47	74.00	18.53	PK	Vertical
2	5460.00	42.93	6.82	32.90	-30.92	51.73	68.20	16.47	PK	Vertical
3	5470.00	44.25	6.84	32.90	-30.91	53.08	68.20	15.12	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5416.31	35.84	6.74	32.90	-30.93	44.55	54.00	9.45	AV	Vertical
2	5460.00	35.94	6.82	32.90	-30.92	44.74	54.00	9.26	AV	Vertical


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\135
Memo: 11BE80MIMO 5530 RU65+RU63

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5451.48	46.31	6.80	32.90	-30.92	55.09	74.00	18.91	PK	Horizontal
2	5460.00	43.69	6.82	32.90	-30.92	52.49	68.20	15.71	PK	Horizontal
3	5470.00	42.84	6.84	32.90	-30.91	51.67	68.20	16.53	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5451.48	35.24	6.80	32.90	-30.92	44.02	54.00	9.98	AV	Horizontal
2	5460.00	35.37	6.82	32.90	-30.92	44.17	54.00	9.83	AV	Horizontal


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\136
Memo: 11BE80MIMO 5530 RU65+RU63

Test Graph



Suspected Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5420.74	46.32	6.74	32.90	-30.93	55.03	74.00	18.97	PK	Vertical
2	5460.00	43.35	6.82	32.90	-30.92	52.15	68.20	16.05	PK	Vertical
3	5470.00	43.37	6.84	32.90	-30.91	52.20	68.20	16.00	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5420.74	35.68	6.74	32.90	-30.93	44.39	54.00	9.61	AV	Vertical
2	5460.00	35.76	6.82	32.90	-30.92	44.56	54.00	9.44	AV	Vertical


Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\177
Memo: 11AX160MIMO 5570 POWER:10

Test Graph



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5419.36	46.69	6.74	32.90	-30.93	55.40	74.00	18.60	PK	Horizontal
2	5460.00	44.27	6.82	32.90	-30.92	53.07	68.20	15.13	PK	Horizontal
3	5470.00	43.87	6.84	32.90	-30.91	52.70	68.20	15.50	PK	Horizontal
4	5725.00	42.85	7.34	33.45	-30.81	52.83	68.20	15.37	PK	Horizontal
5	5746.92	46.19	7.38	33.49	-30.80	56.26	68.20	11.94	PK	Horizontal

Final Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5419.36	35.64	6.74	32.90	-30.93	44.35	54.00	9.65	AV	Horizontal
2	5460.00	35.87	6.82	32.90	-30.92	44.67	54.00	9.33	AV	Horizontal


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\178
Memo: 11AX160MIMO 5570

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5453.80	47.03	6.81	32.90	-30.92	55.82	74.00	18.18	PK	Vertical
2	5460.00	43.12	6.82	32.90	-30.92	51.92	68.20	16.28	PK	Vertical
3	5470.00	43.70	6.84	32.90	-30.91	52.53	68.20	15.67	PK	Vertical
4	5725.00	43.44	7.34	33.45	-30.81	53.42	68.20	14.78	PK	Vertical
5	5749.37	46.22	7.39	33.50	-30.80	56.31	68.20	11.89	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5453.80	35.87	6.81	32.90	-30.92	44.66	54.00	9.34	AV	Vertical
2	5460.00	35.86	6.82	32.90	-30.92	44.66	54.00	9.34	AV	Vertical


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\179
Memo: 11BE160MIMO 5570

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5415.65	47.21	6.73	32.90	-30.93	55.91	74.00	18.09	PK	Horizontal
2	5460.00	43.15	6.82	32.90	-30.92	51.95	68.20	16.25	PK	Horizontal
3	5470.00	43.47	6.84	32.90	-30.91	52.30	68.20	15.90	PK	Horizontal
4	5725.00	42.86	7.34	33.45	-30.81	52.84	68.20	15.36	PK	Horizontal
5	5735.41	45.97	7.36	33.47	-30.81	55.99	68.20	12.21	PK	Horizontal

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5415.65	35.87	6.73	32.90	-30.93	44.57	54.00	9.43	AV	Horizontal
2	5460.00	35.39	6.82	32.90	-30.92	44.19	54.00	9.81	AV	Horizontal


Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\180
Memo: 11BE160MIMO 5570

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.81	46.59	6.81	32.90	-30.92	55.38	74.00	18.62	PK	Vertical
2	5460.00	43.30	6.82	32.90	-30.92	52.10	68.20	16.10	PK	Vertical
3	5470.00	43.17	6.84	32.90	-30.91	52.00	68.20	16.20	PK	Vertical
4	5725.00	43.59	7.34	33.45	-30.81	53.57	68.20	14.63	PK	Vertical
5	5741.95	46.40	7.37	33.48	-30.80	56.45	68.20	11.75	PK	Vertical

Final Data List

N O.	Freq. [MHz]	Reading [dBμV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.81	35.67	6.81	32.90	-30.92	44.46	54.00	9.54	AV	Vertical
2	5460.00	35.99	6.82	32.90	-30.92	44.79	54.00	9.21	AV	Vertical

Note:


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\83
Memo: 11AC80MIMO 5610

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.05	4.36	33.45	-30.81	50.05	68.20	18.15	PK	Horizontal
2	5744.90	46.29	4.36	33.49	-30.80	53.34	68.20	14.86	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\84
Memo: 11AC80MIMO 5610

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	44.36	4.36	33.45	-30.81	51.36	68.20	16.84	PK	Vertical
2	5729.48	46.46	4.36	33.46	-30.81	53.47	68.20	14.73	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\85
Memo: 11AX80MIMO 5610

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.52	4.36	33.45	-30.81	50.52	68.20	17.68	PK	Horizontal
2	5747.08	45.65	4.36	33.49	-30.80	52.70	68.20	15.50	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\86
Memo: 11AX80MIMO 5610

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	44.31	4.36	33.45	-30.81	51.31	68.20	16.89	PK	Vertical
2	5730.98	46.33	4.36	33.46	-30.81	53.34	68.20	14.86	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\125
Memo: 11BE80MIMO 5610

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	44.42	7.34	33.45	-30.81	54.40	68.20	13.80	PK	Horizontal
2	5730.53	46.16	7.35	33.46	-30.81	56.16	68.20	12.04	PK	Horizontal


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\126
Memo: 11BE80MIMO 5610

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	42.86	7.34	33.45	-30.81	52.84	68.20	15.36	PK	Vertical
2	5738.70	47.55	7.37	33.48	-30.80	57.60	68.20	10.60	PK	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\177
Memo: 11BE80MIMO 5610 RU66+RU62

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	45.07	7.34	33.45	-30.81	55.05	68.20	13.15	PK	Horizontal
2	5734.30	46.03	7.36	33.47	-30.81	56.05	68.20	12.15	PK	Horizontal


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\178
Memo: 11BE80MIMO 5610 RU66+RU62

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.26	7.34	33.45	-30.81	53.24	68.20	14.96	PK	Vertical
2	5731.13	45.95	7.35	33.46	-30.81	55.95	68.20	12.25	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\87
Memo: 11N40MIMO 5670

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	44.45	4.36	33.45	-30.81	51.45	68.20	16.75	PK	Horizontal
2	5735.02	46.68	4.36	33.47	-30.81	53.70	68.20	14.50	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\88
Memo: 11N40MIMO 5670

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.83	4.36	33.45	-30.81	50.83	68.20	17.37	PK	Vertical
2	5732.60	46.79	4.36	33.47	-30.81	53.81	68.20	14.39	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\89
Memo: 11AC40MIMO 5670

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.10	4.36	33.45	-30.81	50.10	68.20	18.10	PK	Horizontal
2	5737.71	46.04	4.36	33.48	-30.80	53.08	68.20	15.12	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\90
Memo: 11AC40MIMO 5670

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.11	4.36	33.45	-30.81	50.11	68.20	18.09	PK	Vertical
2	5739.75	46.70	4.36	33.48	-30.80	53.74	68.20	14.46	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\91
Memo: 11AX40MIMO 5670

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	44.05	4.36	33.45	-30.81	51.05	68.20	17.15	PK	Horizontal
2	5748.52	46.20	4.36	33.50	-30.80	53.26	68.20	14.94	PK	Horizontal

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.