

FCC ID: 2AX5VHUB24GJafa

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

Operation Frequency: GFSK: 905 MHz~926.5MHz

Antenna Type: Antenna 1Type: Planar Inverted L- Antenna(ocw=120k)

Antenna 2Type: Planar Inverted F- Antenna(ocw=120k)

Antenna 3Type: Planar Inverted F- Antenna(ocw=140k)

Antenna 4Type: Planar Inverted F- Antenna(ocw=140k)

R=20cm

Module 1:ant1

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
905.00	GFSK-120K	10.605	10.5±1	11.5	14.125	-5.00	0.32	0.0009	0.60
915.85		10.49	10.5±1	11.5	14.125	-5.00	0.32	0.0009	0.61
926.50		10.22	10.5±1	11.5	14.125	-5.00	0.32	0.0009	0.62

ant2

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
905.00	GFSK-120K	17.22	17±1	18	63.096	-6.00	0.25	0.0032	0.60
915.85		16.895	17±1	18	63.096	-6.00	0.25	0.0032	0.61
926.50		16.666	17±1	18	63.096	-6.00	0.25	0.0032	0.62

Module 2: ant3

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
905.00	GFSK-140K	16.507	16.5±1	17.5	56.234	-6.00	0.25	0.0028	0.60
915.85		16.167	16.5±1	17.5	56.234	-6.00	0.25	0.0028	0.61
926.50		15.853	16.5±1	17.5	56.234	-6.00	0.25	0.0028	0.62

ant4

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
905.00	GFSK-140K	16.075	16	17	50.119	-6.00	0.25	0.0025	0.60
915.85		15.721	16	17	50.119	-6.00	0.25	0.0025	0.61
926.50		15.434	16	17	50.119	-6.00	0.25	0.0025	0.62

Conclusion:

For the max result : $0.0032 \leq 0.60$ for Max Power Density, compliance RF exposure..

SIMULTANEOUS TRANSMISSIONS

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE. To comply with the MPE, the fraction of the MPE in terms of E^2 , H^2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity. In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

Max. SIMULTANEOUS TRANSMISSIONS MODE

Band						MIMO		Verdict
	Max Conducted	Antenna	Separation distance (cm)	Evaluation result	Power density	Evaluation result	Power density Limits	
	(dBm)	Gain (dBi)		(mW/cm ²)	(mW/cm ²)			
SRD 905 + WCDMA Band 2	17.22	-6	20	0.010489	0.603	0.098224	1	PASS
	23.5	-1	20	0.044537	0.551			
SRD 905 + WCDMA Band 4	17.22	-6	20	0.010489	0.603	0.061932	1	PASS
	23.5	-1	20	0.044537	1			
SRD 905 + WCDMA Band 5	17.22	-6	20	0.010489	0.603	0.061932	1	PASS
	23.5	-1	20	0.044537	1			
SRD 905 + LTE Band 2	17.22	-6	20	0.010489	0.603	0.067366	1	PASS
	24	-1	20	0.049971	1			
SRD 905 + LTE Band 4	17.22	-6	20	0.010489	0.603	0.067366	1	PASS
	24	-1	20	0.049971	1			
SRD 905 + LTE Band 12	17.22	-6	20	0.010489	0.603	0.124629	1	PASS
	24	-1	20	0.049971	0.466			

Alex

Signature:

Date: 2023/08/10

NAME AND TITLE (Please print or type): Alex Li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.