



PRODUCT / PROCESS CHANGE NOTIFICATION

PCN-000780

Date: April 8, 2022

P1/2

Semtech Corporation, 200 Flynn Road, Camarillo CA 93012

Change Details

Part Number(s) Affected: SX1231IMLTRT SX1231HIMLTRT SX1232IMLTRT SX1233IMLTRT SX1239IMLTRT	Customer Part Number(s) Affected: <input checked="" type="checkbox"/> N/A
---	--

Description, Purpose and Effect of Change:

For business continuity purposes, Semtech will start using qualified second-sources for assembly of the above-mentioned parts.

The assembly of these parts are currently performed at Carsem (Malaysia). Second-source assembly has been qualified at Greatek (Taiwan).

Change Classification	<input checked="" type="checkbox"/> Major <input type="checkbox"/> Minor	Impact to Form, Fit, Function	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Impact to Data Sheet	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	New Revision or Date	<input checked="" type="checkbox"/> N/A

Impact to Performance, Characteristics or Reliability:

No impact to performance, characteristics or reliability is expected as a result of this change.

Implementation Date	July 8, 2022	Work Week	2227
Last Time Ship (LTS) Of unchanged product	N/A	Affecting Lot No. / Serial No. (SN)	N/A
Sample Availability	April 8, 2022 (SX1231IMLTRT, SX1232IMLTRT)	Qualification Report Availability	April 8, 2022

Supporting Documents for Change Validation/Attachments:

- From-To analysis
- Reliability qualification report available upon request.



PRODUCT / PROCESS CHANGE NOTIFICATION

PCN-000780

Date: April 8, 2022

P2/2

Issuing Authority	
Semtech Business Unit:	Wireless and Sensing Product Group
Semtech Contact Info:	<p>Anne Lévy-Mandel Sr Quality Assurance Manager, Wireless & Sensing Products</p> <p>Semtech Neuchâtel SA Gouttes d'Or 40 CH-2000 Neuchâtel</p> <p>Alevymandel@semtech.com</p> <p>Office: + 41 32 729 40 61 Fax: + 41 32 729 40 01</p> 
FOR FURTHER INFORMATION & WORLDWIDE SALES COVERAGE: http://www.semtech.com/contact/index.html#support	



PCN No. 000780

Qualification of Greatek Taiwan as a second source Assembly manufacturer for LORA and ISM products

Introduction


- ❑ In order to increase the overall production capacity, Semtech is qualifying Greatek as a second source for assembly and test. Assembly is currently performed at Carsem.

- ❑ The change affect applicable to products:
SX1231IMLTRT & derivatives, SX1232IMLTRT, SX1233IMLTRT, SX1239IMLTRT

- ❑ Qualification Vehicle selected is SX1276IMLTRT

- ❑ Schedule for Implementation
Passing REL qualification under Rel job# 7140.

SEMTECH Package Outline on SX1231IMLTRT/ SX1232IMLTRT/ SX1233IMLTRT/ SX1239IMLTRT (Carsem and Greatek)



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	0.80	-	1.00
A1	0.00	-	0.05
A2	-	(0.20)	-
b	0.25	0.30	0.35
D	4.90	5.00	5.10
D1	3.20	3.25	3.30
E	4.90	5.00	5.10
E1	3.20	3.25	3.30
e	0.65 BSC		
L	0.35	0.40	0.45
N	24		
aaa	0.08		
bbb	0.10		

**No Change in
Package Outline.**

NOTES:

1. CONTROLLING DIMENSIONS ARE IN MILLIMETERS (ANGLES IN DEGREES).
2. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

BOM (Carsem vs Greatek)




Carsem (Old)				Greatek (New)			
Epoxy	Leadframe	Wire Type	Mold compound	Epoxy	Leadframe	Wire Type	Mold compound
QMI519 Conductive epoxy	AgCu LDF	1.0 mils Au wire	G770HCD	EN-4900 Conductive epoxy	AgCu LDF	1.0 mils Au wire	G700HA


- BOM for both supplier (Greatek/Carsem) is MSL3 qualified.
- Carsem uses conductive epoxy of QMI519. Greatek uses EN-4900 which is also conductive epoxy. Both epoxy are supplier standard BOM with proven MSL3 performance.
- Lead frame base material and finishing is identical for both supplier. These are supplier standard BOM with proven MSL1 performance.
- Wire for both supplier is identical. 1.0mils Au wire.
- Mold compound for Carsem is G770HCD and Greatek is G700HA. This is supplier standard BOM with proven MSL3 performance. Both BOM running >5years high volume production. Greatek has shipped >100Mu with G700HA on QFN/DFN products.
- BOM selection between Carsem and Greatek is to ensure each subcon use their previously qualified process. This avoids risk on new assembly process.

Wire Bonding sequence SX1232IMLTRT (Carsem vs Greatek)

Carsem (OLD)




Greatek (NEW)




- Both supplier – Carsem and Greatek are bonding the down bond wires as 1st priority although there is some difference on its down bond sequence.
- Followed by those I/O pad wires. Although bonding on I/O pad wires were also having some differences. This would not impacted its electrical performance.

Wire Bonding sequence SX1231IMLTRT, SX1233IMLTRT, SX1239IMLTRT (Carsem vs Greatek)

Carsem (OLD)




Greatek (NEW)



- Both supplier – Carsem and Greatek are bonding the down bond wires as 1st priority. – Same sequence.
- Followed by those I/O pad wires. Although bonding on I/O pad wires were having some differences. This would not impacted its electrical performance.

Carrier tape 5x5 comparison (Carsem Vs Greatek)

Carrier tape Carsem - CPAK (Old)				Carrier tape Greatek - Advantek (New)			
Ao	Bo	Ko	W	Ao	Bo	Ko	W
5.25 +/- 0.1	5.25 +/- 0.1	1.1 +/- 0.1	12	5.25 +/- 0.1	5.25 +/- 0.1	1.1 +/- 0.1	12




Pkg size	Carrier tape (mm)					Reel		Minimum Trailer Length (mm)	Minimum Leader Length (mm)	QTY per Reel
	Tape Width (W)	Pocket Pitch (P)	Ao	Bo	Ko	Reel Size (in)	Reel Width (mm)			
5x5	12	8	5.25	5.25	1.10	7/13	12.4	200/400	400	500/3000

Although carrier tape supplier were different but critical dimension were no difference.

Carrier tape for Greatek 5x5 (New)



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
1	DRAWING FORMAT CHANGE	7/24/01	BTH
2	TAPE WIDTH WAS 12.04/-0.3	03/28/12	JH
3	ADD I MATERIAL	10/14/14	JH



SECTION A - A

Ao = 5.25
Bo = 5.25
Ko = 1.10

NOTES:


1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE ± 0.2
2. CAMBER IN COMPLIANCE WITH EIA 481
3. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE

PART#	T	MATERIAL	DRAWING NO.
ML0505-AC	0.30	PS+C	T102531AT
ML0505-AD	0.30	PS+C	T108759BT
ML0505-AI	0.25	PS+C	T111798BT



TITLE ADVANTEK PART DRAWING NUMBER ML0505-A CARRIER TAPE			
TOLERANCES - UNLESS NOTED 1PL ± 0.2 2PL ± 0.10	MATERIAL SEE TABLE	ALL DIMENSIONS IN MILLIMETERS	DWG SIZE B
DRAWN BY TMD/BTH	DATE 10/07/99	SCALE 4:1	SHEET 1 OF 1
REFERENCE NO. T-9204	DWG NO. SEE TABLE	REV 3	

Carrier tape for Carsem 5x5 (Old)



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO C-PAK PTE LTD