# FCC ID: 2AX5VLIFEQUA-NA

## **RF EXPOSURE EVALUATION**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximu	m Permissible	Exposure	(MPE)
		Expoone	(

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)				
(A) Limits for Occupational/Controlled Exposure								
0.3-3.0	614	1.63	*100	6				
3.0-30	1842/1	4.89/1	f *900/f <sup>2</sup>	6				
30-300	61.4	0.163	1.0	6				
300-1,500			f/300	6				
1,500-100,000			5	6				
(B) Limits for General Population/Uncontrolled Exposure								
0.3-1.34	614	1.63	*100	30				
1.34-30	824/1	2.19/1	*180/f <sup>2</sup>	30				
30-300	27.5	0.073	0.2	30				
300-1,500			f/1500	30				
1,500-100,000			1.0	30				

f = frequency in MHz \* = Plane-wave equivalent power density

## MPE Calculation Method

$$\mathsf{E}(\mathsf{V/m}) = \frac{\sqrt{30*P*G}}{d}$$
 Power Density:  $Pd(\mathsf{W/m^2}) = \frac{E^2}{377}$ 

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30*P*G}{377*D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

### Measurement Result

Operation Frequency: GFSK: 905 MHz~926.5MHz Antenna Type: Antenna Type: Planar Inverted L- Antenna Antenna gain: Antenna:-5 dBi R=20cm

### OCW=120KHz

Channel Freq. (MHz)	Channel	conducted power	Tune-up power (dBm)	Мах		Antenna		Evaluation result	Power density Limits	
	modulation	(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)	
				(dBm)	(mW)	(dBi)	Numeric	(IIIVV/CIIIZ)	(IIIVV/CIII2)	
ĺ	905.00	5.85 GFSK	12.66	12±1	13	19.953	-5.00	0.32	0.0013	0.60
ſ	915.85		12.09	12±1	13	19.953	-5.00	0.32	0.0013	0.61
	926.50		12.25	12±1	13	19.953	-5.00	0.32	0.0013	0.62

#### **Conclusion:**

For the max result : 0.0013≤ 0.60 for Max Power Density, compliance RF exposure..

Note: This product does not support simultaneous delivery.

Alex

Signature:

Date: 2022/12/7

NAME AND TITLE (Please print or type): Alex Li/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.