


RF Exposure Evaluation Report

Application No.: SZCR2103020046AT
Applicant: AJAX SYSTEMS CYPRUS HOLDINGS LTD
Address of Applicant: Ifigeneias, 17, Strovolos Nicosia 2007 Cyprus (Republic Of)
Manufacturer: AJAX SYSTEMS MANUFACTURING LIMITED LIABILITY COMPANY
Address of Manufacturer: Sklyarenka, 5, Kyiv, 04073, Ukraine
Factory: AJAX SYSTEMS MANUFACTURING LIMITED LIABILITY COMPANY
Address of Factory: Sklyarenka, 5, Kyiv, 04073, Ukraine
Equipment Under Test (EUT):
Product Name: Wireless curtain motion detector
Model No.: Ajax MotionProtect Curtain (9NA)
Trade Mark: AJAX
IC: 26860-MOPRCUNA1
Standards: RSS-102 Issue 5 March 2015 Amendment 1 (February 2, 2021)
Date of Receipt: 2021-03-16
Date of Test: 2021-03-24 to 2021-04-02
Date of Issue: 2021-04-07

Test Result:	PASS*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager





2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-04-07		Original

Authorized for issue by:			
		<i>Edison Li</i>	
		Edison Li/Project Engineer	
		<i>Eric Fu</i>	
		Eric Fu/Reviewer	





3 Contents

1	COVER PAGE.....	1
2	VERSION.....	2
3	CONTENTS.....	3
4	GENERAL INFORMATION	4
4.1	GENERAL DESCRIPTION OF EUT.....	4
4.2	TEST LOCATION	5
4.3	TEST FACILITY	5
4.4	DEVIATION FROM STANDARDS	5
4.5	ABNORMALITIES FROM STANDARD CONDITIONS	5
4.6	OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5	RF EXPOSURE EVALUATION.....	6
5.1	RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1	Limits.....	6
5.1.2	Test Procedure.....	7
5.1.3	EUT RF Exposure Evaluation.....	7



4 General Information

4.1 General Description of EUT

Power supply:	DC 3V Lithium battery(CR123A)
Internal Source:	More than 108MHz
Operation Frequency:	905MHz to 926.5MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK
Number of Channels:	The number of available frequency hopping channels of this device is 103, only 101 channels are used in normal operation and constantly involved, 2 is reserve in case of jamming.
Antenna Type:	PCB
Antenna Gain:	-2.3dBi
FVIN:	N/A
HMN:	N/A
Hardware Version:	MPC.001.601.000V8
Software Version:	6.53.1.8
IC:	26860-MOPRCUNA1
HVIN:	Ajax MotionProtect Curtain (9NA)
Series Number:	42e2a9061
Test Software:	N/A
Test Software version:	N/A
RF Power Setting:	Default



4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to RSS-102 Issue 5:

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}

Note: *f* is frequency in MHz.
*Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).

Table 6: RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²³	170	180	-	Instantaneous*
0.1-10	-	1.6/ <i>f</i>	-	6**
1.29-10	193/ <i>f</i> ^{0.5}	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ <i>f</i> ^{0.25}	0.3444/ <i>f</i> ^{0.25}	44.72/ <i>f</i> ^{0.5}	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 <i>f</i> ^{0.25}	0.04138 <i>f</i> ^{0.25}	0.6455 <i>f</i> ^{0.5}	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ <i>f</i> ^{1.2}
150000-300000	0.354 <i>f</i> ^{0.5}	9.40 x 10 ⁻⁴ <i>f</i> ^{0.5}	3.33 x 10 ⁻⁴ <i>f</i>	616000/ <i>f</i> ^{1.2}

Note: *f* is frequency in MHz.
*Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).



F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in W/m^2

P_{out} = output power to antenna in W

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in m.

For Uncontrolled Environment, the limit of MPE is $0.02619 \cdot f^{0.6834} W/m^2$. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

5.1.3 EUT RF Exposure Evaluation

1) Test Results

The max tune-up tolerance power Into Antenna & RF Exposure Evaluation Distance:

Antenna	Max Antenna Gain (dBi)	Max Antenna Gain (Numeric)	Max tune-up tolerance power (dBm)	Max tune-up Tolerance Power to Antenna(W)	Power Density at R = 20 cm (W/m^2)	Limit (W/m^2)	MPE Ratios	Result
1	-2.3	0.59	8.44	0.0070	0.0082	2.7461	0.0030	PASS

Note: Refer to report No. SZCR210302004602 or EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement; the limit range of 905MHz-926.5MHz is $2.7461 \sim 2.7905 W/m^2$, The max PSD should need to be less than or equal to the minimum limit.

- End of the Report -

