FCC ID: 2AX5VREX-NA

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)								
(A) Limits for Occupational/Controlled Exposure												
0.3-3.0	614	1.63	*100	6								
3.0-30	1842/1	4.89/1	*900/f ²	6								
30-300	61.4	0.163	1.0	6								
300-1,500			f/300	6								
1,500-100,000			5	6								
(B) Limits for General Population/Uncontrolled Exposure												
0.3-1.34	614	1.63	*100	30								
1.34-30	824/1	2.19/1	*180/f ²	30								
30-300	27.5	0.073	0.2	30								
300-1,500			f/1500	30								
1,500-100,000			1.0	30								

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E (V/m) = \frac{\sqrt{30*P*G}}{d}$$
 Power Density: $Pd (W/m^2) = \frac{E^2}{377}$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30*P*G}{377*D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

Operation Frequency: GFSK: 905 MHz~926.5MHz

Antenna1Type: Planar Inverted F- Antenna Antenna2Type: Planar Inverted L- Antenna

Antenna 1:-5 dBi Antenna 2:-6 dBi

R=20cm GFSK:

Channel Freq. (MHz)	Channel	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
	Freq. (MHz)		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
					(dBm)	(mW)	(dBi)	Numeric	(IIIVV/CIIIZ)	(IIIVV/CIIIZ)
•	905.00		13.069	13±1	14	25.119	-5.00	0.32	0.0016	0.60
	915.85	GFSK	11.137	12±1	13	19.953	-5.00	0.32	0.0013	0.61
	926.50		12.471	12±1	13	19.953	-5.00	0.32	0.0013	0.62

Conclusion:

For the max result : 0.0016≤ 0.60 for Max Power Density, compliance RF exposure..

Signature: Date: 2021/08/09

NAME AND TITLE (Please print or type): Alex Li/Manager

Alex

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.