



RF EXPOSURE EVALUATION

FCC ID: 2AX60-X5

| | | |
|---------------------|---|-------------------------------|
| Product Name | : | Wireless Microphone |
| Model Name | : | X5 |
| Additional model | : | X5S,X5 PRO |
| Bluetooth Version | : | BT BDR and EDR |
| Operating frequency | : | 2402-2480MHz |
| Numbers of Channel | : | 79 channels for BDR |
| Antenna Type | : | Ceramic Antenna |
| Antenna Gain | : | 1.54dBi |
| Type of Modulation | : | GFSK, $\pi/4$ -DQPSK, 8DPSK |
| Power supply | : | Input: DC5V $\overline{=}$ 2A |
| Hardware Version | : | N/A |
| Software Version | : | N/A |

Model difference:

X5, X5S, X5 PRO only the appearance color is different.



Standard Requirement

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4. 3. 1.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g SAR extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is < 5 mm, a distance of 5mm is applied to determine SAR test exclusion. Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to quality for TCB approval.

| Channel (MHz) | Maximum output power (dBm) | Tune up tolerance (dBm) | Max Tune Up Power (mW) | Distance (mm) | Calculation results | Limit | Operating Mode |
|---------------|----------------------------|-------------------------|------------------------|---------------|---------------------|-------|----------------|
| 2402 | -3.28 | -3.28 ± 1 | 0.591562 | 5 | 0.183365 | 3 | BDR |

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

Signature

Ronnie Liu

EMC Manager

Date: 2023-03-10