

RF Exposure Evaluation Report

Equipment under Test: Smart AI Camera

Model No. : AIPC-02-SW, AIPC-01-SW

FCC ID : 2AX6X-AIPC-02-SW

Manufacturer : SpotCam Co. Ltd.

Applicant : Simpnic co., Ltd.

Address : 16F.-6, No. 79, Sec. 1, Xintai 5th Rd., Xizhi Dist.,
New Taipei City 221006, Taiwan (R.O.C.)

Date of Receipt : April 16, 2021

Date of Report : July 23, 2021

Prepared by

Central Research Technology Co.

EMC Test Laboratory



No.11, Lane41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C.

1 Requirement for Compliance

According to FCC 2.1093 and 1.1310, exposure requirement is

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Formula:

$$S = \frac{P_T G}{4\pi d^2}$$

S=Power Density(mW/cm²)

P= power input to antenna(mW)

G=Antenna Gain

d= Distance(cm)

Frequency Range (MHz)	Maximum Power		Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
	(dBm)	(mW)				
2412~2462	19.94	98.6	2.38	20	0.03	1

2 Result

According to result, MPE is PASS.