



12. Hopping Channel Separation

12.1 Block Diagram Of Test Setup

EUT	SPECTRUM	
	ANALYZER	

12.2 Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 0.125W.

12.3 Test procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW = 30kHz. VBW = 100kHz , Span = 2.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

12.4 Test Result

Mode	Test Channel	Separation (MHz)	Limit(MHz)	Result
1-DH1	Low	1.002	0.607	PASS
1-DH1	Middle	1.000	0.680	PASS
1-DH1	High •••••	1.000	0.665	PASS
2-DH1	Low	0.998	0.845	PASS
2-DH1	Middle	1.000	0.845	PASS
2-DH1	High	1.000	0.841	PASS
3-DH1	Low	0.998	0.815	PASS
3-DH1	Middle	1.000	0.821	PASS
3-DH1	High	1.000	0.825	PASS

No.: BCTC/RF-EMC-005 Page: 62 of 85 / / / / Edition: B.2





























No.: BCTC/RF-EMC-005



13. Number Of Hopping Frequency

13.1 Block Diagram Of Test Setup

EUT SPECTRUM ANALYZER

13.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

13.3 Test procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
- 4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz, Sweep=auto;


13.4 Test Result

Condition Mode		Hopping Number	Limit	Verdict	
NVNT	1-DH1	79	15	Pass	
NVNT	2-DH1	79	15	Pass	
NVNT	3-DH1	79	15	Pass	


No.: BCTC/RF-EMC-005 Page: 68 of 85 / / / / Edition: B.2
















14. Dwell Time

14.1 Block Diagram Of Test Setup

EUT	SPECTRUM		
	ANALYZER		

14.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

14.3 Test procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set spectrum analyzer span = 0. Centred on a hopping channel;
- 3. Set RBW = 1MHz and VBW = 3MHz.Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- 4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

14.4 Test Result


Mode	Frequency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
1-DH1	2441	0.376	117.688	313	31600	400	Pass
1-DH3	2441	1.631	256.067	157	31600	400	Pass
1-DH5	2441	2.88	313.92	109	31600	400	Pass
2-DH1	2441	0.386	122.362	317	31600	400	Pass
2-DH3	2441	1.638	260.442	159	31600	400	Pass
2-DH5	2441	2.886	297.258	103	31600	400	Pass
3-DH1	2441	0.387	122.679	317	31600	400	Pass
3-DH3	2441	1.636	253.58	155	31600	400	Pass
3-DH5	2441	2.888	303.24	105	31600	400	Pass


Note: Total Dwell Time (ms) = Pulse Time (ms)*Burst Count

No.: BCTC/RF-EMC-005 Page: 71 of 85 / / / / Edition; B.2




















































15. Antenna Requirement

15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.2 Test Result

The EUT antenna is Internal antenna, fulfill the requirement of this section.



No.: BCTC/RF-EMC-005



16. EUT Photographs

EUT Photo



NOTE: Appendix-Photographs Of EUT Constructional Details





17. EUT Test Setup Photographs

Conducted emissions



Radiated Measurement Photos




No.: BCTC/RF-EMC-005 Page: 83 of 85 / / / Edition: B.2











STATEMENT

- 1. The equipment lists are traceable to the national reference standards.
- 2. The test report can not be partially copied unless prior written approval is issued from our lab.
- 3. The test report is invalid without the "special seal for inspection and testing".
- 4. The test report is invalid without the signature of the approver.
- 5. The test process and test result is only related to the Unit Under Test.
- 6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
- 7. The quality system of our laboratory is in accordance with ISO/IEC17025.
- 8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END ****

No.: BCTC/RF-EMC-005 Page: 85 of 85 / / / / Edition; B.2