

# FCC Test Report

## (PART 90S)

**Report No.:** RFBGSN-WTW-P20070580-5

**FCC ID:** 2AX8C-3544

**Test Model:** FL44TE

**Received Date:** Jul. 29, 2020

**Test Date:** Aug. 06, 2020 ~ Nov. 17, 2020

**Issued Date:** Nov. 30, 2020

**Applicant:** Amazon.com Services LLC

**Address:** 410 Terry Ave N Seattle, WA 98109 650 694 8333

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, Taiwan

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 Summary of Test Results</b> .....	<b>5</b>
2.1 Measurement Uncertainty .....	5
2.2 Test Site and Instruments .....	6
<b>3 General Information</b> .....	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Configuration of System under Test .....	8
3.2.1 Description of Support Units .....	8
3.3 Test Mode Applicability and Tested Channel Detail .....	9
3.4 General Description of Applied Standards and references .....	10
<b>4 Test Types and Results</b> .....	<b>11</b>
4.1 Output Power Measurement .....	11
4.1.1 Limits of Output Power Measurement .....	11
4.1.2 Test Procedures .....	11
4.1.3 Test Setup .....	12
4.1.4 Test Results .....	13
4.2 Modulation Characteristics Measurement .....	16
4.2.1 Limits of Modulation Characteristics .....	16
4.2.2 Test Setup .....	16
4.2.3 Test Procedure .....	16
4.2.4 Test Results .....	16
4.3 Frequency Stability Measurement .....	17
4.3.1 Limits of Frequency Stability Measurement .....	17
4.3.2 Test Procedure .....	17
4.3.3 Test Setup .....	17
4.3.4 Test Results .....	18
4.4 Occupied Bandwidth Measurement .....	22
4.4.1 Limits of Occupied Bandwidth Measurement .....	22
4.4.2 Test Procedure .....	22
4.4.3 Test Setup .....	22
4.4.4 Test Results .....	23
4.5 Emission Mask Measurement .....	25
4.5.1 Limits of Emission Mask Measurement .....	25
4.5.2 Test Setup .....	25
4.5.3 Test Procedures .....	25
4.5.4 Test Results .....	26
4.6 Conducted Spurious Emissions .....	34
4.6.1 Limits of Conducted Spurious Emissions Measurement .....	34
4.6.2 Test Setup .....	34
4.6.3 Test Procedure .....	34
4.6.4 Test Results .....	35
4.7 Radiated Emission Measurement .....	39
4.7.1 Limits of Radiated Emission Measurement .....	39
4.7.2 Test Procedure .....	39
4.7.3 Deviation from Test Standard .....	39
4.7.4 Test Setup .....	40
4.7.5 Test Results .....	41
<b>5 Pictures of Test Arrangements</b> .....	<b>55</b>
<b>Appendix – Information of the Testing Laboratories</b> .....	<b>56</b>

### Release Control Record

Issue No.	Description	Date Issued
RFBGSN-WTW-P20070580-5	Original Release	Nov. 30, 2020

## 1 Certificate of Conformity

**Product:** Fleet Edge  
**Brand:** N/A  
**Test Model:** FL44TE  
**Sample Status:** Engineering Sample  
**Applicant:** Amazon.com Services LLC  
**Test Date:** Aug. 06, 2020 ~ Nov. 17, 2020  
**Standards:** FCC Part 90, Subpart I, S  
FCC Part 2

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Vera Huang , Date: Nov. 30, 2020  
Vera Huang / Specialist

Approved by : Dylan Chiou , Date: Nov. 30, 2020  
Dylan Chiou / Senior Project Engineer

## 2 Summary of Test Results

Applied Standard: FCC Part 90 & Part 2 (LTE 26)			
FCC Clause	Test Item	Result	Remarks
2.1046 90.635 (b)	Effective Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement.
2.1055 90.213	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 90.209	Occupied Bandwidth	Pass	Meet the requirement of limit.
90.691	Emission Masks	Pass	Meet the requirement of limit.
2.1051 90.691	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 90.691	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -4.84 dB at 40.67 MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	9 kHz ~ 30 MHz	3.04 dB
	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

## 2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Mar. 18, 2020	Mar. 17, 2021
Spectrum Analyzer Agilent	N9010A	MY52220314	Dec. 12, 2019	Dec. 11, 2020
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-969	Nov. 24, 2019	Nov. 23, 2020
BILOG Antenna SCHWARZBECK	VULB 9168	9168-472	Nov. 08, 2019	Nov. 07, 2020
			Nov. 06, 2020	Nov. 05, 2021
Fixed Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	Apr. 14, 2020	Apr. 13, 2021
BILOG Antenna SCHWARZBECK	VULB 9168	9168-160	Nov. 07, 2019	Nov. 06, 2020
			Nov. 06, 2020	Nov. 05, 2021
HORN Antenna SCHWARZBECK	9120D	9120D-1169	Nov. 24, 2019	Nov. 23, 2020
MXG Vector signal generator Agilent	N5182B	MY53050430	Nov. 25, 2019	Nov. 24, 2020
Preamplifier EMCI	EMC001340	980201	Oct. 14, 2019	Oct. 13, 2020
			Oct. 21, 2020	Oct. 20, 2021
Preamplifier EMCI	EMC 012645	980115	Oct. 08, 2019	Oct. 07, 2020
			Oct. 07, 2020	Oct. 06, 2021
Preamplifier EMCI	EMC 330H	980112	Oct. 08, 2019	Oct. 07, 2020
			Oct. 07, 2020	Oct. 06, 2021
RF Coaxial Cable EMCI	EMC104-SM-SM-8000	180409	Jan. 18, 2020	Jan. 17, 2021
RF Coaxial Cable HUBER+SUHNNER	SUCOFLEX 104	EMC104-SM-SM-1000(140807)	Oct. 08, 2019	Oct. 07, 2020
			Oct. 07, 2020	Oct. 06, 2021
RF Coaxial Cable WOKEN	8D-FB	Cable-Ch10-01	Oct. 08, 2019	Oct. 07, 2020
			Oct. 07, 2020	Oct. 06, 2021
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Radio Communication Analyzer Anritsu	MT8821C	6201462755	Feb. 13, 2020	Feb. 12, 2021
Radio Communication Analyzer Anritsu	MT8820C	6201300640	Aug. 19, 2019	Aug. 18, 2021
Temperature & Humidity Chamber GIANT FORCE	GTH-120-40-CP-AR	MAA1306-019	Sep. 09, 2020	Sep. 08, 2021
DC power supply Keysight	U8002A	MY56330015	NA	NA
Digital Multimeter Fluke	87-III	70360742	Jun. 23, 2020	Jun. 22, 2021

Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 10.

### 3 General Information

#### 3.1 General Description of EUT

<b>Product</b>	Fleet Edge	
<b>Brand</b>	N/A	
<b>Test Model</b>	FL44TE	
<b>Status of EUT</b>	Engineering Sample	
<b>Power Supply Rating</b>	12 Vdc (Power Supply)	
<b>Modulation Type</b>	LTE	QPSK, 16QAM
<b>Frequency Range</b>	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	814.7 ~ 823.3 MHz
	LTE Band 26 (Channel Bandwidth: 3 MHz)	815.5 ~ 822.5 MHz
	LTE Band 26 (Channel Bandwidth: 5 MHz)	816.5 ~ 821.5 MHz
	LTE Band 26 (Channel Bandwidth: 10 MHz)	819 MHz
<b>Emission Designator</b>	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	1M09D7W
	LTE Band 26 (Channel Bandwidth: 3 MHz)	2M70G7D
	LTE Band 26 (Channel Bandwidth: 5 MHz)	4M49G7D
	LTE Band 26 (Channel Bandwidth: 10 MHz)	8M99D7W
<b>Max. ERP Power</b>	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	54.08 mW
	LTE Band 26 (Channel Bandwidth: 3 MHz)	55.34 mW
	LTE Band 26 (Channel Bandwidth: 5 MHz)	56.75 mW
	LTE Band 26 (Channel Bandwidth: 10 MHz)	56.75 mW
<b>Antenna Type</b>	Refer to Note as below	
<b>Accessory Device</b>	N/A	
<b>Data Cable Supplied</b>	N/A	

Note:

1. The information of module collocated in this EUT is listed as below.

Product	Brand	Model
BT/WLAN Module	Intel	9560NGW
WWAN Module	Quectel	EM06-A


2. The antenna information is listed as below.

Ant.	Brand	Model	Antenna Type	Antenna Gain (dBi)	Remark
				LTE 26	
1	TAOGLAS	MA491.A.BICG.005.gb	Multiband Antennas	-3	Main Antenna
2	TAOGLAS	MA491.A.BICG.005.gb	Multiband Antennas	-3.4	Diversity Antenna

3. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

### 3.2 Configuration of System under Test



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Keyboard	DELL	RT7D50	CN-0J4624-37172-44T-000M	FCC DOC Approved	--
B	Mouse	DELL	MS111-L	N/A	N/A	--
C	Monitor	ViewSonic	VX2457-MHD	UG0182942333	N/A	--
D	Communication Tester	R&S	CMU200	123295	N/A	For WCDMA
		ANRITSU	MT8821C	6201502978	NA	For LTE
E	Power Supply	NA	NA	NA	NA	--
F	WLAN&WWAN Antenna	TAOGLAS	MA491.A.BICG.005.gb	NA	NA	Provided by client
G	GPS Antenna	NA	NA	NA	NA	Provided by client

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item D acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	HDMI Cable	1	2	N	0	-
2.	RF Cable	1	0.5	N	0	-
3.	RF Cable	1	0.5	N	0	-
4.	RF Cable	1	0.5	N	0	-
5.	USB Cable	1	2.4	N	0	-
6.	USB Cable	1	2.2	N	0	-
7.	DC power Cable	1	1.2	N	0	-
8.	Power Cord	1	1.8	N	0	-



### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP	Radiated Emission
LTE Band 26	Y-plane	Y-axis

#### LTE Band 26

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	26697 to 26783	26697, 26740, 26783	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26740	26740	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Modulation Characteristics	26740	26740	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Frequency Stability	26697 to 26783	26697, 26783	1.4 MHz	QPSK	6 RB / 0 RB Offset
		26705 to 26775	26705, 26775	3 MHz	QPSK	15 RB / 0 RB Offset
		26715 to 26765	26715, 26765	5 MHz	QPSK	25 RB / 0 RB Offset
		26740	26740	10 MHz	QPSK	50 RB / 0 RB Offset
-	Occupied Bandwidth	26697 to 26783	26697, 26740, 26783	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		26740	26740	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Emission Mask	26697 to 26783	26697, 26740, 26783	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		26740	26740	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Conducted Emission	26697 to 26783	26697, 26740, 26783	1.4 MHz	QPSK	1 RB / 0 RB Offset
		26705 to 26775	26705, 26740, 26775	3 MHz	QPSK	1 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5 MHz	QPSK	1 RB / 0 RB Offset
		26740	26740	10 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	26697 to 26783	26697, 26740, 26783	1.4 MHz	QPSK	1 RB / 0 RB Offset
		26715 to 26765	26715, 26740, 26765	5 MHz	QPSK	1 RB / 0 RB Offset
		26740	26740	10 MHz	QPSK	1 RB / 0 RB Offset

#### Note:

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation. Therefore, only ERP, modulation characteristics, occupied bandwidth and Emission Mask items had been tested under QPSK, 16QAM mode, the other items were performed under QPSK mode only.
2. For radiated emission above 1 GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5 MHz & highest channel bandwidth for final test.
3. For radiated emissions below 1 GHz, select the worst radiated emission channel (above 1GHz) for final testing

**Test Condition:**

Test Item	Environmental Conditions	Input Power	Tested By
ERP	25 deg. C, 65 % RH	12 Vdc	Cyril Chen
Frequency Stability	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Occupied Bandwidth	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Emission Mask	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Band Edge	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Conducted Emission	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Cyril Chen

**3.4 General Description of Applied Standards and references**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

**Test Standard:**

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 90**

**ANSI 63.26-2015**

**Note:** All test items have been performed and recorded as per the above standards.

**References Test Guidance:**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

**KDB 971168 D02 Misc Rev Approv License Devices v02r01**

**ANSI/TIA/EIA-603-E 2016**

**Note:** All test items have been performed as a reference to the above KDB test guidance.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw) ERP.

#### 4.1.2 Test Procedures

##### **EIRP / ERP Measurement:**

- a. All measurements were done at low, middle and high operational frequency range. RBW is 1.4 MHz ∙ 3 MHz ∙ 5 MHz ∙ 10 MHz for LTE mode, and VBW ≥ 3 x RBW.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15 dB.
- d. Correction Factor (includes EIRP and ERP unit conversion factor) = Antenna gain of substitution horn. – Tx cable loss. Measurement method refers to ANSI C63.26 section 5.2.7 & 5.2.4.


##### **Conducted Power Measurement:**

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 Test Setup

**EIRP / ERP Measurement:**

**<Radiated Emission below or equal 1 GHz>**




**<Radiated Emission above 1 GHz>**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

**Conducted Power Measurement:**



4.1.4 Test Results

Conducted Output Power (dBm)

LTE Band 26															
BW	MCS Index	RB Size	RB Offset				3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
				Channel	26740							26715	26740	26765	
				Frequency (MHz)	819.0							816.5	819.0	821.5	
10M	QPSK	1	0		23.17		0	5M	QPSK	1	0	23.22	23.05	23.17	0
		1	24		23.03		0			1	12	22.96	22.88	23.06	0
		1	49		22.79		0			1	24	22.79	22.77	22.88	0
		25	0		21.97		1			12	0	21.89	21.81	22.02	1
		25	12		21.77		1			12	6	21.73	21.65	21.86	1
		25	25		21.66		1			12	13	21.58	21.48	21.70	1
	50	0		22.00		1	25		0	21.85	21.81	22.14	1		
	16QAM	1	0		22.12		1		16QAM	1	0	22.16	21.96	22.16	1
		1	24		21.93		1			1	12	21.94	21.80	22.00	1
		1	49		21.74		1			1	24	21.78	21.71	21.81	1
		25	0		20.74		2			12	0	20.84	20.74	20.80	2
		25	12		20.87		2			12	6	20.66	20.62	20.81	2
		25	25		20.66		2			12	13	20.55	20.47	20.64	2
		50	0		20.88		2			25	0	20.69	20.62	21.05	2

ERP Power (dBm)

LTE Band 26							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	26697	814.7	-14.82	32.01	17.19	52.36	H
	26740	819.0	-14.78	32.11	17.33	54.08	
	26783	823.3	-15.40	32.32	16.92	49.20	
	V	26697	814.7	-19.61	32.54	12.93	19.63
		26740	819.0	-19.44	32.51	13.07	20.28
		26783	823.3	-19.72	32.51	12.79	19.01
Channel Bandwidth: 1.4 MHz / 16QAM							
Y	26697	814.7	-16.02	32.01	15.99	39.72	H
	26740	819.0	-15.92	32.11	16.19	41.59	
	26783	823.3	-16.51	32.32	15.81	38.11	
	V	26697	814.7	-20.70	32.54	11.84	15.28
		26740	819.0	-20.53	32.51	11.98	15.78
		26783	823.3	-20.88	32.51	11.63	14.55

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 26							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	26705	815.5	-14.75	32.02	17.27	53.33	H
	26740	819.0	-14.68	32.11	17.43	55.34	
	26775	822.5	-15.17	32.18	17.01	50.23	
	26705	815.5	-19.48	32.5	13.02	20.04	V
	26740	819.0	-19.34	32.51	13.17	20.75	
	26775	822.5	-19.58	32.47	12.89	19.45	
Channel Bandwidth: 3 MHz / 16QAM							
Y	26705	815.5	-15.94	32.02	16.08	40.55	H
	26740	819.0	-15.81	32.11	16.30	42.66	
	26775	822.5	-16.26	32.18	15.92	39.08	
	26705	815.5	-20.59	32.5	11.91	15.52	V
	26740	819.0	-20.44	32.51	12.07	16.11	
	26775	822.5	-20.74	32.47	11.73	14.89	

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 26							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	26715	816.5	-14.68	32.04	17.36	54.45	H
	26740	819.0	-14.57	32.11	17.54	56.75	
	26765	821.5	-14.69	31.79	17.10	51.29	
	26715	816.5	-19.41	32.52	13.11	20.46	V
	26740	819.0	-19.23	32.51	13.28	21.28	
	26765	821.5	-19.19	32.17	12.98	19.86	
Channel Bandwidth: 5 MHz / 16QAM							
Y	26715	816.5	-15.87	32.04	16.17	41.40	H
	26740	819.0	-15.72	32.11	16.39	43.55	
	26765	821.5	-15.78	31.79	16.01	39.90	
	26715	816.5	-20.52	32.52	12.00	15.85	V
	26740	819.0	-20.33	32.51	12.18	16.52	
	26765	821.5	-20.33	32.17	11.84	15.28	

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 26							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	26740	819.0	-14.57	32.11	17.54	56.75	H
	26740	819.0	-19.23	32.51	13.28	21.28	V
Channel Bandwidth: 10 MHz / 16QAM							
Y	26740	819.0	-15.63	32.11	16.48	44.46	H
	26740	819.0	-20.24	32.51	12.27	16.87	V


Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB)

## 4.2 Modulation Characteristics Measurement

### 4.2.1 Limits of Modulation Characteristics

N/A


### 4.2.2 Test Setup



### 4.2.3 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector. The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

### 4.2.4 Test Results





### 4.3 Frequency Stability Measurement

#### 4.3.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

#### 4.3.2 Test Procedure

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

#### 4.3.3 Test Setup



#### 4.3.4 Test Results

##### Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 26				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
12	814.700002	0.002	823.300000	-0.002	2.5
10.2	814.700002	0.003	823.300000	-0.002	2.5
13.8	814.700003	0.004	823.300000	-0.002	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

##### Frequency Error vs. Temperature

Temp. (°C)	LTE Band 26				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	814.700002	0.002	823.300000	0.002	2.5
-20	814.700001	0.001	823.300000	0.002	2.5
-10	814.700002	0.002	823.300000	0.005	2.5
0	814.700003	0.004	823.300000	0.002	2.5
10	814.699996	-0.005	823.300000	0.001	2.5
20	814.699998	-0.002	823.300000	0.004	2.5
30	814.699998	-0.002	823.300000	0.005	2.5
40	814.699997	-0.003	823.300000	-0.004	2.5
50	814.699999	-0.001	823.300000	-0.004	2.5
60	814.699998	-0.002	823.300000	-0.005	2.5
70	814.699997	-0.003	823.300000	-0.001	2.5
80	814.699997	-0.003	823.300000	-0.004	2.5

**Note:**

1. The applicant declared that the normal operating temperature of the EUT is from -30°C to 80°C.
2. The EUT would shut down automatically as below -30°C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 26				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
12	815.500002	0.002	822.500000	-0.002	2.5
10.2	815.500004	0.005	822.500000	-0.002	2.5
13.8	815.500003	0.004	822.500000	-0.001	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 26				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	815.500003	0.004	822.500000	0.004	2.5
-20	815.500001	0.002	822.500000	0.003	2.5
-10	815.500001	0.001	822.500000	0.001	2.5
0	815.500003	0.004	822.500000	0.002	2.5
10	815.499998	-0.003	822.500000	0.002	2.5
20	815.499999	-0.001	822.500000	0.005	2.5
30	815.499996	-0.005	822.500000	0.005	2.5
40	815.499999	-0.001	822.500000	-0.002	2.5
50	815.499998	-0.003	822.500000	-0.004	2.5
60	815.499997	-0.004	822.500000	-0.004	2.5
70	815.499996	-0.005	822.500000	-0.001	2.5
80	815.499996	-0.005	822.500000	-0.004	2.5

**Note:**

1. The applicant declared that the normal operating temperature of the EUT is from -30°C to 80°C.
2. The EUT would shut down automatically as below -30°C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 26				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
12	816.500002	0.002	821.500000	-0.003	2.5
10.2	816.500001	0.001	821.500000	-0.002	2.5
13.8	816.500001	0.001	821.500000	-0.003	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 26				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	816.500002	0.002	821.500000	0.004	2.5
-20	816.500001	0.001	821.500000	0.004	2.5
-10	816.500002	0.003	821.500000	0.001	2.5
0	816.500001	0.001	821.500000	0.003	2.5
10	816.499997	-0.004	821.500000	0.003	2.5
20	816.499996	-0.005	821.500000	0.004	2.5
30	816.499997	-0.004	821.500000	0.002	2.5
40	816.499997	-0.003	821.500000	-0.004	2.5
50	816.499998	-0.003	821.500000	-0.004	2.5
60	816.499996	-0.004	821.500000	-0.003	2.5
70	816.499996	-0.005	821.500000	-0.002	2.5
80	816.499999	-0.002	821.500000	-0.002	2.5

**Note:**

1. The applicant declared that the normal operating temperature of the EUT is from -30°C to 80°C.
2. The EUT would shut down automatically as below -30°C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 26		Limit (ppm)
	Channel Bandwidth: 10 MHz		
	Frequency (MHz)	Frequency Error (ppm)	
12	819.000004	0.005	2.5
10.2	819.000002	0.003	2.5
13.8	819.000002	0.002	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 26		Limit (ppm)
	Channel Bandwidth: 10 MHz		
	Frequency (MHz)	Frequency Error (ppm)	
-30	819.000001	0.001	2.5
-20	819.000002	0.003	2.5
-10	819.000003	0.003	2.5
0	819.000002	0.003	2.5
10	818.999997	-0.004	2.5
20	818.999996	-0.005	2.5
30	818.999996	-0.005	2.5
40	818.999998	-0.003	2.5
50	818.999997	-0.004	2.5
60	818.999998	-0.003	2.5
70	818.999996	-0.005	2.5
80	818.999997	-0.003	2.5

**Note:**

1. The applicant declared that the normal operating temperature of the EUT is from -30°C to 80°C.
2. The EUT would shut down automatically as below -30°C.

## 4.4 Occupied Bandwidth Measurement

### 4.4.1 Limits of Occupied Bandwidth Measurement


The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

### 4.4.2 Test Procedure

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Measurement method, please refer to section 5.4.4 of ANSI C63.26. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.


For the 26dBc bandwidth measurement method, please refer to section 5.4.3 of ANSI C63.26.

### 4.4.3 Test Setup



#### 4.4.4 Test Results

LTE Band 26					
Channel Bandwidth: 1.4 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26697	814.7	1.09	1.09	1.22	1.23
26740	819.0	1.09	1.09	1.22	1.22
26783	823.3	1.09	1.09	1.21	1.22
Channel Bandwidth: 3 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26705	815.5	2.70	2.70	2.94	2.94
26740	819.0	2.70	2.70	2.93	2.93
26775	822.5	2.70	2.70	2.91	2.93



LTE Band 26					
Channel Bandwidth: 5 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26715	816.5	4.49	4.49	4.82	4.82
26740	819.0	4.49	4.49	4.79	4.81
26765	821.5	4.49	4.49	4.81	4.80

Channel Bandwidth: 10 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26740	819.0	8.99	8.99	9.54	9.54





## 4.5 Emission Mask Measurement


### 4.5.1 Limits of Emission Mask Measurement

According to FCC part 90.691 shall be tested the emission mask. For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116 \text{ Log}_{10}(f/6.1)$  decibels or  $50 + 10\text{Log}_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10\text{Log}_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

For §90.691(a), RBW=300 Hz for offset less than 37.5 kHz from channel edge and RBW=100 kHz for offsets greater than 37.5 kHz is allowed.


### 4.5.2 Test Setup





### 4.5.3 Test Procedures


- The measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Record the test plot.


### 4.5.4 Test Results























## 4.6 Conducted Spurious Emissions

### 4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission is equal to -13 dBm.


### 4.6.2 Test Setup



### 4.6.3 Test Procedure



- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 1 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 100 kHz and VBW = 300 kHz are used for conducted emission measurement.
- Measuring frequency range is from 1 GHz to 9 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz are used for conducted emission measurement.

#### 4.6.4 Test Results





Note: The signal over the limit in 9 kHz is from spectrum analyzer.



**LTE Band 26**  
**Channel Bandwidth: 3 MHz**  
**Channel 26705**



**Channel 26740**




**Channel 26775**




Note: The signal over the limit in 9 kHz is from spectrum analyzer.

**LTE Band 26**  
**Channel Bandwidth: 5 MHz**


**Channel 26715**




**Channel 26740**



**Channel 26765**



Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.

## 4.7 Radiated Emission Measurement

### 4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB. The limit of emission is equal to -13 dBm.

### 4.7.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ . Correction Factor (includes EIRP and ERP unit conversion factor) = Antenna gain of substitution horn. - Tx cable loss. Measurement method refers to ANSI C63.26 section 5.5.3.2.
- c. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dB}$ .


**Note:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

### 4.7.3 Deviation from Test Standard


No deviation.

4.7.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).



#### 4.7.5 Test Results

LTE Band 26

Channel Bandwidth: 1.4 MHz / QPSK


Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5

Condition: PART 90 HORIZONTAL

Remak : LTE Band 26 QPSK\_1.4M Link\_L-CH

Tested by: Cyril Chen

Read	Limit	Over				
Freq	Level	Level	Line	Factor	Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 1629.40 -65.21 -50.42 -13.00 -14.79 -52.21 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5  
 Condition: PART 90 VERTICAL  
 Remak : LTE Band 26 QPSK\_1.4M Link\_L-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1629.40	-64.67	-49.88	-13.00	-14.79	-51.67	Peak


### Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART 90 HORIZONTAL  
 Remak : LTE Band 26 QPSK\_1.4M Link\_M-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 1638.00 -64.45 -49.66 -13.00 -14.79 -51.45 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5  
 Condition: PART 90 VERTICAL  
 Remak : LTE Band 26 QPSK\_1.4M Link\_M-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1638.00	-64.80	-50.01	-13.00	-14.79	-51.80	Peak


# High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART 90 HORIZONTAL  
 Remak : LTE Band 26 QPSK\_1.4M Link\_H-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 1646.60 -64.40 -49.67 -13.00 -14.73 -51.40 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5  
 Condition: PART 90 VERTICAL  
 Remark : LTE Band 26 QPSK\_1.4M Link\_H-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Over	Remark
MHz	dBm	dBm	dBm	dB	
1 pp 1646.60	-64.09	-49.36	-13.00	-14.73	-51.09 Peak


Channel Bandwidth: 5 MHz / QPSK  
Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
Condition: PART 90 HORIZONTAL  
Remak : LTE Band 26 QPSK\_5M Link\_L-CH  
Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Over	Remark
MHz	dBm	dBm	dBm	dB	


1 pp 1633.00 -64.99 -50.20 -13.00 -14.79 -51.99 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5  
 Condition: PART 90 VERTICAL  
 Remak : LTE Band 26 QPSK\_5M Link\_L-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1633.00	-64.94	-50.15	-13.00	-14.79	-51.94	Peak




Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART 90 HORIZONTAL  
 Remak : LTE Band 26 QPSK\_5M Link\_M-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 1638.00 -64.38 -49.59 -13.00 -14.79 -51.38 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5  
 Condition: PART 90 VERTICAL  
 Remak : LTE Band 26 QPSK\_5M Link\_M-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1638.00	-64.79	-50.00	-13.00	-14.79	-51.79	Peak


# High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART 90 HORIZONTAL  
 Remak : LTE Band 26 QPSK\_5M Link\_H-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 1643.00 -64.53 -49.80 -13.00 -14.73 -51.53 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5  
 Condition: PART 90 VERTICAL  
 Remak : LTE Band 26 QPSK\_5M Link\_H-CH  
 Tested by: Cyril Chen

Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1643.00	-65.31	-50.58	-13.00	-14.73	-52.31	Peak


Channel Bandwidth: 10 MHz / QPSK  
Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
Condition: PART 90 HORIZONTAL  
Remak : LTE Band 26 QPSK\_10M Link\_M-CH  
Tested by: Cyril Chen

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	71.71	-28.25	-19.40	-13.00	-8.85	-15.25	Peak
2	185.20	-37.35	-30.11	-13.00	-7.24	-24.35	Peak
3	299.66	-47.42	-40.41	-13.00	-7.01	-34.42	Peak
4	451.95	-65.05	-59.54	-13.00	-5.51	-52.05	Peak
5	597.45	-59.58	-58.71	-13.00	-0.87	-46.58	Peak
6	789.51	-62.43	-63.20	-13.00	0.77	-49.43	Peak
7	1638.00	-63.66	-48.87	-13.00	-14.79	-50.66	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 11-17-2020



Site : 966 Chamber 5  
 Condition: PART 90 VERTICAL  
 Remak : LTE Band 26 QPSK\_10M Link\_M-CH  
 Tested by: Cyril Chen

	Freq	Level	Read Level	Limit Line	Over Factor	Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	40.67	-17.84	-17.96	-13.00	0.12	-4.84	Peak
2	170.65	-38.55	-32.85	-13.00	-5.70	-25.55	Peak
3	320.03	-52.36	-45.66	-13.00	-6.70	-39.36	Peak
4	502.39	-60.00	-55.46	-13.00	-4.54	-47.00	Peak
5	615.88	-63.03	-62.24	-13.00	-0.79	-50.03	Peak
6	757.50	-59.97	-60.83	-13.00	0.86	-46.97	Peak
7	1638.00	-64.95	-50.16	-13.00	-14.79	-51.95	Peak

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---