

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	Robot Vacuum Cleaner
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz)
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	11.84dBm(15.28mW)
<b>Antenna gain</b>	0 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )
300-1500	--	--	F/1500
1500-100000	--	--	1

## Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in Mw

$G$ = gain of antenna in linear scale

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Channel	Gain	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b							
Low	0	2412	11.84	± 0.5	17.13	0.0341	1
Middle	0	2437	11.70	± 0.5	16.60	0.0330	1
High	0	2462	11.22	± 0.5	14.86	0.0296	1
802.11g							
Low	0	2412	10.78	± 0.5	13.43	0.0267	1
Middle	0	2437	10.58	± 0.5	12.82	0.0255	1
High	0	2462	10.35	± 0.5	12.16	0.0242	1
802.11n HT20							
Low	0	2412	10.87	± 0.5	13.71	0.0276	1
Middle	0	2437	10.70	± 0.5	13.18	0.0262	1
High	0	2462	10.26	± 0.5	11.91	0.0237	1

According to the test result of power density at separation distance 20cm, compliance with RF Exposure requirement.