

RF EXPOSURE EVALUATION

EUT Specification

| | |
|-----------------------------------|---|
| EUT | Robot Vacuum Cleaner |
| Frequency band (Operating) | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz) |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____ |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | 17.93dBm(62.09mW) |
| Antenna gain | 0 dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) |
|----------------------|------------------------------|------------------------------|------------------------------------|
| 300-1500 | -- | -- | F/1500 |
| 1500-100000 | -- | -- | 1 |

Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

| Channel | Channel Frequency (MHz) | Max Output power (dBm) | Max Output power (mW) | Power density at 20cm (mW/cm^2) | Power density Limits (mW/cm^2) |
|-------------------------------|-------------------------|------------------------|-----------------------|-------------------------------------|------------------------------------|
| Test mode: IEEE 802.11b | | | | | |
| Low | 2412 | 17.93 | 62.09 | 0.01235 | 1 |
| Middle | 2437 | 16.72 | 46.99 | 0.00935 | 1 |
| High | 2462 | 16.18 | 41.50 | 0.00826 | 1 |
| Test mode: IEEE 802.11g | | | | | |
| Low | 2412 | 15.89 | 38.82 | 0.00772 | 1 |
| Middle | 2437 | 15.94 | 39.26 | 0.00781 | 1 |
| High | 2462 | 15.59 | 36.22 | 0.00721 | 1 |
| Test mode: IEEE 802.11n(HT20) | | | | | |
| Low | 2412 | 16.21 | 41.78 | 0.00831 | 1 |
| Middle | 2437 | 16.20 | 41.69 | 0.00829 | 1 |
| High | 2462 | 15.72 | 37.33 | 0.00743 | 1 |
| Test mode: IEEE 802.11n(HT40) | | | | | |
| Low | 2422 | 16.56 | 45.29 | 0.00901 | 1 |
| Middle | 2437 | 16.78 | 47.64 | 0.00948 | 1 |
| High | 2452 | 16.49 | 44.57 | 0.00887 | 1 |

According to the test result of power density at separation distance 20cm, compliance with RF Exposure requirement.