

RF Exposure Evaluation

FCC ID: 2AX96-Y16-T

1. Client Information

Applicant	:	ACCUTIME WATCH CORPORATION
Address	:	1001 AVE. OF THE AMERICAS 6TH FLOOR NY, NY 10018 USA
Manufacturer	:	ShenZhen KY Technology Co., Ltd
Address	:	4th Floor, Building A4, Anle Industrial Zone, NO.172, Hangcheng Road, Xixiang Town, Baoan District, ShenZhen, China

2. General Description of EUT

EUT Name	:	KESSARIS WEARABLE TECHNOLOGY INTERCHANGEABLE STRAP WATCH	
Model(s) No.	:	Y16-T	
Model Different	:	----	
Sample ID	:	TBBJ-20201106-11-1# & TBBJ-20201106-11-2#	
Product Description	:	Operation Frequency:	Bluetooth 4.2(BLE): 2402MHz~2480MHz
	:	Number of Channel:	Bluetooth 4.2(BLE): 40 channels
	:	RF Output Power:	-0.838 dBm (Max)
	:	Antenna Gain:	0.6 dBi Internal Antenna
	:	Modulation Type:	GFSK
	:	Bit Rate of Transmitter:	1Mbps
Power Rating	:	Input:DC 5V DC 3.7V by 170mAh Li-ion battery	
Software Version	:	V5.12	
Hardware Version	:	V1.0	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.			

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f(\text{GHz})}] \leq 7.5.0$ for 10-g SAR

2. Calculation:

Test separation: 5mm						
BLE Mode (1Mbps)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-0.859	-0±1	1	1.259	0.390	3.0
2.442	-0.838	-0±1	1	1.259	0.393	3.0
2.480	-1.34	-1±1	0	1.000	0.315	3.0

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----