

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AX97-A45

EUT Specification

EUT	Projector
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others: BT:2.402GHz~2.480GHz Wi-Fi 5.2G: 5150~5250MHz Wi-Fi 5.3G:5250~5350MHz Wi-Fi 5.6G: 5470~5725MHz Wi-Fi 5.8G: 5725~5850MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure <input checked="" type="checkbox"/> General Population/Uncontrolled exposure
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	BDR,EDR: 8.05dBm (0.0064W); BLE: 5.83dBm (0.0038W); WIFI 2.4G: 17.04dBm (0.0506W); Wi-Fi 5.2G: 18.42dBm (0.0695W); Wi-Fi 5.3G: 15.03dBm (0.0318W); Wi-Fi 5.6G: 20.07dBm (0.1016W); Wi-Fi 5.8G: 18.12dBm (0.0649W);
Antenna gain (Max)	BT: 5.64dBi WIFI 2.4G: 5.64dBi Wi-Fi 5.2G: 6.35dBi Wi-Fi 5.3G: 6.55dBi Wi-Fi 5.6G: 6.63dBi Wi-Fi 5.8G: 6.47dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Max Measurement Result

Operating Mode	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits
	(dBm)	(dBm)	(dBm)	(dBi)	(mW/cm^2)	(mW/cm^2)
BDR EDR	8.05	8.05 ±1	9.05	5.64	0.0059	1
BLE	5.83	5.83 ±1	6.83	5.64	0.0035	1
Wifi 2.4G	17.04	17.04 ±1	18.04	5.64	0.0464	1
Wifi 5G	20.07	20.07 ±1	21.07	6.63	0.1172	1

The WLAN and BT can transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= \frac{S_{WiFi2.4}}{S_{Limit-2.4}} + \frac{S_{WiFi5G}}{S_{Limit-WiFi5G}} + \frac{S_{BDR,EDR}}{S_{Limit-BDR,EDR}}$$

$$= \frac{0.0464}{1} + \frac{0.1172}{1} + \frac{0.0059}{1}$$

$$= 0.1695$$

$$< 1.0$$