

Part# W5030



The W5030 Radome Omni, a Pulse/Larsen dual-band WiFi omni antenna is designed for harsh outdoor environments where WiFi connection is needed in either the 2.4 GHz or 5 GHz bands. This robust antenna provides excellent mechanical stability and UV/IP67 protection to ensure a long, reliable, maintenance-free life.

The antenna is part of a Radome Omni (RO) series of antennas offered in many different frequencies from 698 MHz to 6 GHz with varying gains and N Male and Female connector options. The W5030 and all additional RO antennas are designed for installation on a mast or wall using an FB2BRACKET or FB3BRACKET.

Features

- Frequency 2.4-2.5 / 5.15-5.875 GHz
- Omni-Direction with 3.5/6.5 dBi Gain
- UV Protected and IP67 rated
- Connector N-Male

Applications

- Access Points
- Base Stations
- Public Safety
- Repeaters
- Small Cell

Confidential and Proprietary - Pulse Electronics - All Rights reserved - 2015

Tel: 1-360-944-7551

Fax: 1-360-944-7556

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its content, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. Information subject to change without notice.

For More Information

Tel:1-858-674-8100

Fax: 1-858-674-8262

Pulse Worldwide Headquarters	Larsen Brand Antennas	Europe Headquarters	Pulse (Suzhou) Wireless Products Co, Inc.
12220 World Trade Drive San Diego, CA 92128 USA	3611 NE 112 th Ave Vancouver, WA 98682 USA	Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany	99 Huo Ju Road(#29 Bldg, 4 th Phase Suzhou New District Science & Tech Industrial Park Jiangsu Province, Suzhou 215009 PR China

Tel: 86 512 6807 9998 Fax: 86 512 6809 8023



Performance warranty of products offered in this data sheet is limited to the parameters specified. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

©Copyright, 2015. Pulse Electronics, Inc. All rights
Reserved.

Tel: 49 7032 7806 0

Fax: 49 7032 7806 135



Part# W5030

ELECTRICAL SPECIFICATIONS		
Frequency 1 (GHz)	2.4 - 2.5	
Frequency 2 (GHz)	5.15 – 5.875	
Nominal Impedance (Ω)	50	
VSWR (Max)	2:1	
Average Peak Gain 2.4 GHz (dBi)	3.5	
Average Peak Gain 5X GHz (dBi)	6.5	
HPWB / Horizontal Plane	Omni	
HPBW / Vertical Plane 2.4 GHz (° TYP)	45	
HPBW / Vertical Plane 5X GHz (° TYP)	25	
Polarization	Vertical	
Power Withstanding (W)	20	
E.S.D. Protection	External Recommended	
Connector Type	N Male	


ENVIRONMENTAL SPECIFICATIONS		
Operation Temperature (° C)	-40 - +85	

MECHANICAL SPECIFICATIONS		
Radome Material	Pultruded Polyester/Fiberglass – UV Protected	
Color	White	
Ingress Protection	IP67	
Weight (grams)	166	
Wind Loading (MPH)	150	
Overall Length (inches)	6.81	
Side Loading @ 1 Ft (Lbs)	30	
Pull Off (Lbs)	100	



Part# W5030


HORIZONTAL PLANE 2.4 - 2.5 GHz





Part# W5030


HORIZONTAL PLANE 5.15 - 5.875 GHz





Part# W5030


VERTICAL PLANE 2.4 – 2.5 GHz





Part# W5030

VERTICAL PLANE 5.15 - 5.875 GHz



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pulse: W5030