

## FCC 47 CFR MPE REPORT

Anhui Grizzly Vision Technology Co.,Ltd

75" ULTRA HD SMART TV(ATSC TUNER)

Model Number: RWOSU7549

Additional Model: RWOSU7547, PLED7538-C-UHDSM, RNSMU7536,  
RQSM7527

FCC ID: 2AXAQ-RCA-HX-75

Prepared for:	Anhui Grizzly Vision Technology Co.,Ltd
	High-tech Industrial Park,High-tech Zone,Huainan,Anhui,China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2109136
Date of Test:	Jul. 29~Sep. 07, 2021
Date of Report:	Sep. 10, 2021



## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Antenna	Mode (MHz)	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)
0	GFSK 1M-BLE	2480	3.26	2.1184	3±1
0	GFSK-2M-BLE	2480	3.28	2.1281	3±1
0	GFSK-BT	2480	3.30	2.1380	3±1
0	8-DPSK-BT	2480	6.19	4.1591	6±1
1	IEEE 802.11b	2412	17.39	54.8277	16±1
1	IEEE 802.11g	2412	21.04	127.0574	20±1
1	IEEE 802.11n HT20 (2.4G)	2462	19.34	85.9014	18±1
1	IEEE 802.11n HT40 (2.4G)	2422	19.58	90.7821	19±1
1	IEEE 802.11a	5240	13.21	20.9411	13±1
1	IEEE 802.11n HT20 (5G)	5240	11.80	15.1356	11±1
1	IEEE 802.11ac VHT20 (5G)	5240	11.55	14.2889	11±1
1	IEEE 802.11n HT40 (5G)	5230	11.73	14.8936	11±1
1	IEEE 802.11acVHT40 (5G)	5230	11.47	14.0281	11±1
1	IEEE 802.11acVHT80 (5G)	5210	10.73	11.8304	10±1
2	IEEE 802.11b	2462	18.17	65.6145	18±1
2	IEEE 802.11g	2462	21.75	149.6236	21±1
2	IEEE 802.11n HT20 (2.4G)	2462	20.82	120.7814	20±1
2	IEEE 802.11n HT40 (2.4G)	2437	21.05	127.3503	21±1
2	IEEE 802.11a	5785	12.06	16.0694	12±1
2	IEEE 802.11n HT20 (5G)	5785	10.98	12.5314	10±1

2	IEEE 802.11ac VHT20(5G)	5785	10.64	11.5878	10±1
2	IEEE 802.11n HT40 (5G)	5795	10.79	11.9950	10±1
2	IEEE 802.11acVHT40 (5G)	5795	10.07	10.1625	10±1
2	IEEE 802.11acVHT80 (5G)	5775	9.60	9.1201	9±1

### 3. Calculated Result and Limit

#### Bluetooth Antenna 0

Mode	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW/cm <sup>2</sup> )	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
		(dBi)	(Linear)			
2.4G Band						
BLE	4	2	1.585	0.0008	1	Complies
BT	7	2	1.585	0.0016	1	Complies

#### W-Fi Antenna 1

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm <sup>2</sup> )	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11b	17	2	1.585	0.0158	1	Complies
IEEE 802.11g	21	2	1.585	0.0397	1	Complies
IEEE 802.11n HT20	19	2	1.585	0.0250	1	Complies
IEEE 802.11n HT40	20	2	1.585	0.0315	1	Complies
5G Band						
IEEE 802.11a	14	2	1.585	0.0079	1	Complies
IEEE 802.11n HT20	12	2	1.585	0.0050	1	Complies
IEEE 802.11ac VHT20	12	2	1.585	0.0050	1	Complies
IEEE 802.11n HT40	12	2	1.585	0.0050	1	Complies
IEEE 802.11ac VHT40	12	2	1.585	0.0050	1	Complies
IEEE 802.11ac VHT80	11	2	1.585	0.0040	1	Complies

**Wi-Fi Antenna 2**

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm <sup>2</sup> )	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
		(dBi)	(Linear)			
<b>2.4G Band</b>						
IEEE 802.11b	19	2	1.585	0.0250	1	Complies
IEEE 802.11g	22	2	1.585	0.0500	1	Complies
IEEE 802.11n HT20	21	2	1.585	0.0397	1	Complies
IEEE 802.11n HT40	22	2	1.585	0.0500	1	Complies
<b>5G Band</b>						
IEEE 802.11a	13	2	1.585	0.0063	1	Complies
IEEE 802.11n HT20	11	2	1.585	0.0040	1	Complies
IEEE 802.11ac VHT20	11	2	1.585	0.0040	1	Complies
IEEE 802.11n HT40	11	2	1.585	0.0040	1	Complies
IEEE 802.11ac VHT40	11	2	1.585	0.0040	1	Complies
IEEE 802.11ac VHT80	10	2	1.585	0.0032	1	Complies

**Wi-Fi Antenna 1+2**

Mode	Power Density (S) (mW/cm <sup>2</sup> ) Antenna 1	Power Density (S) (mW/cm <sup>2</sup> ) Antenna 2	Power Density (S) (mW/cm <sup>2</sup> ) Total	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
<b>2.4G Band</b>					
IEEE 802.11n HT20	0.0250	0.0397	0.0647	1	Complies
IEEE 802.11n HT40	0.0315	0.0500	0.0815	1	Complies
<b>5G Band</b>					
IEEE 802.11n HT20	0.0050	0.0040	0.0090	1	Complies
IEEE 802.11ac VHT20	0.0050	0.0040	0.0090	1	Complies
IEEE 802.11n HT40	0.0050	0.0040	0.0090	1	Complies
IEEE 802.11ac VHT40	0.0050	0.0040	0.0090	1	Complies
IEEE 802.11ac VHT80	0.0040	0.0032	0.0072	1	Complies

**Bluetooth+2.4G Wi-Fi+5G Wi-Fi**

MAX Power Density (S) (mW/cm <sup>2</sup> ) Bluetooth	MAX Power Density (S) (mW/cm <sup>2</sup> ) 2.4G WiFi ANT1+ANT2	MAX Power Density (S) (mW/cm <sup>2</sup> ) 5G WiFi ANT1+ANT2	Power Density (S) (mW/cm <sup>2</sup> ) Total	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
0.0016	0.0815	0.0090	0.0921	1	Complies

Note: 2.4 and 5GHz bands are share an antenna, Can't both the 2.4 and 5 GHz bands operate simultaneously.

**End of Test Report**