

FCC RF EXPOSURE REPORT

FCC ID: 2AXCA-INFINITEV2

Project No. : 2108C044
Equipment : Infinite Wireless Receiver
Brand Name : DURGOD
Test Model : Infinite V2
Series Model : N/A
Applicant : Zhuhai Hoksi Technology CO.,LTD
Address : Room803, No.3 BLDG, No.6, Pingbei 1 Rd., Nanping Technology & Industry Park, Xiangzhou St., ZhuHai, China
Manufacturer : Zhuhai Hoksi Technology CO.,LTD
Address : Room803, No.3 BLDG, No.6, Pingbei 1 Rd., Nanping Technology & Industry Park, Xiangzhou St., ZhuHai, China
Factory : Zhuhai Hengchang Electronic Technology Co.,Ltd
Address : 3rd floor, A building, No. 7 of 3rd pingxi Road, Nanping Technical industry park, Zhuhai, China
Date of Receipt : Aug. 06, 2021
Date of Test : Aug. 09, 2021 ~ Aug. 31, 2021
Issued Date : Oct. 09, 2021
Report Version : R01
Test Sample : Engineering Sample No.: DG2021080942
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & KDB447498 D01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Vincent Tan

Prepared by : Vincent Tan

Ethan Ma

Approved by : Ethan Ma



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China

Tel: +86-769-8318-3000

Web: www.newbtl.com

REPORT ISSUED HISTORY

| Report Version | Description | Issued Date |
|----------------|--------------------|---------------|
| R00 | Original Issue. | Sep. 30, 2021 |
| R01 | Updated the limit. | Oct. 09, 2021 |

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China.

BTL's Test Firm Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

2. GENERAL CONCLUSION

According to FCC KDB447498 D01, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

| Appendix A - SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm | | | | | | | | | | | |
|--|----|----|-----|-----|-----|-----|-----|-----|-----|-----|---------------------------------------|
| MHz | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | mm |
| 150 | 39 | 77 | 116 | 155 | 194 | 232 | 271 | 310 | 349 | 387 | SAR Test Exclusion Thresholds (mW) |
| 300 | 27 | 55 | 82 | 110 | 137 | 164 | 192 | 219 | 246 | 274 | |
| 450 | 22 | 45 | 67 | 89 | 112 | 134 | 157 | 179 | 201 | 224 | |
| 835 | 16 | 33 | 49 | 66 | 82 | 98 | 115 | 131 | 148 | 164 | |
| 900 | 16 | 32 | 47 | 63 | 79 | 95 | 111 | 126 | 142 | 158 | |
| 1500 | 12 | 24 | 37 | 49 | 61 | 73 | 86 | 98 | 110 | 122 | |
| 1900 | 11 | 22 | 33 | 44 | 54 | 65 | 76 | 87 | 98 | 109 | |
| 2450 | 10 | 19 | 29 | 38 | 48 | 57 | 67 | 77 | 86 | 96 | |
| 3600 | 8 | 16 | 24 | 32 | 40 | 47 | 55 | 63 | 71 | 79 | |
| 5200 | 7 | 13 | 20 | 26 | 33 | 39 | 46 | 53 | 59 | 66 | |
| 5400 | 6 | 13 | 19 | 26 | 32 | 39 | 45 | 52 | 58 | 65 | |
| 5800 | 6 | 12 | 19 | 25 | 31 | 37 | 44 | 50 | 56 | 62 | |

3. TABLE FOR FILED ANTENNA

| Ant. | Brand | P/N | Antenna Type | Connector | Gain (dBi) |
|------|-------|-----|--------------|-----------|------------|
| 1 | N/A | N/A | PCB | N/A | 1.87 |

Note: The antenna gain is provided by the manufacturer.

4. TEST RESULTS

| |
|-------------------------|
| Tune up tolerance (dBm) |
| 2.4G SRD |
| 1.50 |

| Frequency (MHz) | Max Tune-up power (dBm) | Max Tune-up power (mW) | Result | Limit |
|-----------------|-------------------------|------------------------|--------|-------|
| 2402 | 1.50 | 1.413 | 0.438 | 3.0 |

Note:

- (1) Output power including tune up tolerance.
- (2) No SAR evaluation required since transmitter power is below FCC threshold.

End of Test Report