

MPE Calculation

Mode	Frequency range (MHz)	Tune-up Max. Power(dBm)	ANT Gain (dBi)	Duty Factor(dB)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirment (mW/cm ²)
GSRS850 (1TX)	824.20 ~ 848.80	35.00	1.84	-9.03	27.81	603.949	0.1202	0.5490
GSRS850 (4TX)	824.20 ~ 848.80	30.00	1.84	-3.01	28.83	763.836	0.1520	0.5490
GSRS1900 (1TX)	1850.20 ~ 1909.80	27.80	2.98	-9.03	21.75	149.624	0.0298	1.0000
GSRS1900 (4TX)	1850.20 ~ 1909.80	26.80	2.98	-3.01	26.77	475.336	0.0946	1.0000
WCDMA850	826.40 ~ 846.60	25.00	1.84	-	26.84	483.059	0.0962	0.5500
WCDMA1700	1712.40 ~ 1752.60	25.00	2.50	-	27.50	562.342	0.1119	1.0000
WCDMA1900	1852.40 ~ 1907.60	25.00	2.98	-	27.98	628.059	0.1250	1.0000
LTE B12	699.70 ~ 715.30	25.00	0.40	-	25.40	346.737	0.0690	0.4660
LTE B13	779.50 ~ 784.50	25.00	1.96	-	26.96	496.593	0.0988	0.5190
LTE B26	814.70 ~ 823.30	25.00	0.70	-	25.70	371.536	0.0740	0.5430
LTE B26(5)	824.70 ~ 848.30	25.00	1.84	-	26.84	483.059	0.0962	0.5490
LTE B4	1710.70 ~ 1754.30	25.00	2.50	-	27.50	562.342	0.1119	1.0000
LTE B25(2)	1850.70 ~ 1914.30	25.00	2.98	-	27.98	628.059	0.1250	1.0000
LTE B41(38)	2498.50 ~ 2687.50	25.00	1.46	-	26.46	442.589	0.0881	1.0000
LTE B7	2502.50 ~ 2567.50	25.00	1.46	-	26.46	442.589	0.0881	1.0000

Note1: Please refer to the operation description for Max tune-up power.

Note2: For GSM, duty factor was applied.

-

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 603.949 / (4 \times 20^2 \times \pi) \\
 &= 0.1202 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(20cm)

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averageing time (minutes)
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19 / f	*180 / f ²	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1,500			f / 1500	30
1,500 ~ 100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC

RF Exposure Compliance for simultaneous operations

- Worst case for simultaneous operations
- GPRS850(4TX) + Satellite

Mode	GPRS850 (4TX)	Satellite	-	-	-	-	-	Σ of MPE ratios
Power Density (mW/cm ²)	0.1520	0.0847	-	-	-	-	-	
Requirement (mW/cm ²)	0.5490	1.0000	-	-	-	-	-	
MPE ratio (Power Density/Requirement)	0.2769	0.0847	-	-	-	-	-	
Worst case(MPE ratio)	0.2769	0.0847	-	-	-	-	-	

- Requirement = Σ of MPE ratios ≤ 1

Conclusion : The exposure condition of this device is compliant with FCC rules.