



# K5IGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,  
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China  
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website:  
www.gdkesign.com

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	Sofabaton X1 Smart Remote
Model Name	X1-Hub
FCC ID	2AXDU-X1-HUB

### 2. EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

#### LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

\*Note:

1. f= Frequency in MHz \* Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



# K SIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,  
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China  
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdksign.cn Website:  
www.gdksign.com

### 3. CALCULATION

A minimum test separation distance  $\geq 20$  cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated.

Antenna Gain=2.5dBi (Numeric 1.41),  $\pi=1.78$

Mode	Frequency (MHz)	Output Power (dBm)	Tune-up power (dBm)	Output Power (mW)	Power Density (mW/cm <sup>2</sup> )	Power Density Limit (mW/cm <sup>2</sup> )	Result
802.11b	2412	20.83	20±1	125.89	0.04454	1	Pass
	2437	20.94	20±1	125.89	0.04454	1	Pass
	2462	21.33	21±1	158.49	0.05607	1	Pass
802.11g	2412	20.93	20±1	125.89	0.04454	1	Pass
	2437	20.88	20±1	125.89	0.04454	1	Pass
	2462	21.19	21±1	158.49	0.05607	1	Pass
802.11n(H T20)	2412	20.02	20±1	125.89	0.04454	1	Pass
	2437	20.06	20±1	125.89	0.04454	1	Pass
	2462	20.24	20±1	125.89	0.04454	1	Pass
802.11n(H T40)	2422	19.11	19±1	100	0.03538	1	Pass
	2437	19.26	19±1	100	0.03538	1	Pass
	2452	19.49	19±1	100	0.03538	1	Pass
GFSK1M	2402	1.78	1±1	1.585	0.0006	1	Pass
	2440	1.76	1±1	1.585	0.0006	1	Pass
	2480	1.62	1±1	1.585	0.0006	1	Pass
GFSK2M	2402	1.85	1±1	1.585	0.0006	1	Pass
	2440	1.87	1±1	1.585	0.0006	1	Pass
	2480	1.61	1±1	1.585	0.0006	1	Pass



## **K SIGN (Guangdong) Testing Co., Ltd.**

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,  
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China  
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website:  
www.gdkesign.com

DH5	2402	-5.05	$-0.5 \pm 1$	1.096	0.0004	1	Pass
	2440	-5.00	$-0.5 \pm 1$	1.096	0.0004	1	Pass
	2480	-5.28	$-0.5 \pm 1$	1.096	0.0004	1	Pass

**Note:**

1. The WIFI, BT and BLE can be transmit simultaneously:

$0.05607+0.03538+0.0006+0.0004=0.09245 < 1$ ,so comply with RF exposure assessment.

**--THE END--**