



Engineering Test Report No. 2400866-01	
Report Date	June 10, 2024
Manufacturer Name	Trulli Audio
Manufacturer Address	200 Terrace Dr Mundelein, IL 60060
Test Item Name Model No.	Bass50 Portable Subwoofer BASS50
Date Received	May 7, 2024
Test Dates	May 7, 2024 – May 9, 2024
Specifications	FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 Innovation, Science, and Economic Development Canada, RSS-GEN Innovation, Science, and Economic Development Canada, RSS-247
Test Facility	Elite Electronic Engineering, Inc. 1516 Centre Circle, Downers Grove, IL 60515 FCC Reg. Number: 269750 IC Reg. Number: 2987A CAB Identifier: US0107
Signature	
Tested by	Edwin Casas
Signature	
Approved by	Raymond J. Klouda, Registered Professional Engineer of Illinois – 44894
PO Number	PO002474
<p>This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.</p> <p>This report shall not be reproduced, except in full, without the written approval of Elite Electronic Engineering Inc.</p> <p>Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 and Innovation, Science, and Economic Development Canada, RSS-247 test specifications. The data presented in this test report pertains to the EUT on the test dates specified. Any electrical or mechanical modifications made to the EUT subsequent to the specified test date will serve to invalidate the data and void this certification. This report must not be used to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.</p>	

Table of Contents

1.	Report Revision History	3
2.	Introduction	4
2.1.	Scope of Tests	4
2.2.	Purpose	4
2.3.	Identification of the EUT	4
3.	Power Input	4
4.	Grounding	4
5.	Support Equipment	5
6.	Interconnect Leads	5
7.	Modifications Made to the EUT	5
8.	Modes of Operation	5
9.	Test Specifications	5
10.	Test Plan	6
11.	Deviation, Additions to, or Exclusions from Test Specifications	6
12.	Laboratory Conditions	6
13.	Summary	6
14.	Sample Calculations	7
15.	Statement of Conformity	7
16.	Certification	7
17.	Photographs of EUT	8
18.	Equipment List	10
19.	Block Diagram of Test Setup	11
20.	20dB Bandwidth	12
21.	Occupied Bandwidth (99%)	16
22.	Carrier Frequency Separation	20
23.	Number of Carrier Channels	22
24.	Average Time of Occupancy	24
25.	Maximum Peak Conducted Output Power	27
26.	Effective Isotropic Radiated Power (EIRP)	31
27.	Duty Cycle Factor Measurements	33
28.	Case Spurious Radiated Emissions	35
29.	Band-Edge Compliance	49
30.	Scope of Accreditation	57

**This report shall not be reproduced, except in full,
without the written approval of Elite Electronic Engineering Inc.**

1. Report Revision History

Revision	Date	Description
–	12 JUN 2024	Initial Release of Engineering Test Report No. 2400866-01

2. Introduction

2.1. Scope of Tests

This document presents the results of a series of RF emissions tests that were performed on the Trulli Audio Bass50 Portable Subwoofer (hereinafter referred to as the Equipment Under Test (EUT)). The EUT was manufactured and submitted for testing by Trulli Audio located in Mundelein, IL.

2.2. Purpose

The test series was performed to determine if the EUT meets the RF emission requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart B, §15.107 for Receivers and Subpart C, §15.247 for a Frequency Hopping Spread Spectrum intentional radiator operating within the 2400 – 2483.5MHz band.

The test series was also performed to determine if the EUT meets the RF emission requirements of the Innovation, Science, and Economic Development Canada Radio Standards Specification RSS-Gen and RSS-247 for a Frequency Hopping Spread Spectrum intentional radiator operating within the 2400 – 2483.5MHz band.

Testing was performed in accordance with ANSI C63.10-2013.

2.3. Identification of the EUT

The EUT was identified as follows:

EUT Identification	
Product Description	Bass50 Portable Subwoofer
Model/Part No.	BASS50
Serial No.	ACFAA24180001
Size of EUT	20.2" x 15.5" x 7.45"
Software/Firmware Version	1.1
Device Type	Frequency Hopping Transmission Device (SKAA)
Band of Operation	2400 – 2483.5MHz
Modulation Type	FSK
Antenna Type	Bowtie Dipole
Conducted Output Power	8.2dBm
Radiated Output Power (EIRP)	10.1dBm
20dB Bandwidth	2.3MHz
Occupied Bandwidth (99% CBW)	2.3MHz
Emission Classification	2M30F1D
FCC ID	FCC ID: 2AXEJBASS50
ISED Certification Number	IC: 26435-BASS50

The EUT listed above was used throughout the test series.

3. Power Input

The EUT was powered by 16VDC from an internal rechargeable battery.

4. Grounding

The EUT was not connected to ground.

5. Support Equipment

The EUT was submitted for testing along with the following support equipment:

Description	Model #	S/N
Laptop	--	--

6. Interconnect Leads

No interconnect leads were used during the tests.

7. Modifications Made to the EUT

No modifications were made to the EUT during the testing.

8. Modes of Operation

The EUT and all peripheral equipment were energized. The unit was programmed to transmit in one of the following modes:

Mode	Description
SKAA 2403.5MHz	Low channel. Power Setting = 5
SKAA 2440.4MHz	Mid channel. Power Setting = 7
SKAA 2477.3MHz	High channel. Power Setting = 7
SKAA Hopping	SKAA in hopping mode. BT off.

9. Test Specifications

The tests were performed to selected portions of, and in accordance with, the test specifications.

- Federal Communications Commission "Code of Federal Regulations", Title 47, Chapter I, Subchapter A, Part 15, Subpart B
- Federal Communications Commission "Code of Federal Regulations", Title 47, Chapter I, Subchapter A, Part 15, Subpart C
- ANSI C63.4-2014, "American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz"
- ANSI C63.10-2013, "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices"
- Federal Communications Commission Office of Engineering and Technology Laboratory Division, Guidance For Compliance Measurements On Digital Transmission Systems, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.247 April 2, 2019 KDB 558074 D01v05r02
- RSS-Gen Issue 5, February 2020, Amendment 2, Innovation, Science, and Economic Development Canada, "General Requirements for Compliance of Radio Apparatus"
- RSS-247 Issue 2, February 2017, "Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and License-Exempt Local Area Network (LE-LAN) Devices"

10. Test Plan

No test plan was provided. Instructions were provided by personnel from Trulli Audio and used in conjunction with the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247, Innovation, Science, and Economic Development Canada, RSS-247, and ANSI C63.4-2014 specifications.

11. Deviation, Additions to, or Exclusions from Test Specifications

There were no deviations, additions to, or exclusions from the test specifications during this test series.

12. Laboratory Conditions

The ambient parameters of the laboratory during testing were as follows:

Ambient Parameters	Value
Temperature	17°C
Relative Humidity	63%
Atmospheric Pressure	1014mb

13. Summary

The following EMC tests were performed and the results are shown below:

Test Description	Requirements	Test Method	S/N	Results
20dB Bandwidth	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms
Occupied Bandwidth (99%)	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms
Carrier Frequency Separation	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms
Number of Carrier Channels	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms
Average Time of Occupancy	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms
Maximum Peak Conducted Output Power	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms
Effective Isotropic Radiated Power (EIRP)	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms
Duty Cycle Factor Measurements	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	—
Case Spurious Radiated Emissions	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms
Band-Edge Compliance	FCC 15.247 ISED RSS-247	ANSI C63.10:2013	ACFAA24180001	Conforms

Note 1: Per the FCC "Code of Federal Regulations" Title 47, Subchapter A, Part 15, Subpart B, Section 15.101(b), receivers operating above 960MHz are exempt from complying with the technical provisions of §15.5.

14. Sample Calculations

For Powerline Conducted Emissions:

The resultant voltage level (VL) is a summation in decibels (dB) of the receiver meter reading (MTR) and the cable loss factor (CF).

$$\text{Formula 1: VL (dB}\mu\text{V)} = \text{MTR (dB}\mu\text{V)} + \text{CF (dB)}.$$

For Radiated Emissions:

The resultant field strength (FS) is a summation in decibels (dB) of the receiver meter reading (MTR), the antenna correction factor (AF), and the cable loss factor (CF). If an external preamplifier is used, the total is reduced by its gain (-PA). If a distance correction (DC) is required, it is added to the total.

$$\text{Formula 1: FS (dB}\mu\text{V/m)} = \text{MTR (dB}\mu\text{V)} + \text{AF (dB/m)} + \text{CF (dB)} + (-\text{PA (dB)}) + \text{DC (dB)}$$

To convert the Field Strength dB μ V/m term to μ V/m, the dB μ V/m is first divided by 20. The Base 10 AntiLog is taken of this quotient. The result is the Field Strength value in μ V/m terms.

$$\text{Formula 2: FS (}\mu\text{V/m)} = \text{AntiLog} [(\text{FS (dB}\mu\text{V/m)})/20]$$


15. Statement of Conformity

The Trulli Audio Bass50 Portable Subwoofer (Model No. BASS50, Serial No. ACFAA24180001) did fully conform to the selected requirements of FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 and Innovation, Science, and Economic Development Canada, RSS-247.

16. Certification

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the FCC "Code of Federal Regulations" Title 47 Part 15, Subpart C, Section 15.247 and Innovation, Science, and Economic Development Canada, RSS-247 test specifications. The data presented in this test report pertains to the EUT as received by the customer on the test date specified. Any electrical or mechanical modifications made to the EUT subsequent to the specified test date will serve to invalidate the data and void this certification.

17. Photographs of EUT





18. Equipment List

Eq ID	Equipment Description	Manufacturer	Model No.	Serial No.	Frequency Range	Cal Date	Due Date
APW18	PREAMPLIFIER	PLANAR	PE2-30-20G20R6G-3R0-10-12-SFF	PL34312/2148	18-26.5GHZ	2/23/2024	2/23/2025
APW3	PREAMPLIFIER	PLANAR ELECTRONICS	PE2-35-120-5R0-10-12	PL2924	1GHZ-20GHZ	3/20/2024	3/20/2025
CDX8	COMPUTER	ELITE	WORKSTATION			N/A	
CDZ4	LAB WORKSTATION	ELITE	LWS-10		WINDOWS 10	CNR	
GRB0	1MHZ, LISN SIGNAL CHECKER	ELITE	LISNCHKR1M	1	1MHZ	12/6/2022	12/6/2024
GSE3	SIGNAL GENERATOR (40GHZ)	ROHDE & SCHWARZ	SMB100A	183294	100KHZ-40GHZ	1/30/2023	1/30/2025
GSFE	OSP120	ROHDE & SCHWARZ	OSP120	101288	.01-40GHZ	4/4/2023	4/4/2025
NHG1	STANDARD GAIN HORN ANTENNA	NARDA	638	---	18-26.5GHZ	NOTE 1	
NWN0	DOUBLE RIDGED GUIDE ANTENNA	ETS-LINDGREN	3116	00026778	18 - 40 GHZ	12/16/2022	12/16/2024
NWQ0	DOUBLE RIDGED WAVEGUIDE ANTENNA	ETS LINDGREN	3117	66657	1GHZ-18GHZ	6/13/2022	6/13/2024
NWQ1	DOUBLE RIDGED WAVEGUIDE ANTENNA	ETS-LINDGREN	3117	66655	1GHZ-18GHZ	5/26/2022	5/26/2024
PLF2	CISPR16 50UH LISN	ELITE	CISPR16/70A	002	.15-30MHz	3/26/2024	3/26/2025
PLF4	CISPR16 50UH LISN	ELITE	CISPR16/70A	003	.15-30MHz	3/26/2024	3/26/2025
RBG3	EMI ANALYZER	ROHDE & SCHWARZ	ESW44	101592	2HZ-44GHZ	3/7/2024	3/7/2025
RBG4	EMI ANALYZER	ROHDE & SCHWARZ	ESW44	103007	2HZ-44GHZ	3/16/2024	3/16/2025
T1EG	10DB 25W ATTENUATOR	WEINSCHTEL	46-10-34	CD3551	DC-18GHZ	12/19/2023	12/19/2025
VBR8	COMMERCIAL CONDUCTED EMISSIONS.EXE	ELITE				N/A	
WKA1	SOFTWARE, UNIVERSAL RCV EMI	ELITE	UNIV_RCV_EMI	1	---	I/O	
XLJ12	50 OHM, 2W TERMINATION	JFW INDUSTRIES	50T-199	---	DC-2GHZ	12/21/2023	12/21/2025
XPR0	HIGH PASS FILTER	K&L MICROWAVE	11SH10-4800/X20000	001	4.8-20GHZ	9/14/2023	9/14/2025


N/A: Not Applicable

I/O: Initial Only

CNR: Calibration Not Required

NOTE 1: For the purpose of this test, the equipment was calibrated over the specified frequency range, pulse rate, or modulation prior to the test or monitored by a calibrated instrument.

19. Block Diagram of Test Setup



Radiated Measurements Test Setup

20. 20dB Bandwidth


EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz SKAA 2440.4MHz SKAA 2477.3MHz

Test Setup Details	
Setup Format	Tabletop
Height of Support	N/a
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/a
Notes	None


Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Procedure
<p>The antenna port of the EUT was connected to an R&S OSP RF control and switch. With the hopping function disabled, the EUT was allowed to transmit continuously.</p> <p>The frequency hopping channel was set separately to low, middle, and high hopping channels. The resolution bandwidth (RBW) was set to $\geq 1\%$ of the 20dB BW. The span was set to approximately 2 to 3 times the 20dB bandwidth.</p> <p>The 'Max-Hold' function was engaged. The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined. The analyzer's display was then screenshot and saved.</p>


Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz
Frequency Tested	2403.5MHz
Result	20dB BW = 2.231MHz
Notes	None



Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2440.4MHz
Frequency Tested	2440.4MHz
Result	20dB BW = 2.306MHz
Notes	None



Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2477.3MHz
Frequency Tested	2477.3MHz
Result	20dB BW = 2.331MHz
Notes	None



21. Occupied Bandwidth (99%)


EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz SKAA 2440.4MHz SKAA 2477.3MHz

Test Setup Details	
Setup Format	Tabletop
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/a
Type of Antennas Used	N/a
Notes	None


Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Procedure
<p>The antenna port of the EUT was connected to an R&S OSP RF control and switch.</p> <p>The EUT was allowed to transmit continuously. The transmit channel was set separately to low, middle, and high channels. The resolution bandwidth (RBW) was set to 1% to 5% of the actual occupied / x dB bandwidth, the video bandwidth (VBW) was set 3 times greater than the RBW, and the span was set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency.</p> <p>The 'Max-Hold' function was engaged. The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined. The analyzer's display was plotted using a 'screen dump' utility.</p>


Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz
Frequency Tested	2403.5MHz
Result	OBW = 2.281MHz
Notes	None



Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2440.4MHz
Frequency Tested	2440.4MHz
Result	OBW = 2.281MHz
Notes	None



Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2477.3MHz
Frequency Tested	2477.3MHz
Result	OBW = 2.306MHz
Notes	None



22. Carrier Frequency Separation

EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping


Test Setup Details	
Setup Format	Tabletop
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/A
Type of Antennas Used	N/A
Notes	None

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Requirement
Channel carrier frequencies shall be separated by a minimum of 25kHz or the 20dB bandwidth, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

Procedure
<p>The antenna port of the EUT was connected an R&S OSP RF control and switch. With the hopping function enabled, the EUT was allowed to transmit continuously.</p> <p>Span was set wide enough to capture the peaks of two adjacent channels. The resolution bandwidth was set to approximately 30% of the channel spacing. The peak detector and 'Max-Hold' function were engaged. The span was set wide enough to capture the peaks of at least two adjacent channels. When the trace had stabilized after multiple scans, the marker-delta function was used to determine the separation between the peaks of the adjacent channels. The analyzer's display was plotted using a 'screen dump' utility.</p>

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping
Frequency Tested	2440MHz
Result	Separation = 153.8kHz
Notes	None



23. Number of Carrier Channels

EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping


Test Setup Details	
Setup Format	Tabletop
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/A
Type of Antennas Used	N/A
Notes	None

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Requirements
The system shall use at least 15 hopping frequencies.

Procedure
<p>The antenna port of the EUT was connected to an R&S OSP RF control and switch. With the hopping function enabled, the EUT was allowed to transmit continuously.</p> <p>The resolution bandwidth (RBW) was set to less than 30% of the channel spacing or the 20dB bandwidth, whichever is smaller. The peak detector and 'Max-Hold' function were engaged. The span was set wide enough to capture the entire frequency band of operation.</p> <p>The EUT's signal was allowed to stabilize after multiple scans. The number of hopping frequencies was counted. The analyzer's display was plotted using a 'screen dump' utility.</p>

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping
Frequency Tested	2440MHz
Result	49 hopping frequencies
Notes	None



24. Average Time of Occupancy

EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping


Test Setup Details	
Setup Format	Tabletop
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/a
Type of Antennas Used	N/a
Notes	None


Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Requirements
The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Procedure
The antenna port of the EUT was connected to an R&S OSP RF control and switch. With the hopping function enabled, the EUT was allowed to transmit continuously.
The spectrum analyzer was set to zero span centered on a hopping channel. The resolution bandwidth (RBW) was set \geq to the channel spacing. The sweep was set to capture the entire dwell time per hopping channel. The peak detector and 'Max-Hold' function were engaged. The analyzer's display was plotted using a 'screen dump' utility.

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping
Frequency Tested	SKAA 2440.4MHz
Result	Ave. Time of Occupancy = 377.4ms
Notes	74 pulses





25. Maximum Peak Conducted Output Power

EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz SKAA 2440.4MHz SKAA 2477.3MHz

Test Setup Details	
Setup Format	Tabletop
Measurement Method	Antenna Conducted
Type of Test Site	Tabletop
Test Site Used	N/a
Notes	None


Requirements
The output power shall not exceed 125mW (21dBm).

Procedure
The antenna port of the EUT was connected to an R&S OSP RF control and switch. With the hopping function disabled, the EUT was allowed to transmit continuously. The frequency hopping channel was set separately to low, middle, and high hopping channels. The resolution bandwidth (RBW) was set to greater than the 20dB bandwidth. The span was set to approximately 5 times the 20dB bandwidth. The 'Max-Hold' function was engaged. The maximum meter reading was recorded. The peak power output was calculated for the low, middle, and high hopping frequencies.

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz
Frequency Tested	2403.5MHz
Result	Output Power = 5mW (7dBm)
Notes	None

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2403.500000	7.0	21.0	PASS


Peak Power



— Connector 1 X Peak Connector 1


Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2440.4MHz
Frequency Tested	2440.4MHz
Result	Output Power = 6.6mW (8.2dBm)
Notes	None

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2440.400000	8.2	21.0	PASS



Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2477.3MHz
Frequency Tested	2477.3MHz
Result	Output Power = 5.6mW (7.5dBm)
Notes	None

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2477.300000	7.5	21.0	PASS



26. Effective Isotropic Radiated Power (EIRP)

EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz SKAA 2440.4MHz SKAA 2477.3MHz

Test Setup Details	
Setup Format	Tabletop
Measurement Method	Radiated
Type of Test Site	Semi-Anechoic Chamber
Test Site Used	Room #21
Type of Antennas Used	Above 1GHz: Double-ridged waveguide (or equivalent)
Notes	None

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Requirements
The output power shall not exceed 500mW (27dBm).

Procedure
<p>The EUT was placed on the non-conductive stand and set to transmit. A double ridged waveguide antenna was placed at a test distance of 3 meters from the EUT. The resolution bandwidth (RBW) of the spectrum analyzer was set to greater than the 20dB bandwidth. The span was set to approximately 5 times the 20 dB bandwidth. The EUT was maximized for worst case emissions (or maximum output power) at the measuring antenna. The maximum meter reading was recorded. The peak power output was measured for the low, middle, and high hopping frequencies.</p> <p>The equivalent power was determined from the field intensity levels measured at 3 meters using the substitution method. To determine the emission power, a double ridged waveguide antenna was then set in place of the EUT and connected to a calibrated signal generator. The output of the signal generator was adjusted to match the received level at the spectrum analyzer. The signal level was recorded. The reading was then corrected to compensate for cable loss (and antenna gain for all measurements above 1GHz), as required. The peak power output was calculated for low, middle, and high hopping frequencies.</p>

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz SKAA 2440.4MHz SKAA 2477.3MHz
Result	Max EIRP = 10.2mW (10.1dBm)
Notes	None

Freq (MHz)	Ant Pol	Wide BW Meter Reading (dBμV)	Matched Sig Gen Reading (dBm)	Equivalent Antenna Gain (dB)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2403.50	H	69.0	7.2	5.3	2.7	9.8	27.0	-17.2
	V	65.6	4.3	5.3	2.7	6.9	27.0	-20.1
2440.40	H	66.1	4.3	5.2	2.8	6.7	27.0	-20.3
	V	61.6	0.5	5.2	2.8	2.9	27.0	-24.1
2477.30	H	68.8	7.8	5.2	2.8	10.1	27.0	-16.9
	V	64.8	4.2	5.2	2.8	6.6	27.0	-20.4

27. Duty Cycle Factor Measurements


EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz

Test Setup Details	
Setup Format	Tabletop
Measurement Method	Radiated
Type of Test Site	Semi-Anechoic Chamber
Type of Antennas Used	Above 1GHz: Double-Ridged Waveguide (or equivalent)
Notes	None

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Procedure
<p>The duty cycle factor is used to convert peak detected readings to average readings when pulsed modulation is employed. This factor is computed from the time domain trace of the pulse modulation signal.</p> <p>With the transmitter set up to transmit for maximum pulse density, the time domain trace is displayed on the spectrum analyzer. This trace is obtained by tuning center frequency to the transmitter frequency and then setting a zero span width with 10msec/div. The amplitude settings are adjusted so that the on/off transitions clear the 4th division from the bottom of the display. The markers are set at the beginning and end of the “on-time”. The trace is recorded.</p> <p>Next the spectrum analyzer center frequency is set to the transmitter frequency with a zero span width and 10msec/div. This shows if the word is longer than 100msec or shorter than 100msec. If the word period is less than 100msec, the display is set to show at least one word. The on-time and off-time are then measured. The on-time is total time signal level exceeds the 4th division. Off-time is time under for the word period.</p> <p>The duty cycle is then computed as $\left(\frac{On\ Time}{Word\ Period}\right)$, where $Word\ Period = (On\ Time + Off\ Time)$.</p>

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz
Frequency Tested	2403.5MHz
Result	Duty Cycle = -20.53dB
Notes	On Time = 2 x 4.7 = 9.4 Duty Cycle Factor Calculation: $\text{Duty Cycle Factor} = 20 \log \left(\frac{9.4\text{ms}}{100\text{ms}} \right) = -20.53\text{dB}$



28. Case Spurious Radiated Emissions

EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz, SKAA 2440.4MHz, SKAA 2477.3MHz

Test Setup Details	
Setup Format	Tabletop
Type of Test Site	Semi-Anechoic Chamber
Test Site Used	Room 21
Type of Antennas Used	1 – 18GHz: Double-Ridged Waveguide (or equivalent) Above 18GHz: Horn (or equivalent)
Notes	N/a

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1
Radiated disturbance (electric field strength on an open area test site or alternative test site) (6 GHz – 18 GHz)	3.2
Radiated disturbance (electric field strength on an open area test site or alternative test site) (18 GHz – 26.5 GHz)	3.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (26.5 GHz – 40 GHz)	3.4

Procedure

Radiated measurements were performed in a 32ft. x 20ft. x 14ft. high shielded enclosure. The shielded enclosure prevents emissions from other sources, such as radio and TV stations from interfering with the measurements. All powerlines and signal lines entering the enclosure pass through filters on the enclosure wall. The powerline filters prevent extraneous signals from entering the enclosure on these leads.

Preliminary radiated emissions tests were performed to determine the emission characteristics of the EUT. For the preliminary test, a broadband measuring antenna was positioned at a 3 meter distance from the EUT. The entire frequency range from 30MHz to 25GHz used for 2400-2483.5MHz range was investigated using a peak detector function.

The final open field emission tests were then manually performed over the frequency range of 30MHz to 26.5GHz used for 2400-2483.5MHz range.

1) For all harmonics not in the restricted bands, the following procedure was used:

- a) The field strength of the fundamental was measured using a double ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on a 1.5 meter high non-conductive stand. A peak detector with a resolution bandwidth of 100 kHz was used on the spectrum analyzer.
- b) The field strengths of all of the harmonics not in the restricted band were then measured using a double-ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on a 1.5 meter high non-conductive stand. A peak detector with a resolution bandwidth of 100kHz was used on the spectrum analyzer.
- c) To ensure that maximum or worst case emission levels at the fundamental and harmonics were measured, the following steps were taken when measuring the fundamental emissions and the spurious emissions:
 - i) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - ii) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
 - iii) The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.
 - iv) In instances where it was necessary to use a shortened cable between the measuring antenna and the spectrum analyzer, the measuring antenna was not raised or lowered to ensure maximized readings. Instead, the EUT was rotated through all axis to ensure the maximum readings were recorded for the EUT.
- d) All harmonics not in the restricted bands must be at least 20dB below levels measured at the fundamental. However, attenuation below the general limits specified in §15.209(a) is not required.

2) For all emissions in the restricted bands, the following procedure was used:

- a) The field strengths of all emissions below 1GHz were measured using a bi-log antenna. The bi-log antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on an 80cm high non-conductive stand. A peak detector with a resolution bandwidth of 100 kHz was used on the spectrum analyzer.
- b) The field strengths of all emissions above 1GHz were measured using a double-ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. The EUT was placed on a 1.5 meter high non-conductive stand. A peak detector with a resolution bandwidth of 1MHz was used on the spectrum analyzer.
- c) To ensure that maximum or worst case emission levels were measured, the following steps were taken when taking all measurements:
 - i) The EUT was rotated so that all of its sides were exposed to the receiving antenna.

- ii) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
 - iii) The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.
 - iv) In instances where it was necessary to use a shortened cable between the measuring antenna and the spectrum analyzer, the measuring antenna was not raised or lowered to ensure maximized readings. Instead, the EUT was rotated through all axis to ensure the maximum readings were recorded for the EUT.
- d) For all radiated emissions measurements below 1GHz, if the peak reading is below the limits listed in §15.209(a), no further measurements are required. If, however, the peak readings exceed the limits listed in §15.209(a), then the emissions are remeasured using a quasi-peak detector.
- e) For all radiated emissions measurements above 1GHz, the peak readings must comply with the §15.35(b) limits. §15.35(b) states that when average radiated emissions measurements are specified, there also is a limit on the peak level of the radiated emissions. The limit on the peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. Therefore, all peak readings above 1GHz must be no greater than 20dB above the limits specified in §15.209(a).
- f) Next, for all radiated emissions measurements above 1GHz, the resolution bandwidth was set to 1MHz. The analyzer was set to linear mode with a 10Hz video bandwidth in order to simulate an average detector. An average reading was taken.

If the dwell time per channel of the hopping signal is less than 100msec, then the reading obtained with the 10Hz video bandwidth may be further adjusted by a duty cycle correction factor derived from $20 \cdot \log(\text{dwell time}/100\text{msec})$. These readings must be no greater than the limits specified in §15.209(a).



Test Setup for Spurious Radiated Emissions, 1 – 18GHz – Antenna Polarization
Horizontal



Test Setup for Spurious Radiated Emissions, 1 – 18GHz – Antenna Polarization
Vertical



Test Setup for Spurious Radiated Emissions, Above 18GHz – Antenna Polarization Horizontal



Test Setup for Spurious Radiated Emissions, Above 18GHz – Antenna Polarization Vertical

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz
Frequency Tested	2403.5MHz
Notes	Peak Measurements in the Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dBμV/m)	Peak Total at 3m (μV/m)	Peak Limit at 3m (μV/m)	Margin (dB)
4807.00	H	70.2		4.8	34.7	-39.0	70.8	3479.2	5000.0	-3.1
	V	66.2		4.8	34.7	-39.0	66.8	2182.7	5000.0	-7.2
12017.50	H	50.7	*	8.0	39.0	-38.6	59.2	910.5	5000.0	-14.8
	V	50.5	*	8.0	39.0	-38.6	59.0	888.8	5000.0	-15.0
19228.00	H	39.6	*	2.0	40.4	-27.6	54.4	526.4	5000.0	-19.6
	V	39.4	*	2.0	40.4	-27.6	54.2	512.6	5000.0	-19.8

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz
Frequency Tested	2403.5MHz
Notes	Average Measurements in the Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle Factor (dB)	Average Total at 3m (dB μ V/m)	Average Total at 3m (μ V/m)	Average Limit at 3m (μ V/m)	Margin (dB)
4807.00	H	70.24		4.8	34.7	-39.0	-20.5	50.3	327.3	500.0	-3.7
	V	66.20		4.8	34.7	-39.0	-20.5	46.3	205.6	500.0	-7.7
12017.50	H	50.73	*	8.0	39.0	-38.6	-20.5	38.7	85.7	500.0	-15.3
	V	50.52	*	8.0	39.0	-38.6	-20.5	38.4	83.6	500.0	-15.5
19228.00	H	39.64	*	2.0	40.4	-27.6	-20.5	33.9	49.5	500.0	-20.1
	V	39.41	*	2.0	40.4	-27.6	-20.5	33.7	48.2	500.0	-20.3

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz
Frequency Tested	2403.5MHz
Notes	Peak Measurements in Non-Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dB μ V/m)	Peak Total at 3m (μ V/m)	Peak Limit at 3m (μ V/m)	Margin (dB)
7210.50	H	40.98	*	6.1	35.7	-39.0	43.8	155.4	12477.8	-38.1
	V	39.74	*	6.1	35.7	-39.0	42.6	134.7	12477.8	-39.3
9614.00	H	39.79	*	6.8	36.7	-38.8	44.5	167.4	12477.8	-37.4
	V	39.43	*	6.8	36.7	-38.8	44.1	160.6	12477.8	-37.8
14421.00	H	39.22	*	8.7	39.9	-37.9	50.0	315.7	12477.8	-31.9
	V	39.61	*	8.7	39.9	-37.9	50.4	330.2	12477.8	-31.5
16824.50	H	38.82	*	9.4	42.7	-37.3	53.6	480.2	12477.8	-28.3
	V	38.58	*	9.4	42.7	-37.3	53.4	467.1	12477.8	-28.5
21631.50	H	26.75	*	1.8	40.6	-25.3	43.8	155.8	12477.8	-38.1
	V	26.00	*	1.8	40.6	-25.3	43.1	142.9	12477.8	-38.8
24035.00	H	27.84	*	2.2	40.6	-25.2	45.5	187.7	12477.8	-36.5
	V	27.57	*	2.2	40.6	-25.2	45.2	182.0	12477.8	-36.7

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2440.4MHz
Frequency Tested	2440.4MHz
Notes	Peak Measurements in the Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dBμV/m)	Peak Total at 3m (μV/m)	Peak Limit at 3m (μV/m)	Margin (dB)
4880.80	H	67.0		4.9	34.6	-39.0	67.5	2358.4	5000.0	-6.5
	V	66.2		4.9	34.6	-39.0	66.7	2158.3	5000.0	-7.3
7321.20	H	50.5	*	6.2	35.7	-39.0	53.4	468.4	5000.0	-20.6
	V	49.9	*	6.2	35.7	-39.0	52.8	438.7	5000.0	-21.1
12202.00	H	50.0	*	8.0	39.1	-38.5	58.6	850.2	5000.0	-15.4
	V	49.7	*	8.0	39.1	-38.5	58.2	814.7	5000.0	-15.8
19523.20	H	38.3	*	2.0	40.4	-27.6	53.1	450.2	5000.0	-20.9
	V	38.4	*	2.0	40.4	-27.6	53.2	458.0	5000.0	-20.8

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2440.4MHz
Frequency Tested	2440.4MHz
Notes	Average Measurements in the Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle Factor (dB)	Average Total at 3m (dB μ V/m)	Average Total at 3m (μ V/m)	Average Limit at 3m (μ V/m)	Margin (dB)
4880.80	H	67.01		4.9	34.6	-39.0	-20.5	46.9	221.9	500.0	-7.1
	V	66.24		4.9	34.6	-39.0	-20.5	46.2	203.1	500.0	-7.8
7321.20	H	50.51	*	6.2	35.7	-39.0	-20.5	32.9	44.1	500.0	-21.1
	V	49.94	*	6.2	35.7	-39.0	-20.5	32.3	41.3	500.0	-21.7
12202.00	H	50.02	*	8.0	39.1	-38.5	-20.5	38.1	80.0	500.0	-15.9
	V	49.65	*	8.0	39.1	-38.5	-20.5	37.7	76.6	500.0	-16.3
19523.20	H	38.28	*	2.0	40.4	-27.6	-20.5	32.5	42.4	500.0	-21.4
	V	38.43	*	2.0	40.4	-27.6	-20.5	32.7	43.1	500.0	-21.3

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2440.4MHz
Frequency Tested	2440.4MHz
Notes	Peak Measurements in Non-Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dBμV/m)	Peak Total at 3m (μV/m)	Peak Limit at 3m (μV/m)	Margin (dB)
9761.60	H	38.03	*	6.9	36.9	-38.8	43.0	141.8	11202.9	-38.0
	V	38.68	*	6.9	36.9	-38.8	43.7	152.8	11202.9	-37.3
14642.40	H	39.67	*	8.8	40.2	-37.8	50.8	348.7	11202.9	-30.1
	V	39.76	*	8.8	40.2	-37.8	50.9	352.3	11202.9	-30.0
17082.80	H	38.85	*	9.5	41.9	-37.4	52.9	441.2	11202.9	-28.1
	V	38.17	*	9.5	41.9	-37.4	52.2	408.0	11202.9	-28.8
21963.60	H	27.81	*	2.1	40.6	-25.3	45.2	181.9	11202.9	-35.8
	V	27.43	*	2.1	40.6	-25.3	44.8	174.1	11202.9	-36.2
24404.00	H	26.95	*	2.1	40.6	-25.2	44.5	167.7	11202.9	-36.5
	V	26.83	*	2.1	40.6	-25.2	44.4	165.4	11202.9	-36.6

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2477.3MHz
Frequency Tested	2477.3MHz
Notes	Peak Measurements in the Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dBμV/m)	Peak Total at 3m (μV/m)	Peak Limit at 3m (μV/m)	Margin (dB)
4954.60	H	64.2		4.9	34.4	-39.0	64.5	1677.8	5000.0	-9.5
	V	63.3		4.9	34.4	-39.0	63.7	1523.1	5000.0	-10.3
7431.90	H	51.2	*	6.2	35.7	-39.0	54.1	507.8	5000.0	-19.9
	V	50.1	*	6.2	35.7	-39.0	53.0	446.9	5000.0	-21.0
12386.50	H	50.2	*	8.0	38.9	-38.5	58.6	852.9	5000.0	-15.4
	V	50.6	*	8.0	38.9	-38.5	59.0	896.2	5000.0	-14.9
19818.40	H	39.8	*	2.0	40.4	-27.6	54.5	533.4	5000.0	-19.4
	V	36.7	*	2.0	40.4	-27.6	51.5	374.2	5000.0	-22.5
22295.70	H	38.3	*	1.8	40.6	-25.3	55.5	595.0	5000.0	-18.5
	V	38.1	*	1.8	40.6	-25.3	55.3	580.8	5000.0	-18.7

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2477.3MHz
Frequency Tested	2477.3MHz
Notes	Average Measurements in the Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle Factor (dB)	Average Total at 3m (dBμV/m)	Average Total at 3m (μV/m)	Average Limit at 3m (μV/m)	Margin (dB)
4954.60	H	64.18		4.9	34.4	-39.0	-20.5	44.0	157.8	500.0	-10.0
	V	63.34		4.9	34.4	-39.0	-20.5	43.1	143.3	500.0	-10.9
7431.90	H	51.17	*	6.2	35.7	-39.0	-20.5	33.6	47.8	500.0	-20.4
	V	50.06	*	6.2	35.7	-39.0	-20.5	32.5	42.0	500.0	-21.5
12386.50	H	50.20	*	8.0	38.9	-38.5	-20.5	38.1	80.2	500.0	-15.9
	V	50.63	*	8.0	38.9	-38.5	-20.5	38.5	84.3	500.0	-15.5
19818.40	H	39.76	*	2.0	40.4	-27.6	-20.5	34.0	50.2	500.0	-20.0
	V	36.68	*	2.0	40.4	-27.6	-20.5	30.9	35.2	500.0	-23.0
22295.70	H	38.33	*	1.8	40.6	-25.3	-20.5	35.0	56.0	500.0	-19.0
	V	38.12	*	1.8	40.6	-25.3	-20.5	34.8	54.6	500.0	-19.2

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2477.3MHz
Frequency Tested	2477.3MHz
Notes	Peak Measurements in Non-Restricted Bands

Freq (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dBμV/m)	Peak Total at 3m (μV/m)	Peak Limit at 3m (μV/m)	Margin (dB)
9909.20	H	38.53	*	7.0	37.1	-38.8	43.8	154.0	12256.6	-38.0
	V	39.05	*	7.0	37.1	-38.8	44.3	163.5	12256.6	-37.5
14863.80	H	39.10	*	8.9	40.1	-37.8	50.4	329.5	12256.6	-31.4
	V	39.12	*	8.9	40.1	-37.8	50.4	330.3	12256.6	-31.4
17341.10	H	39.33	*	9.7	41.7	-37.5	53.1	454.3	12256.6	-28.6
	V	39.44	*	9.7	41.7	-37.5	53.3	460.1	12256.6	-28.5
24773.00	H	28.13	*	2.4	40.6	-25.2	45.9	197.5	12256.6	-35.9
	V	26.45	*	2.4	40.6	-25.2	44.2	162.7	12256.6	-37.5

29. Band-Edge Compliance

EUT Information	
Manufacturer	Trulli Audio
Product	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping SKAA 2403.5MHz SKAA 2477.3MHz

Test Setup Details	
Setup Format	Tabletop
Measurement Method	Radiated Antenna Conducted
Type of Test Site	Semi-Anechoic Chamber Elite Test Bench
Type of Antennas Used	Double-Ridged Waveguide (or equivalent)
Notes	None

Measurement Uncertainty	
Measurement Type	Expanded Measurement Uncertainty
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1000 MHz)	4.3
Radiated disturbance (electric field strength on an open area test site or alternative test site) (1 GHz – 6 GHz)	3.1

Procedure
<p>1) Low Band Edge:</p> <ol style="list-style-type: none"> a) The antenna port of the EUT was connected to an R&S OSP RF control and switch. b) The EUT was set to transmit continuously at the channel closest to the low band-edge, hopping function disabled. c) To determine the band edge compliance, the following spectrum analyzer settings were used: <ul style="list-style-type: none"> o Center Frequency = 2400MHz (low band-edge frequency). o Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation. o Resolution Bandwidth (RBW) = $\geq 1\%$ of the span. o 'Max-Hold' function was engaged. d) The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined. e) The marker was set on the peak of the in-band emissions. A display line was placed 20dB down from the peak of the in-band emissions. All emissions which fall outside of the authorized band of operation must be below the 20dB down display line. (All emissions to the left of the center frequency (band-edge) must be below the display line.) f) The analyzer's display was then screenshot and saved. g) Steps (d) through (f) were repeated with the frequency hopping function enabled.


2) High Band Edge:

- a) The EUT was setup inside the test chamber on a non-conductive stand and set to transmit continuously at the channel closest to the high band-edge, hopping function disabled.
- b) A broadband measuring antenna was placed at a test distance of 3 meters from the EUT. The antenna was connected to the input of a spectrum analyzer.
- c) The center frequency of the analyzer was set to the high band edge (2483.5MHz).
- d) The Resolution Bandwidth was set to 1MHz.
- e) To ensure that the maximum or worst case emission level was measured, the following steps were taken:
 - o The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - o Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
 - o The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - o The measuring antenna was raised and lowered from 1 to 4 meters for each antenna polarization to maximize the readings.
 - o The highest measured peak reading and the highest measured average reading were recorded.
- f) Steps (a) through (e) were repeated with the frequency hopping function enabled.

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping
Frequency Tested	2483.5MHz
Notes	High Band Edge

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2489.217325	-48.2	36.2	-12.0	PASS
2485.455927	-48.3	36.3	-12.0	PASS
2485.405775	-48.5	36.5	-12.0	PASS
2489.167173	-48.7	36.7	-12.0	PASS
2486.458967	-48.9	36.9	-12.0	PASS
2486.408815	-49.3	37.3	-12.0	PASS
2485.506079	-50.1	38.1	-12.0	PASS
2489.267477	-50.6	38.5	-12.0	PASS
2486.509119	-51.3	39.3	-12.0	PASS
2487.010638	-51.4	39.4	-12.0	PASS
2488.565350	-51.5	39.5	-12.0	PASS
2490.120061	-51.7	39.7	-12.0	PASS
2490.069909	-51.7	39.7	-12.0	PASS
2493.179331	-51.8	39.7	-12.0	PASS
2492.427052	-51.8	39.8	-12.0	PASS

Band Edge




— Limit — Sum Level × Fail

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2477.3MHz
Frequency Tested	2483.5MHz
Notes	High Band Edge

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2484.452888	-43.4	31.6	-11.8	PASS
2484.402736	-43.4	31.6	-11.8	PASS
2484.352584	-44.1	32.3	-11.8	PASS
2483.550152	-45.2	33.4	-11.8	PASS
2484.503040	-45.3	33.5	-11.8	PASS
2483.600304	-46.3	34.5	-11.8	PASS
2485.455927	-46.8	35.0	-11.8	PASS
2485.405775	-47.3	35.5	-11.8	PASS
2485.506079	-48.0	36.2	-11.8	PASS
2483.650456	-48.4	36.7	-11.8	PASS
2484.302432	-48.8	37.0	-11.8	PASS
2483.700608	-48.8	37.0	-11.8	PASS
2484.252280	-49.4	37.6	-11.8	PASS
2484.202128	-49.7	37.9	-11.8	PASS
2486.458967	-50.1	38.3	-11.8	PASS

Band Edge



— Limit — Sum Level × Fail

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping
Frequency Tested	2483.5MHz
Notes	High Band Edge – Peak and Average Measurements

Freq (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dBμV/m)	Peak Total at 3m (μV/m)	Peak Limit at 3m (μV/m)	Margin (dBm)
2483.50	H	25.0	FH	3.5	32.9	0.0	61.4	1179.1	5000.0	-12.5
	V	25.3	FH	3.5	32.9	0.0	61.7	1220.5	5000.0	-12.2

Freq (MHz)	Ant Pol	Meter Reading (dBμV)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle Factor (dB)	Average Total at 3m (dBμV/m)	Average Total at 3m (μV/m)	Average Limit at 3m (μV/m)	Margin (dB)
2483.50	H	24.98	FH	3.5	32.9	0.0	-26.6	34.8	55.1	500.0	-19.1
	V	25.28	FH	3.5	32.9	0.0	-26.6	35.1	57.1	500.0	-18.8

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2477.3MHz
Frequency Tested	2483.5MHz
Notes	High Band Edge – Peak and Average Measurements


Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	Cable Factor (dB)	Antenna Factor (dB/m)	Pre Amp (dB)	Peak Total at 3m (dB μ V/m)	Peak Total at 3m (μ V/m)	Peak Limit at 3m (μ V/m)	Margin (dBm)
2483.50	H	29.4	*	3.5	32.9	0.0	65.8	1959.0	5000.0	-8.1
	V	26.4	*	3.5	32.9	0.0	62.8	1380.5	5000.0	-11.2

Freq (MHz)	Ant Pol	Meter Reading (dB μ V)	Ambient	CBL Fac (dB)	Ant Fac (dB/m)	Pre Amp (dB)	Duty Cycle Factor (dB)	Average Total at 3m (dB μ V/m)	Average Total at 3m (μ V/m)	Average Limit at 3m (μ V/m)	Margin (dB)
2483.50	H	29.39	*	3.5	32.9	0.0	-26.6	39.2	91.6	500.0	-14.7
	V	26.35	*	3.5	32.9	0.0	-26.6	36.2	64.6	500.0	-17.8

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA Hopping
Frequency Tested	2400MHz
Notes	Low Band Edge

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.099500	-51.6	39.7	-12.0	PASS
2399.399666	-51.7	39.7	-12.0	PASS
2399.549750	-51.8	39.8	-12.0	PASS
2399.449694	-52.1	40.1	-12.0	PASS
2399.499722	-52.2	40.2	-12.0	PASS
2399.649805	-52.2	40.3	-12.0	PASS
2399.049472	-52.3	40.3	-12.0	PASS
2399.149528	-52.4	40.4	-12.0	PASS
2399.599778	-52.4	40.4	-12.0	PASS
2399.699833	-52.4	40.5	-12.0	PASS
2399.949972	-52.5	40.6	-12.0	PASS
2398.849361	-53.0	41.0	-12.0	PASS
2398.899389	-53.1	41.2	-12.0	PASS
2398.699277	-53.4	41.4	-12.0	PASS
2357.426348	-53.4	41.5	-12.0	PASS

Band Edge




— Limit — Sum Level × Fail

Test Details	
Manufacturer	Trulli Audio
EUT	Bass50 Portable Subwoofer
Model No.	BASS50
Serial No.	ACFAA24180001
Mode	SKAA 2403.5MHz
Frequency Tested	2400MHz
Notes	Low Band Edge

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.499722	-30.7	18.6	-12.0	PASS
2399.449694	-30.7	18.7	-12.0	PASS
2399.549750	-31.6	19.5	-12.0	PASS
2399.399666	-33.2	21.2	-12.0	PASS
2399.649805	-35.1	23.1	-12.0	PASS
2399.599778	-35.3	23.2	-12.0	PASS
2398.449138	-35.4	23.4	-12.0	PASS
2398.499166	-35.8	23.8	-12.0	PASS
2398.399111	-36.4	24.4	-12.0	PASS
2399.699833	-36.5	24.4	-12.0	PASS
2399.349639	-37.5	25.5	-12.0	PASS
2398.549194	-37.8	25.7	-12.0	PASS
2399.749861	-38.0	26.0	-12.0	PASS
2399.299611	-38.7	26.6	-12.0	PASS
2397.448583	-39.2	27.2	-12.0	PASS

Band Edge



30. Scope of Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

ELITE ELECTRONIC ENGINEERING, INC.
1516 Centre Circle
Downers Grove, IL 60515
Robert Bugielski (QA Manager) Phone: 630 495 9770 ext. 168
Email: rbugielski@elitetest.com
Craig Fanning (EMC Lab Manager) Phone: 630 495 9770 ext. 112
Email: cfanning@elitetest.com
Brandon Lugo (Automotive Team Leader) Phone: 630 495 9770 ext. 163
Email: blugo@elitetest.com
Richard King (FCC/Commercial Team Leader) Phone: 630 495 9770 ext. 123
Email: reking@elitetest.com
Website: www.elitetest.com

ELECTRICAL

Valid To: June 30, 2025

Certificate Number: 1786.01

In recognition of the successful completion of the A2LA Accreditation Program evaluation process, accreditation is granted to this laboratory to perform the following automotive electromagnetic compatibility and other electrical tests:

Test Technology:**Test Method(s)¹:**

Transient Immunity
(Max Voltage 60V/Max current 100A)

ISO 7637-2 (including emissions); ISO 7637-3;
ISO 16750-2:2012, Sections 4.6.3 and 4.6.4;
CS-11979, Section 6.4; CS.00054, Section 5.9;
EMC-CS-2009.1 (CI220); FMC1278 (CI220, CI221, CI222);
GMW 3097, Section 3.5; SAE J1113-11; SAE J1113-12;
ECE Regulation 10.06 Annex 10

Electrostatic Discharge (ESD)
(Up to +/-25kV)

ISO 10605 (2001, 2008);
CS-11979 Section 7.0; CS.00054, Section 5.10;
EMC-CS-2009.1 (CI 280); FMC1278 (CI280); SAE J1113-13;
GMW 3097 Section 3.6

Conducted Emissions

CISPR 25 (2002, 2008), Sections 6.2 and 6.3;
CISPR 25 (2016), Sections 6.3 and 6.4;
CS-11979, Section 5.1; CS.00054, Sections 5.6.1 and 5.6.2;
GMW 3097, Section 3.3.2;
EMC-CS-2009.1 (CE 420); FMC1278 (CE420, CE421,
CE 430, CE440)

(A2LA Cert. No. 1786.01) 08/15/2023



Page 1 of 9

5202 Presidents Court, Suite 220 | Frederick, MD 21703-8515 | Phone: 301 644 3248 | Fax: 240 454 9449 | www.A2LA.org

Test Technology:

Test Method(s)¹:

*Radiated Emissions Anechoic
(Up to 6GHz)*

CISPR 25 (2002, 2008), Section 6.4;
CISPR 25 (2016), Section 6.5;
CS-11979, Section 5.3; CS.00054, Section 5.6.3;
GMW 3097, Section 3.3.1;
EMC-CS-2009.1 (RE 310); FMC1278 (RE310, RE320);

Vehicle Radiated Emissions

CISPR 12; CISPR 36; ICES-002;
ECE Regulation 10.06 Annex 5

*Bulk Current Injection (BCI)
(1 to 400MHz 500mA)*

ISO 11452-4; CS-11979, Section 6.1; CS.00054, Section 5.8.1;
GMW 3097, Section 3.4.1; SAE J1113-4;
EMC-CS-2009.1 (RI112); FMC1278 (RI112);
ECE Regulation 10.06 Annex 9

*Radiated Immunity Anechoic
(Up to 6GHz and 200V/m)
(Including Radar Pulse 600V/m)*

ISO 11452-2;
CS-11979, Section 6.2; CS.00054, Section 5.8.2;
GMW 3097, Section 3.4.2;
EMC-CS-2009.1 (RI114); FMC1278 (RI114); SAE J1113-21;
ECE Regulation 10.06 Annex 9

Radiated Immunity Magnetic Field

ISO 11452-8; FMC 1278 (RI140)

*Radiated Immunity Reverb
(360MHz to 6GHz and 100V/m)*

ISO/IEC 61000-4-21; GMW 3097, Section 3.4.3;
EMC-CS-2009.1 (RI114); FMC1278 (RI114);
ISO 11452-11

*Radiated Immunity
(Portable Transmitters)
(Up to 6GHz and 20W)*

ISO 11452-9;
EMC-CS-2009.1 (RI115); FMC1278 (RI115);
GMW 3097, Sec 3.4.4

Vehicle Radiated Immunity (ALSE)

ISO 11451-2; ECE Regulation 10.06 Annex 6

*Vehicle Product Specific EMC
Standards*

EN 14982; EN ISO 13309; ISO 13766; EN 50498;
EC Regulation No. 2015/208; EN 55012

Electrical Loads

ISO 16750-2

Stripline

ISO 11452-5

*Transverse Electromagnetic (TEM)
Cell*

ISO 11452-3

Test Technology:

Test Method(s)¹:

Emissions

Radiated and Conducted
(3m Semi-anechoic chamber,
up to 40 GHz)

47 CFR, FCC Part 15 B (using ANSI C63.4:2014);
47 CFR, FCC Part 18 (using FCC MP-5:1986);
ICES-001; ICES-003; ICES-005;
IEC/CISPR 11, Ed. 4.1 (2004-06); AS/NZS CISPR 11 (2004);
IEC/CISPR 11 Ed 5 (2009-05) + A1 (2010);
KN 11 (2008-5) with RRL Notice No. 2008-3 (May 20, 2008);
CISPR 11; EN 55011; KS C 9811; CNS 13803 (1997, 2003);
CISPR 14-1; EN 55014-1; AS/NZS CISPR 14.1;
CISPR 16-2-1 (2008); CISPR 16-2-1; KS C 9814-1; KN 14-1;
IEC/CISPR 22 (1997);
EN 55022 (1998) + A1(2000);
EN 55022 (1998) + A1(2000) + A2(2003); EN 55022 (2006);
IEC/CISPR 22 (2008-09); AS/NZS CISPR 22 (2004);
AS/NZS CISPR 22, 3rd Edition (2006); KN 22 (up to 6 GHz);
CNS 13438 (up to 6 GHz); VCCI V-3 (up to 6 GHz);
CISPR 32; EN 55032; KS C 9832; KN 32;
ECE Regulation 10.06 Annex 7 (Broadband);
ECE Regulation 10.06 Annex 8 (Narrowband);
ECE Regulation 10.06 Annex 14 (Conducted)

Cellular Radiated Spurious Emissions

ETSI TS 151 010-1 GSM; 3GPP TS 51.010-1, Sec 12;
ETSI TS 134 124 UMTS; 3GPP TS 34.124;
ETSI TS 136 124 LTE; E-UTRA; 3GPP TS 36.124

Current Harmonics

IEC 61000-3-2; IEC 61000-3-12;
EN 61000-3-2; KN 61000-3-2;
KS C 9610-3-2; ECE Regulation 10.06 Annex 11

Flicker and Fluctuations

IEC 61000-3-3; IEC 61000-3-11;
EN 61000-3-3; KN 61000-3-3;
KS C 9610-3-3; ECE Regulation 10.06 Annex 12

Immunity

Electrostatic Discharge

IEC 61000-4-2, Ed. 1.2 (2001);
IEC 61000-4-2 (1995) + A1(1998) + A2(2000);
EN 61000-4-2 (1995); EN 61000-4-2 (2009-05);
KN 61000-4-2 (2008-5);
RRL Notice No. 2008-4 (May 20, 2008);
IEC 61000-4-2; EN 61000-4-2; KN 61000-4-2;
KS C 9610-4-2; IEEE C37.90.3 2001

Radiated Immunity

IEC 61000-4-3 (1995) + A1(1998) + A2(2000);
IEC 61000-4-3, Ed. 3.0 (2006-02);
IEC 61000-4-3, Ed. 3.2 (2010);
KN 61000-4-3 (2008-5);
RRL Notice No. 2008-4 (May 20, 2008);
IEC 61000-4-3; EN 61000-4-3; KN 61000-4-3;
KS C 9610-4-3; IEEE C37.90.2 2004

Test Technology:

Test Method(s)¹:

Immunity (cont'd)

Electrical Fast Transient/Burst

IEC 61000-4-4, Ed. 2.0 (2004-07);
IEC 61000-4-4, Ed. 2.1 (2011);
IEC 61000-4-4 (1995) + A1(2000) + A2(2001);
KN 61000-4-4 (2008-5);
RRL Notice No. 2008-5 (May 20, 2008);
IEC 61000-4-4; EN 61000-4-4; KN 61000-4-4;
KS C 9610-4-4; ECE Regulation 10.06 Annex 15

Surge

IEC 61000-4-5 (1995) + A1(2000);
IEC 61000-4-5, Ed 1.1 (2005-11);
EN 61000-4-5 (1995) + A1(2001);
KN 61000-4-5 (2008-5);
RRL Notice No. 2008-4 (May 20, 2008);
IEC 61000-4-5; EN 61000-4-5; KN 61000-4-5;
KS C 9610-4-5;
IEEE C37.90.1 2012; IEEE STD C62.41.2 2002;
ECE Regulation 10.06 Annex 16

Conducted Immunity

IEC 61000-4-6 (1996) + A1(2000);
IEC 61000-4-6, Ed 2.0 (2006-05);
IEC 61000-4-6 Ed. 3.0 (2008);
KN 61000-4-6 (2008-5);
RRL Notice No. 2008-4 (May 20, 2008);
EN 61000-4-6 (1996) + A1(2001); IEC 61000-4-6;
EN 61000-4-6; KN 61000-4-6; KS C 9610-4-6

Power Frequency Magnetic Field
Immunity (*Down to 3 A/m*)

IEC 61000-4-8 (1993) + A1(2000); IEC 61000-4-8 (2009);
EN 61000-4-8 (1994) + A1(2000);
KN 61000-4-8 (2008-5);
RRL Notice No. 2008-4 (May 20, 2008);
IEC 61000-4-8; EN 61000-4-8; KN 61000-4-8; KS C 9610-4-8

Voltage Dips, Short Interrupts, and Line
Voltage Variations

IEC 61000-4-11, Ed. 2 (2004-03);
KN 61000-4-11 (2008-5);
RRL Notice No. 2008-4 (May 20, 2008);
IEC 61000-4-11; EN 61000-4-11; KN 61000-4-11;
KS C 9610-4-11

Ring Wave

IEC 61000-4-12, Ed. 2 (2006-09);
EN 61000-4-12:2006;
IEC 61000-4-12; EN 61000-4-12; KN 61000-4-12;
IEEE STD C62.41.2 2002

Test Technology:

Test Method(s):

Generic and Product Specific EMC Standards

IEC/EN 61000-6-1; AS/NZS 61000-6-1; KN 61000-6-1; KS C 9610-6-1; IEC/EN 61000-6-2; AS/NZS 61000-6-2; KN 61000-6-2; KS C 9610-6-2; IEC/EN 61000-6-3; AS/NZS 61000-6-3; KN 61000-6-3; KS C 9610-6-3; IEC/EN 61000-6-4; AS/NZS 61000-6-4; KN 61000-6-4; KS C 9610-6-4; EN 50130-4; EN 61326-1; EN 50121-3-2; EN 12895; EN 50270; EN 50491-1; EN 50491-2; EN 50491-3; EN 55015; EN 60730-1; EN 60945; IEC 60533; EN 61326-2-6; EN 61800-3; IEC/CISPR 14-2; EN 55014-2; AS/NZS CISPR 14.2; KN 14-2; KS C 9814-2; IEC/CISPR 24; AS/NZS CISPR 24; EN 55024; KN 24; IEC/CISPR 35; AS/NZS CISPR 35; EN 55035; KN 35; KS C 9835; IEC 60601-1-2; JIS T0601-1-2

TxRx EMC Requirements

EN 301 489-1; EN 301 489-3; EN 301 489-9; EN 301 489-17; EN 301 489-19; EN 301 489-20

European Radio Test Standards

ETSI EN 300 086-1; ETSI EN 300 086-2; ETSI EN 300 113-1; ETSI EN 300 113-2; ETSI EN 300 220-1; ETSI EN 300 220-2; ETSI EN 300 220-3-1; ETSI EN 300 220-3-2; ETSI EN 300 330-1; ETSI EN 300 330-2; ETSI EN 300 440-1; ETSI EN 300 440-2; ETSI EN 300 422-1; ETSI EN 300 422-2; ETSI EN 300 328; ETSI EN 301 893; ETSI EN 301 511; ETSI EN 301 908-1; ETSI EN 908-2; ETSI EN 908-13; ETSI EN 303 413; ETSI EN 302 502; EN 303 340; EN 303 345-2; EN 303 345-3; EN 303 345-4

Canadian Radio Tests

RSS-102 measurement (RF Exposure Evaluation); RSS-102 measurement (Nerve Stimulation); SPR-002; RSS-111; RSS-112; RSS-117; RSS-119; RSS-123; RSS-125; RSS-127; RSS-130; RSS-131; RSS-132; RSS-133; RSS-134; RSS-135; RSS-137; RSS-139; RSS-140; RSS-141; RSS-142; RSS-170; RSS-181; RSS-182; RSS-191; RSS-192; RSS-194; RSS-195; RSS-196; RSS-197; RSS-199; RSS-210; RSS-211; RSS-213; RSS-215; RSS-216; RSS-220; RSS-222; RSS-236; RSS-238; RSS-243; RSS-244; RSS-247; RSS-248; RSS-251; RSS-252; RSS-287; RSS-288; RSS-310; RSS-GEN

Mexico Radio Tests

IFT-008-2015; NOM-208-SCFI-2016

Japan Radio Tests

Radio Law No. 131, Ordinance of MPT No. 37, 1981, MIC Notification No. 88:2004, Table No. 22-11; ARIB STD-T66, Regulation 18

Taiwan Radio Tests

LP-0002 (July 15, 2020)

<u>Test Technology:</u>	<u>Test Method(s)¹:</u>
<i>Australia/New Zealand Radio Tests</i>	AS/NZS 4268; Radiocommunications (Short Range Devices) Standard (2014)
<i>Hong Kong Radio Tests</i>	HKCA 1039 Issue 6; HKCA 1042; HKCA 1033 Issue 7; HKCA 1061; HKCA 1008; HKCA 1043; HKCA 1057; HKCA 1073
<i>Korean Radio Test Standards</i>	KN 301 489-1; KN 301 489-3; KN 301 489-9; KN 301 489-17; KN 301 489-52; KS X 3124; KS X 3125; KS X 3130; KS X 3126; KS X 3129
<i>Vietnam Radio Test Standards</i>	QCVN 47:2015/BTTTT; QCVN 54:2020/BTTTT; QCVN 55:2011/BTTTT; QCVN 65:2013/BTTTT; QCVN 73:2013/BTTTT; QCVN 74:2020/BTTTT; QCVN 112:2017/BTTTT; QCVN 117:2020/BTTTT
<i>Vietnam EMC Test Standards</i>	QCVN 18:2014/BTTTT; QCVN 86:2019/BTTTT; QCVN 96:2015/BTTTT; QCVN 118:2018/BTTTT
<i>Unlicensed Radio Frequency Devices (3 Meter Semi-Anechoic Room)</i>	47 CFR FCC Part 15C, 15D, 15E, 15F, 15G, 15H (using ANSI C63.10:2013, ANSI C63.17:2013 and FCC KDB 905462 D02 (v02))
<i>Licensed Radio Service Equipment</i>	47 CFR FCC Parts 20, 22, 24, 25, 27, 30, 73, 74, 80, 87, 90, 95, 96, 97, 101 (using ANSI/TIA-603-E, TIA-102.CAAA-E, ANSI C63.26:2015)
<i>OIA (Over the Air) Performance</i> GSM, GPRS, EGPRS UMTS (W-CDMA) LTE including CAT M1 A-GPS for UMTS/GSM LTS A-GPS, A-GLONASS, SIB8/SIB16 Large Device/Laptop/Tablet Testing Integrated Device Testing WiFi 802.11 a/b/g/n/a	CTIA Test Plan for Wireless Device Over-the-Air Performance (Method for Measurement for Radiated Power and Receiver Performance) V3.8.2; CTIA Test Plan for RF Performance Evaluation of WiFi Mobile Converged Devices V2.1.0

Test Technology:

Test Method(s)¹:

Electrical Measurements and Simulation

AC Voltage / Current

(1mV to 5kV) 60 Hz
(0.1V to 250V) up to 500 MHz
(1µA to 150A) 60 Hz

FAA AC 150/5345-10H;
FAA AC 150/5345-43J;
FAA AC 150/5345-44K;
FAA AC 150/5345-46E;
FAA AC 150/5345-47C;
FAA EB 67D

DC Voltage / Current

(1mV to 15 kV) / (1µA to 10A)

Power Factor / Efficiency / Crest Factor

(Power to 30kW)

Resistance

(1mΩ to 4000MΩ)

Surge

(Up to 10 kV / 5 kA) (Combination Wave and Ring Wave)

On the following products and materials:

Telecommunications Terminal Equipment (TTE), Radio Equipment, Network Equipment, Information Technology Equipment (ITE), Automotive Electronic Equipment, Automotive Hybrid Electronic Devices, Maritime Navigation and Radio Communication Equipment and Systems, Vehicles, Boats and Internal Combustion Engine Driven Devices, Automotive, Aviation, and General Lighting Products, Medical Electrical Equipment, Motors, Industrial, Scientific and Medical (ISM) Radio-Frequency Equipment, Household Appliances, Electric Tools, Low-voltage Switchgear and Control gear, Programmable Controllers, Electrical Equipment for Measurement, Control and Laboratory Use, Base Materials, Power and Data Transmission Cables and Connectors

¹ When the date, edition, version, etc. is not identified in the scope of accreditation, laboratories may use the version that immediately precedes the current version for a period of one year from the date of publication of the standard measurement method, per part C., Section 1 of A2LA R101 - *General Requirements - Accreditation of ISO-IEC 17025 Laboratories*.

Testing Activities Performed in Support of FCC Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1²

Rule Subpart/Technology	Test Method	Maximum Frequency (MHz)
<u>Unintentional Radiators</u> Part 15B	ANSI C63.4:2014	40000
<u>Industrial, Scientific, and Medical Equipment</u> Part 18	FCC MP-5 (February 1986)	40000
<u>Intentional Radiators</u> Part 15C	ANSI C63.10:2013	40000



Testing Activities Performed in Support of FCC Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1²

Rule Subpart/Technology	Test Method	Maximum Frequency (MHz)
<u>Unlicensed Personal Communication Systems Devices</u> Part 15D	ANSI C63.17:2013	40000
<u>U-NII without DFS Intentional Radiators</u> Part 15E	ANSI C63.10:2013	40000
<u>U-NII with DFS Intentional Radiators</u> Part 15E	FCC KDB 905462 D02 (v02)	40000
<u>UWB Intentional Radiators</u> Part 15F	ANSI C63.10:2013	40000
<u>BPL Intentional Radiators</u> Part 15G	ANSI C63.10:2013	40000
<u>White Space Device Intentional Radiators</u> Part 15H	ANSI C63.10:2013	40000
<u>Commercial Mobile Services (FCC Licensed Radio Service Equipment)</u> Parts 22 (cellular), 24, 25 (below 3 GHz), and 27	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>General Mobile Radio Services (FCC Licensed Radio Service Equipment)</u> Parts 22 (non-cellular), 90 (below 3 GHz), 95, 97, and 101 (below 3 GHz)	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Citizens Broadband Radio Services (FCC Licensed Radio Service Equipment)</u> Part 96	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Maritime and Aviation Radio Services</u> Parts 80 and 87	ANSI/TIA-603-E; ANSI C63.26:2015	40000
<u>Microwave and Millimeter Bands Radio Services</u> Parts 25, 30, 74, 90 (above 3 GHz), 97 (above 3 GHz), and 101	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000

(A2LA Cert. No. 1786.01) 08/15/2023



Page 8 of 9

Testing Activities Performed in Support of FCC Certification in Accordance with 47 Code of Federal Regulations and FCC KDB 974614, Appendix A, Table A.1²

Rule Subpart/Technology	Test Method	Maximum Frequency (MHz)
<u>Broadcast Radio Services</u> Parts 73 and 74 (below 3 GHz)	ANSI/TIA-603-E; TIA-102.CAAA-E; ANSI C63.26:2015	40000
<u>Signal Boosters</u> Part 20 (Wideband Consumer Signal Boosters, Provider-specific signal boosters, and Industrial Signal Boosters) Section 90.219	ANSI C63.26:2015	40000

² Accreditation does not imply acceptance to the FCC equipment authorization program. Please see the FCC website (<https://apps.fcc.gov/oetcf/eas/>) for a listing of FCC approved laboratories.





Accredited Laboratory

A2LA has accredited

ELITE ELECTRONIC ENGINEERING INC.

Downers Grove, IL

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 15th day of August 2023.



Mr. Trace McInturf, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 1786.01
Valid to June 30, 2025

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.