



Test Report

FCC ID:2AXGG-MA01

Date of issue: Oct. 29, 2020

Report number: MTi20082103-7E1

Sample description: TRUE WIRELESS POWER

Model(s): MA01

Applicant: Momax Technology (HK) Ltd.

Address: Unit A, 4/F, Cheung Lung Industrial Building, 10 Cheung Yee Street, Lai Chi Kok, Kowloon, Hong Kong

Date of test: Aug. 27, 2020 – Oct. 29, 2020

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel:(86-755)88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: mti@51mti.com

Address: 101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



Table of Contents

1	GENERAL INFORMATION	4
1.1	FEATURE OF EQUIPMENT UNDER TEST (EUT).....	4
1.2	TEST MODE	4
1.3	EUT TEST SETUP.....	5
1.4	ANCILLARY EQUIPMENT	5
2	SUMMARY OF TEST RESULT	6
2.1	OPERATION CHANNEL LIST	6
2.2	TEST CHANNEL	6
3	TEST FACILITIES AND ACCREDITATIONS	7
3.1	TEST LABORATORY	7
3.2	ENVIRONMENTAL CONDITIONS	7
3.3	MEASUREMENT UNCERTAINTY.....	7
3.4	TEST SOFTWARE	7
4	LIST OF TEST EQUIPMENT	8
5	TEST RESULTS.....	9
5.1	ANTENNA REQUIREMENT	9
5.1.1	<i>Standard requirement.</i>	9
5.1.2	<i>EUT Antenna</i>	9
5.2	CONDUCTED EMISSION	10
5.2.1	<i>Limits</i>	10
5.2.2	<i>Test Procedures</i>	10
5.2.3	<i>Test Setup</i>	10
5.2.4	<i>Test Result</i>	10
5.3	RADIATED EMISSION.....	15
5.3.1	<i>Limits</i>	15
5.3.2	<i>Test Procedures</i>	16
5.3.3	<i>Test Setup</i>	17
5.3.4	<i>Test Result</i>	17
5.4	OCCUPIED BANDWIDTH.....	21
5.4.1	<i>Test method.</i>	21
5.4.2	<i>Test result</i>	21
5.4.3	<i>Test method.</i>	23
5.4.4	<i>EUT SETUP</i>	23
5.4.5	<i>Test result</i>	23
	PHOTOGRAPHS OF THE TEST SETUP.....	25
	PHOTOGRAPHS OF THE EUT.....	27



Test Result Certification

Applicant's name: Momax Technology (HK) Ltd.

Address: Unit A, 4/F, Cheung Lung Industrial Building, 10 Cheung Yee Street, Lai Chi Kok, Kowloon, Hong Kong

Manufacturer's name: iMX Electronic (Shenzhen) Co., LTD

Address: F/4 East Side Mech. Factory, EVOC Tech. Industrial. Park, No.11 Gaoxin Rd., Gaoxin Area, Guangming New Area, Shenzhen City, Guangdong, PRC.

Product name: TRUE WIRELESS POWER

Trademark: MOMAX

Model name: MA01

Standards: FCC Part 15C

Test procedure: ANSI C63.10-2013

This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Danny Xu

Oct. 29, 2020

Reviewed by:

Leo Su

Oct. 29, 2020

Approved by:

Tom Xue

Oct. 29, 2020



1 GENERAL INFORMATION

1.1 Feature of equipment under test (EUT)

Product name:	TRUE WIRELESS POWER
Model name:	MA01
Model difference:	N/A
Operation frequency:	115–205 kHz, 326.5 kHz
Modulation type:	Load modulation
Antenna type:	Coil Antenna
Power supply:	DC 9V from adapter AC 120V/60Hz or DC 3.85V from battery
Battery:	DC 3.85V 10000mAh
Adapter information:	N/A
EUT serial number:	MTi20082103-7-S0001

1.2 Test mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test mode	Description
Mode 1	TX

Note:

1: The test modes were carried out for all operation modes. The final test mode of the EUT was the worst test mode for EMI, and its test data was showed.

2: EUT is tested under full load.



1.3 EUT test setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary equipment

Equipment	Model	S/N	Manufacturer
Watch	/	/	Apple
Load	/	/	/
Airpods	/	/	Apple



2 Summary of Test Result

Item	FCC Part No.	Description of Test	Result
1	FCC PART 15.203	Antenna requirement	Pass
2	FCC PART 15.207	Conducted emission	Pass
3	FCC PART 15.209	Radiated emission	Pass
4	FCC Part 15.215	20dB bandwidth	Pass

2.1 Operation channel list

Channel	Frequency (kHz)		
	Load	Airpods	Apple watch
Low	115	115	326.5
Middle	117	145	
High	205	205	

2.2 Test channel

	Channel	Frequency (kHz)
Load	Middle	117
Airpods	Middle	145
Apple watch	/	326.5



3 Test Facilities and Accreditations

3.1 Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd
Location	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao' an District, Shenzhen, Guangdong, China
FCC Registration No.:	448573

3.2 Environmental conditions

Temperature:	15°C~35°C
Humidity	20%~75%
Atmospheric pressure	98kPa~101kPa

3.3 Measurement uncertainty

Measurement Uncertainty for a Level of Confidence of 95 %, $U=2\times U_{\text{C}}(y)$

RF frequency	1×10^{-7}
RF power, conducted	$\pm 1 \text{ dB}$
Conducted emission(150kHz~30MHz)	$\pm 2.5 \text{ dB}$
Radiated emission(30MHz~1GHz)	$\pm 4.2 \text{ dB}$
Radiated emission (above 1GHz)	$\pm 4.3 \text{ dB}$
Temperature	$\pm 1 \text{ degree}$
Humidity	$\pm 5 \text{ \%}$

3.4 Test software

Software Name	Manufacturer	Model	Version
RF Test System	Shenzhen JS tonscent co., ltd	JS1120-3	2.5.77.0418



4 List of test equipment

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E004	EMI Test Receiver	Rohde&schwarz	ESPI7	100314	2020/10/09	2021/10/08
MTI-E006	TRILOG Broadband Antenna	schwarbeck	VULB 9163	9163-872	2020/10/15	2021/10/14
MTI-E014	amplifier	Hewlett-Packard	8447D	3113A061 50	2020/10/09	2021/10/08
MTI-E036	Single path vehicle AMN(LISN)	Schwarzbeck	NNBM 8124	01175	2020/10/09	2021/10/08
MTI-E038	Low noise active vertical monopole antenna	Schwarzbeck	VAMP 9243	#565	2020/10/16	2021/10/15
MTI-E039	Biconical antenna	Schwarzbeck	BBA 9106	#164	2020/10/15	2021/10/14
MTI-E041	MXG Vector Signal Generator	Agilent	N5182A	MY49060 455	2020/04/16	2021/04/15
MTI-E042	ESG Series Analog signal generator	Agilent	E4421B	GB40051 240	2020/05/21	2021/05/20
MTI-E044	Thermometer clock humidity monitor	-	HTC-1	/	2020/04/17	2021/04/16
MTI-E062	Log Periodic Antenna	Schwarzbeck	VUSLP 9111B	#312	2020/04/11	2022/04/10
MTI-E063	Log Periodic Dipole Array Antenna	ETS-LIND GREN	3148B	00224524	2020/04/11	2022/04/10
MTI-E065	Amplifier	EMtrace	RP06A	00117	2020/04/29	2021/04/28
MTI-E071	PXA Signal Analyzer	Agilent	N9030A	MY51350 296	2020/10/25	2021/10/24
MTI-E076	EMI Test Receiver	Rohde&schwarz	ESIB26	100273	2020/04/16	2021/04/15
MTI-E078	Synthesized Sweeper	Agilent	83752A	3610A019 57	2020/04/16	2021/04/15
MTI-E079	DC Power Supply	Agilent	E3632A	MY40027 695	2020/04/16	2021/04/15
MTI-E093	Artificial mains network	3ctest	LISN J50	ES391180 5	2020/04/16	2021/04/15
MTI-E096	Power amplifier	Space-Dtronics	EWLNA0118G -P40	1852001	2020/04/29	2021/04/28
MTI-E097	Current Probe	SOLAR ELECTRONICS CO.	9207-1	220095-1	2020/04/17	2021/04/16
MTI-E098	Loop Sensor	SOLAR ELECTRONICS CO.	7334-1	220095-2	2020/04/21	2021/04/20
Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).						



5 Test Results

5.1 Antenna requirement

5.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 EUT Antenna

The EUT antenna is Coil Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.



5.2 Conducted emission

5.2.1 Limits

For the following equipment, when designed to be connected to the public utility (AC) power line the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies shall not exceed the limits in the following tables. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.5 -5	56	46
5 -30	60	50

Note:

the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.2.2 Test Procedures

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.


Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN is at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related Item – photographs of the test setup.

5.2.3 Test Setup




5.2.4 Test Result



Apple Watch:


EUT:	TRUE WIRELESS POWER	Model Name:	MA01
Pressure:	101kPa	Phase:	L
Test voltage:	DC 9V from adapter AC 120V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV	dBuV	dB
1		0.1539	40.47	9.73	50.20	65.79	-15.59
2		0.1539	4.68	9.73	14.41	55.79	-41.38
3 *		0.2086	38.50	9.73	48.23	63.26	-15.03
4		0.2086	21.66	9.73	31.39	53.26	-21.87
5		0.4117	28.68	9.85	38.53	57.61	-19.08
6		0.4117	16.99	9.85	26.84	47.61	-20.77
7		1.3648	24.13	9.99	34.12	56.00	-21.88
8		1.3648	17.33	9.99	27.32	46.00	-18.68
9		7.0195	29.61	10.17	39.78	60.00	-20.22
10		7.0195	23.51	10.17	33.68	50.00	-16.32
11		19.6055	29.55	10.22	39.77	60.00	-20.23
12		19.6055	24.04	10.22	34.26	50.00	-15.74




EUT:	TRUE WIRELESS POWER	Model Name:	MA01
Pressure:	101kPa	Phase:	N
Test voltage:	DC 9V from adapter AC 120V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1500	41.62	9.73	51.35	66.00	-14.65	QP
2		0.1500	2.35	9.73	12.08	56.00	-43.92	AVG
3		0.2086	37.15	9.73	46.88	63.26	-16.38	QP
4		0.2086	18.83	9.73	28.56	53.26	-24.70	AVG
5		0.4352	30.01	9.87	39.88	57.15	-17.27	QP
6		0.4352	14.40	9.87	24.27	47.15	-22.88	AVG
7		2.8570	25.74	10.02	35.76	56.00	-20.24	QP
8		2.8570	20.29	10.02	30.31	46.00	-15.69	AVG
9		5.4453	26.11	10.09	36.20	60.00	-23.80	QP
10		5.4453	21.69	10.09	31.78	50.00	-18.22	AVG
11		17.2578	27.29	10.24	37.53	60.00	-22.47	QP
12	*	17.2578	25.16	10.24	35.40	50.00	-14.60	AVG




EUT:	TRUE WIRELESS POWER	Model Name:	MA01
Pressure:	101kPa	Phase:	L
Test voltage:	DC 9V from adapter AC 240V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.2047	36.31	9.73	46.04	63.42	-17.38	QP
2		0.2047	24.37	9.73	34.10	53.42	-19.32	AVG
3		0.3414	33.68	9.80	43.48	59.17	-15.69	QP
4		0.3414	23.58	9.80	33.38	49.17	-15.79	AVG
5		1.4977	27.52	9.99	37.51	56.00	-18.49	QP
6		1.4977	19.23	9.99	29.22	46.00	-16.78	AVG
7		4.3867	35.56	10.06	45.62	56.00	-10.38	QP
8	*	4.3867	28.01	10.06	38.07	46.00	-7.93	AVG
9		9.2852	29.68	10.30	39.98	60.00	-20.02	QP
10		9.2852	21.06	10.30	31.36	50.00	-18.64	AVG
11		19.8555	28.05	10.21	38.26	60.00	-21.74	QP
12		19.8555	26.59	10.21	36.80	50.00	-13.20	AVG



EUT:	TRUE WIRELESS POWER	Model Name:	MA01
Pressure:	101kPa	Phase:	N
Test voltage:	DC 9V from adapter AC 240V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV	dBuV	dB
							Detector
1	0.2047	37.13	9.73	46.86	63.42	-16.56	QP
2	0.2047	27.28	9.73	37.01	53.42	-16.41	AVG
3	0.3375	35.56	9.80	45.36	59.26	-13.90	QP
4	0.3375	21.42	9.80	31.22	49.26	-18.04	AVG
5	0.8805	30.35	9.97	40.32	56.00	-15.68	QP
6	0.8805	18.76	9.97	28.73	46.00	-17.27	AVG
7	2.2008	29.21	10.01	39.22	56.00	-16.78	QP
8	2.2008	22.16	10.01	32.17	46.00	-13.83	AVG
9	6.1913	28.26	10.13	38.39	60.00	-21.61	QP
10	6.1913	24.04	10.13	34.17	50.00	-15.83	AVG
11	21.3945	26.37	10.25	36.62	60.00	-23.38	QP
12 *	21.3945	27.28	10.25	37.53	50.00	-12.47	AVG



5.3 Radiated emission

5.3.1 Limits

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

The limit for radiated test was performed according to FCC PART 15C.

The tighter limit applies at the band edges.

Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP



Start ~ Stop Frequency

30MHz~1000MHz / RB 120kHz for QP

5.3.2 Test Procedures


- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
- h. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.




5.3.3 Test Setup

Radiated Emission Test-Up Frequency Below 30MHz



Radiated Emission Test-Up Frequency 30MHz~1GHz




5.3.4 Test Result



Frequency range (9kHz – 30MHz)

EUT:	TRUE WIRELESS POWER	Model Name:	MA01
Pressure:	101kPa	Test mode:	Mode 1
Test voltage:	DC 9V from adapter AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1307	43.61	20.11	63.72	105.28	-41.56	peak
2	0.1454	33.41	20.11	53.52	104.35	-50.83	peak
3	0.2627	18.89	20.18	39.07	99.21	-60.14	peak
4	0.3942	16.33	20.28	36.61	95.69	-59.08	peak
5	0.4381	17.41	20.30	37.71	94.77	-57.06	peak
6 *	1.6174	12.59	20.47	33.06	63.46	-30.40	peak



Frequency range (30MHz – 1GHz)


EUT:	TRUE WIRELESS POWER	Model Name:	MA01
Pressure:	101kPa	Polarization:	Horizontal
Test voltage:	DC 9V from adapter AC 120V/60Hz	Test mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	80.3617	42.54	-18.03	24.51	40.00	-15.49	QP
2 *	189.0740	47.42	-14.48	32.94	43.50	-10.56	QP
3	218.3084	43.54	-13.15	30.39	46.00	-15.61	QP
4	295.1467	36.36	-10.61	25.75	46.00	-20.25	QP
5	323.3201	38.87	-10.10	28.77	46.00	-17.23	QP
6	813.1114	26.63	-1.33	25.30	46.00	-20.70	QP



EUT:	TRUE WIRELESS POWER	Model Name:	MA01
Pressure:	101kPa	Polarization:	Vertical
Test voltage:	DC 9V from adapter AC 120V/60Hz	Test mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.7494	28.61	-13.93	14.68	40.00	-25.32	QP
2	82.6478	35.23	-17.61	17.62	40.00	-22.38	QP
3 *	190.4050	43.97	-14.35	29.62	43.50	-13.88	QP
4	216.7828	38.85	-13.20	25.65	46.00	-20.35	QP
5	478.8455	31.72	-7.39	24.33	46.00	-21.67	QP
6	863.0561	26.08	-0.42	25.66	46.00	-20.34	QP



5.4 Occupied bandwidth

5.4.1 Test method

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW \geq 1% of the 20 dB bandwidth

VBW \geq RBW

Sweep = auto

Detector function = peak


Trace = max hold


The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth and 99% occupied bandwidth of the emission.

5.4.2 Test result

/	Frequency (kHz)	20dB emission bandwidth (kHz)	99% occupied bandwidth (kHz)
Load	117	4.459	6.915
Airpods	145	4.513	7.517

Test plots as below:







5.4.3 Test method

The transmitter output is connected to the spectrum analyzer.
The RBW is set to 300Hz. The VBW is set to 3 times the RBW.
The sweep time is coupled.
The spectrum analyzer internal 99% bandwidth function is utilized.

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

Note that when the EUT was in standby mode the only signal that comes out from the EUT was the intentional charging signal of 326.5kHz. On the other hand, when the EUT was in operational mode there were two signals. One of the intentional charging signal of 326.5kHz and the other one the control signal of 340kHz that controls the communication/charging status between EUT and the client device-the watch.

5.4.4 EUT SETUP

Configuration 1: Charger in standby mode, transmitting low duty cycle CW signal at 326.5kHz test.


Configuration 2: Charger in pairing mode with FSK modulation (-0/+15 kHz) which occurs over a very short period of time as soon as the watch is placed on the charger.

Configuration 3: Charger in charging mode with CW signal and duty cycle varied to control charge level via load modulation from watch.

5.4.5 Test result


Test plots as below:

Configuration 1:






Configuration 2:



Configuration 3:






Photographs of the Test Setup

Radiated emission(Load: 9K-30MHz)




Radiated emission(Airpods: 30MHz-1GHz)





Conducted emission





Photographs of the EUT

See the APPENDIX 1: EUT PHOTOS in the report No.: MTi20082103-7E1-1.

----END OF REPORT----