




SPECIFICATIONS

Manufacturer:	Shenzhen Bolong Technology Co., Ltd.
Address:	Room 415, 4th Floor, Building A, Youth Pioneer Park , Jianshe East Road, Tsinghua Community, Longhua Street, Longhua District, Shenzhen City, China
Model No.	BL-YD01
Frequency (MHz)	2400-2480
Peak Gain (dBi)	2.499
Average Gain (dBi)	>-4
VSWR	<3.2
Impedance (Ω)	50Ω
Antenna Type	PCB
Polarization	Linear

Test environment: China Science and Technology darkroom test system



Physical object and physical size of the antenna




Antenna passive S parameter: (VSWR)、(Return Loss) And the Smith circle chart



Antenna efficiency and gain

Frequency (MHz)	Gain (dBi)	Efficiency (%)	AverageGain (dBi)	Efficiency (dB)
2400	1.433	59.329%	-2.717	-2.267
2410	0.927	51.861%	-3.416	-2.852
2420	0.829	52.112%	-3.166	-2.831
2430	0.881	49.299%	-3.258	-3.072
2440	1.192	50.672%	-3.612	-2.952
2450	1.688	53.067%	-2.735	-2.752
2460	2.194	59.423%	-2.276	-2.260
2470	2.118	56.680%	-2.438	-2.466
2480	2.499	61.727%	-2.112	-2.095
Average	1.529	54.908%	-2.858	-2.616
Peak	2.499	61.727%	-2.112	-2.095

2440MHz 2D-Theta Pattern



2440MHz 2D-Phi Pattern

