



# SPECIFICATIONS FOR APPROVAL

Customer Name: Shenzhen Creality 3D Technology Co.,LTD

Product Name: WIFI Antenna

Product Model: CL-103

Part Number: LJF02-21051910-R1A

Write By : Huxuwen

Issued Date: 2021-05-19

## CUSTOMER

ENGINEER R&D DEPT	BUSSINESS DEPT	APPROVAL

## LEJIN

R&D DEPT	ENGINEER DEPT	APPROVAL

REV	MODIFIED DESCRIPTION	DATE	REMARK
V1.0	Initial Draft Release	2021/05/19	
V1.1	Revise the spec of cable	2023/02/28	



## Index

1. Cover	1
2. Index	2
3. Product Specification	3
4. Test Equipment & Conditions	3
5. Test Report	4
6. Reliability Test	5
7. Assemble type	6
8. Product Drawing	8

### 3.Product Specification

A. Electrical Characteristics	
<b>Frequency</b>	<b>2400MHz ~2500 MHz</b>
<b>VSWR</b>	<b>&lt;2.0</b>
<b>Efficiency</b>	<b>&gt;60%</b>
<b>Impedance</b>	<b>50Ohm</b>
<b>Polarization</b>	<b>Linear</b>
<b>Gain</b>	<b>&gt;=1.8dB</b>
B. Material & Mechanical Characteristics	
<b>Material of Radiator</b>	<b>FPC(Green),70B</b>
<b>Cable Type</b>	<b>Φ1.37mm,L500mm,Black</b>
<b>Connector Type</b>	<b>IPX1</b>
<b>Dimension</b>	<b>48.3*8.25mm</b>
C. Environmental	
<b>Operation Temperature</b>	<b>- 30 °C ~ + 80 °C</b>
<b>Storage Temperature</b>	<b>- 30 °C ~ + 85 °C</b>
<b>Humidity</b>	<b>40%~95%</b>

### 4.Test Equipment & Conditions

- |                                  |                     |
|----------------------------------|---------------------|
| 1.Network Analyzers              | Agilent 8753D/5071C |
| 2.HSPA and LTE protocol test set | R&S CMW500 -PT      |
| 3.Communications Test Set        | Agilent 8960        |
| 4.3D Chamber Test System         |                     |




Chart 1 Test topology



## 5. Test Report

### 5.1 Voltage Standing Wave Ratio(VSWR).






Chart 2 VSWR

### 5.2 Efficient and gain.

Passive Test For WIFI 2.4G	Freq(MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
	Effi(%)		67.47	69.42	72.23	73.69	70.52	71.04	65.51	68.02	65.23	60.17
Gain(dBi)		1.88	2.03	2.20	2.24	2.12	2.19	2.04	2.02	1.87	1.92	1.69

### 5.3 Radiation pattern.










## 6. Reliability Test

Test Item	Test condition	Equipment	Specification	Result
1 Low Temp. Storage Test	Temperature: -30℃ , Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25℃ and humidity is 65% for one hour, then step-down the temp. to -30℃ in one hour, store antenna for44 hours; step-up temp to 25℃,test antenna after 2 hours.	Temp.&Hum. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
2 High Temp./High Humid Storage Test	Temperature: 85℃ Humidity: 85% RH Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25℃ and humidity is 65% for one hour, then step-up the temp. to 80℃ and the humidity up to 85% in one hour, store antenna for 44 hours; step-down temp to 25℃ ,test antenna after 2 hours.	Temp.&Hum. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
3 Salt-Spray 6 pray Test	Placing antenna in the Salt-Spray Tester ,set the test condition , Temp: 35±2℃ Humidity: 85% NaCl salt spray :5±1%.PH value :6.5~7.2 Testtime:24hours	Salt-Spray Tester	No color change No appear rusting	PASS

## 7. Assemble type(omitted)

## 8. Product Drawing



- Remark:**
- 1.FPC material: Electrolytic copper.
  - 2.Backing in behind:3M300LSE.
  - 3.Tolerance: Cutting die:±0.1mm; Circuit on FPC:±0.05mm; others are ±0.05mm.
  - 4.ROHS:(Pb,Hg,Cr+6,PBBs,PBDEs),<1000ppm; Cd,<100ppm.



SHEN ZHEN LEJIN RADIO FREQUENCY CO., LTD

1	2	3	4	5	6	7	8																																																																								
<table border="1"> <tr> <th>Rev</th> <th>Description</th> <th>Date</th> <th>Remark</th> </tr> <tr> <td>A</td> <td>New drawing</td> <td></td> <td></td> </tr> </table>				Rev	Description	Date	Remark	A	New drawing			<table border="1"> <tr> <th>Location</th> <th>Third Angle</th> <th>Project</th> <th>Creality 3D</th> <th>Date</th> <th>2018-08-09</th> </tr> <tr> <td>0~10</td> <td>±0.05</td> <td>0.02</td> <td></td> <td></td> <td></td> </tr> <tr> <td>10~18</td> <td>±0.10</td> <td>0.03</td> <td>Part Name</td> <td>2.4G ANT</td> <td></td> </tr> <tr> <td>18~30</td> <td>±0.12</td> <td>0.02</td> <td>Part No.</td> <td>CL103</td> <td></td> </tr> <tr> <td>30~40</td> <td>±0.15</td> <td>0.04</td> <td>Material</td> <td></td> <td></td> </tr> <tr> <td>40~</td> <td>±0.20</td> <td>±0.5°</td> <td>Treatment</td> <td>LJJF02-21051910-R1A</td> <td></td> </tr> </table>				Location	Third Angle	Project	Creality 3D	Date	2018-08-09	0~10	±0.05	0.02				10~18	±0.10	0.03	Part Name	2.4G ANT		18~30	±0.12	0.02	Part No.	CL103		30~40	±0.15	0.04	Material			40~	±0.20	±0.5°	Treatment	LJJF02-21051910-R1A		<table border="1"> <tr> <th>Unit</th> <th>mm</th> <th>Scale</th> <th>FTT</th> <th>Rev</th> <th>A</th> </tr> <tr> <td>Approved by</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Checked by</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Designed by</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>				Unit	mm	Scale	FTT	Rev	A	Approved by						Checked by						Designed by					
Rev	Description	Date	Remark																																																																												
A	New drawing																																																																														
Location	Third Angle	Project	Creality 3D	Date	2018-08-09																																																																										
0~10	±0.05	0.02																																																																													
10~18	±0.10	0.03	Part Name	2.4G ANT																																																																											
18~30	±0.12	0.02	Part No.	CL103																																																																											
30~40	±0.15	0.04	Material																																																																												
40~	±0.20	±0.5°	Treatment	LJJF02-21051910-R1A																																																																											
Unit	mm	Scale	FTT	Rev	A																																																																										
Approved by																																																																															
Checked by																																																																															
Designed by																																																																															