

# RF EXPOSURE EVALUATION REPORT

**Product Name:** 3D Printer  
**Trade Mark:** **CREALITY**  
**Model No. / HVIN:** Sermoon V1 Pro  
**Add. Model No. / HVIN:** Sermoon V1  
**Report Number:** 210816008RFC-3  
**Test Standards:** FCC 47 CFR Part 1 Subpart I  
RSS-102 Issue 5  
**FCC ID:** 2AXH6SERMOONV1  
**IC:** 27656-SERMOONV1  
**Test Result:** PASS  
**Date of Issue:** November 20, 2021

Prepared for:

**Shenzhen Crealty 3D Technology Co., Ltd.**  
**18F, JinXiuHongDu Building, Meilong Blvd., Longhua Dist.,**  
**Shenzhen,China 518131**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and**  
**technology park, Longhua district, Shenzhen, China**  
**TEL: +86-755-2823 0888**  
**FAX: +86-755-2823 0886**

Prepared by:



Gavin Xu  
Project Engineer

Reviewed by:



Henry Lu  
Team Leader

Approved by:



Kevin Liang  
Assistant Manager

Date:

November 20, 2021

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

**Version**

Version No.	Date	Description
V1.0	November 20, 2021	Original

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>UTTR-RF-RSS102-V1.1

## CONTENTS

<b>1. GENERAL INFORMATION</b>	<b>4</b>
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
1.4 OTHER INFORMATION	5
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	6
1.6 DEVIATION FROM STANDARDS	6
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
<b>2. EQUIPMENT LIST</b>	<b>6</b>
<b>3. MPE EVALUATION</b>	<b>7</b>
3.1 REFERENCE DOCUMENTS FOR EVALUATION	7
3.2 MPE COMPLIANCE REQUIREMENT	7
3.2.1 LIMITS	7
3.2.2 TEST PROCEDURE	8
3.3 MPE CALCULATION METHOD	8
3.4 MPE CALCULATION RESULTS	8
3.4.1 FOR WLAN	8
3.4.2 FOR BT	11
3.4.3 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	11
<b>APPENDIX 1 PHOTOS OF TEST SETUP</b>	<b>12</b>
<b>APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS</b>	<b>12</b>

## 1. GENERAL INFORMATION

### 1.1 CLIENT INFORMATION

<b>Applicant:</b>	Shenzhen Creality 3D Technology Co., Ltd.
<b>Address of Applicant:</b>	18F, JinXiuHongDu Building, Meilong Blvd., Longhua Dist., Shenzhen,China 518131
<b>Manufacturer:</b>	Shenzhen Creality 3D Technology Co., Ltd.
<b>Address of Manufacturer:</b>	18F, JinXiuHongDu Building, Meilong Blvd., Longhua Dist., Shenzhen,China 518131

### 1.2 EUT INFORMATION

<b>Product Name:</b>	3D Printer	
<b>Model No. / HVIN:</b>	Sermoon V1 Pro	
<b>Add. Model No. / HVIN:</b>	Sermoon V1	
<b>Trade Mark:</b>	<b>CREALITY</b>	
<b>DUT Stage:</b>	Identical Prototype	
<b>EUT Supports Function:</b>	2.4 GHz ISM Band:	IEEE 802.11b/g/n
		Bluetooth V4.1
<b>Sample Received Date:</b>	August 17, 2021	
<b>Note:</b> The test data is gathered from a production sample, provided by the manufacturer. The difference between the other models listed in the report and the main-test model Sermoon V1 Pro is that there is no camera function, but the other circuit and the electronic construction do not change, declared by the manufacturer.		

### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For BT_LE	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth LE
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type:	Internal Antenna
Antenna Gain:	2.39 dBi
Maximum Peak Power:	-1.88 dBm

For 2.4 GHz ISM Band of Wi-Fi	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20, IEEE 802.11n-HT40
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT40: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7 IEEE 802.11n-HT40: Up to MCS7
Number of Channels:	IEEE 802.11b: 11 IEEE 802.11g: 11 IEEE 802.11n-HT20: 11 IEEE 802.11n-HT40: 7
Channel Separation:	5 MHz
Antenna Type:	Internal Antenna
Antenna Gain:	2.39 dBi
Maximum Peak Power:	IEEE 802.11b: 13.96 dBm IEEE 802.11g: 20.54 dBm IEEE 802.11n-HT20: 18.62 dBm IEEE 802.11n-HT40: 16.56 dBm

### 1.4 OTHER INFORMATION

Test channels for BT_LE				
Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

Test channels for 2.4 GHz ISM Band of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
IEEE 802.11b	2412 MHz to 2462 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11

#### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT20	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT40	2422 MHz to 2452 MHz	Channel 3	Channel 6	Channel 9
		2422 MHz	2437 MHz	2452 MHz

## 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

**FCC 47 CFR Part 1 Subpart I**  
**RSS-102 Issue 5**

All test items have been performed and recorded as per the above standards

## 1.6 DEVIATION FROM STANDARDS

None.

## 1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

## 1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 2. EQUIPMENT LIST

Please refer to the RF test report.

### 3. MPE EVALUATION

#### 3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	RSS-102 Issue 5	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
3	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

#### 3.2 MPE COMPLIANCE REQUIREMENT

##### 3.2.1 Limits

##### 3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

##### Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

##### Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

**Note:** f = frequency in MHz: \* = Plane-wave equivalent power density.

### 3.2.1.2 RSS-102 Issue 5

According to RSS-102 Issue 5, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

According to RSS-102 Issue 5, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz<sup>6</sup> and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

### 3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 3.3 MPE CALCULATION METHOD

### FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

## 3.4 MPE CALCULATION RESULTS

**Note:** For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

### 3.4.1 For WLAN

For Wi-Fi function, operating at 2412MHz to 2462 MHz for IEEE802.11b/g/n

#### 3.4.1.1 Antenna Type:

**Chain 0:** Internal Antenna

#### 3.4.1.2 Antenna Gain:

**Chain 0:** 2412MHz to 2462 MHz: 2.39 dBi



**3.4.1.3 Results for FCC 47 CFR Part 1 Subpart I**

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)		(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	
IEEE 802.11b	2412	13	1	2.39	16.39	43.5512	1	0.0087
	2437	13	1	2.39	16.39	43.5512	1	0.0087
	2462	13	1	2.39	16.39	43.5512	1	0.0087
IEEE 802.11g	2412	20	1	2.39	23.39	218.2730	1	0.0434
	2437	20	1	2.39	23.39	218.2730	1	0.0434
	2462	20	1	2.39	23.39	218.2730	1	0.0434
IEEE 802.11n-HT20	2412	18	1	2.39	21.39	137.7209	1	0.0274
	2437	18	1	2.39	21.39	137.7209	1	0.0274
	2462	18	1	2.39	21.39	137.7209	1	0.0274
IEEE 802.11n-HT40	2422	16	1	2.39	19.39	86.8960	1	0.0173
	2437	16	1	2.39	19.39	86.8960	1	0.0173
	2452	16	1	2.39	19.39	86.8960	1	0.0173

**3.4.1.4 Results for RSS-102 Issue 5**

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	Limit
	(MHz)	(dBm)		(dBi)	(dBm)	(W)	(W)
IEEE 802.11g	2412	13	1	2.39	16.39	0.0436	2.6840
	2437	13	1	2.39	16.39	0.0436	2.7030
	2462	13	1	2.39	16.39	0.0436	2.7219
IEEE 802.11b	2412	20	1	2.39	23.39	0.2183	2.6840
	2437	20	1	2.39	23.39	0.2183	2.7030
	2462	20	1	2.39	23.39	0.2183	2.7219
IEEE 802.11n-HT20	2412	18	1	2.39	21.39	0.1377	2.6840
	2437	18	1	2.39	21.39	0.1377	2.7030
	2462	18	1	2.39	21.39	0.1377	2.7219
IEEE 802.11n-HT40	2422	16	1	2.39	19.39	0.0869	2.6916
	2437	16	1	2.39	19.39	0.0869	2.7030
	2452	16	1	2.39	19.39	0.0869	2.7144

### 3.4.2 For BT

For BT\_LE function, operating at 2402MHz to 2480 MHz for GFSK and

#### 3.4.2.1 Antenna Type:

Chain 0: Internal Antenna

#### 3.4.2.2 Antenna Gain:

Chain 0: 2402MHz to 2480 MHz: 2.0 dBi

#### 3.4.2.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)	(dBm)	(dBm)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	
LE	2402-2480	-1	2	2.39	3.39	2.1827	1	0.0004

#### 3.4.2.4 Results for RSS-102 Issue 5

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	Limit
	(MHz)	(dBm)	(dBm)	(dBm)	(dBm)	(W)	(W)
LE	2402-2480	-1	2	2.39	3.39	0.0022	2.6764

### 3.4.3 Simultaneous Multi-band Transmission MPE Analysis

#### 3.4.4.1 List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Support/Not Support
1	2.4G_WLAN + BT	Not Support

## APPENDIX 1 PHOTOS OF TEST SETUP

N/A

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

\*\*\* End of Report \*\*\*

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---