

# TEST REPORT

**Product Name** : True wireless earbuds  
**Brand Mark** : N/A  
**Model No.** : T9  
**Extension model** : A32, A32 Plus, A32 Pro, A32 +  
**Report Number** : BLA-EMC-202307-A0902  
**FCC ID** : 2AXI9T9  
**Date of Sample Receipt** : 2023/7/4  
**Date of Test** : 2023/7/5 to 2023/7/12  
**Date of Issue** : 2023/7/12  
**Test Standard** : 47 CFR Part 15, Subpart C 15.247  
**Test Result** : Pass

Prepared for:

**Shenzhen RB-LINK Intelligent Technology Co., Ltd**  
**Room 401, Building C, Runhe Industrial Park, Zhentou Road, Nandong,**  
**Huangpu Community, Xinqiao Street, Baoan District, Shenzhen**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**  
**Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,**  
**Shenzhen, Guangdong Province, China**  
**TEL: +86-755-23059481**

Compiled by:

*Jozu*

Review by:

*Sueels*

Approved by:

*Blue Zheng*

Date:

2023/7/12



**REPORT REVISE RECORD**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
00	2023/7/12	Original

BlueAsia

**TABLE OF CONTENTS**

<b>1</b>	<b>TEST SUMMARY .....</b>	<b>5</b>
<b>2</b>	<b>GENERAL INFORMATION .....</b>	<b>6</b>
<b>3</b>	<b>GENERAL DESCRIPTION OF E.U.T. ....</b>	<b>6</b>
<b>4</b>	<b>TEST ENVIRONMENT .....</b>	<b>8</b>
<b>5</b>	<b>TEST MODE .....</b>	<b>8</b>
<b>6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>7</b>	<b>DESCRIPTION OF SUPPORT UNIT .....</b>	<b>9</b>
<b>8</b>	<b>LABORATORY LOCATION .....</b>	<b>9</b>
<b>9</b>	<b>TEST INSTRUMENTS LIST .....</b>	<b>10</b>
<b>10</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>12</b>
10.1	CONCLUSION .....	12
<b>11</b>	<b>CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>13</b>
11.1	LIMITS .....	13
11.2	BLOCK DIAGRAM OF TEST SETUP .....	13
11.3	TEST DATA .....	14
<b>12</b>	<b>20DB BANDWIDTH .....</b>	<b>15</b>
12.1	BLOCK DIAGRAM OF TEST SETUP .....	15
12.2	TEST DATA .....	15
<b>13</b>	<b>CONDUCTED PEAK OUTPUT POWER .....</b>	<b>16</b>
13.1	LIMITS .....	16
13.2	BLOCK DIAGRAM OF TEST SETUP .....	16
13.3	TEST DATA .....	17
<b>14</b>	<b>CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) .....</b>	<b>18</b>
14.1	LIMITS .....	18
14.2	BLOCK DIAGRAM OF TEST SETUP .....	18
14.3	PROCEDURE .....	18
14.4	TEST DATA .....	20
<b>15</b>	<b>RADIATED SPURIOUS EMISSIONS .....</b>	<b>23</b>
15.1	LIMITS .....	23

15.2	BLOCK DIAGRAM OF TEST SETUP .....	24
15.3	PROCEDURE .....	24
15.4	TEST DATA .....	26
<b>16</b>	<b>RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....</b>	<b>41</b>
16.1	LIMITS .....	41
16.2	BLOCK DIAGRAM OF TEST SETUP .....	42
16.3	PROCEDURE .....	42
16.4	TEST DATA .....	44
<b>17</b>	<b>CONDUCTED BAND EDGES MEASUREMENT .....</b>	<b>53</b>
17.1	LIMITS .....	53
17.2	BLOCK DIAGRAM OF TEST SETUP .....	53
17.3	TEST DATA .....	54
<b>18</b>	<b>DWELL TIME .....</b>	<b>55</b>
18.1	LIMITS .....	55
18.2	BLOCK DIAGRAM OF TEST SETUP .....	55
18.3	TEST DATA .....	56
<b>19</b>	<b>HOPPING CHANNEL NUMBER .....</b>	<b>57</b>
19.1	LIMITS .....	57
19.2	BLOCK DIAGRAM OF TEST SETUP .....	57
19.3	TEST DATA .....	57
<b>20</b>	<b>CARRIER FREQUENCIES SEPARATION .....</b>	<b>58</b>
20.1	LIMITS .....	58
20.2	BLOCK DIAGRAM OF TEST SETUP .....	58
20.3	TEST DATA .....	58
<b>21</b>	<b>APPENDIX .....</b>	<b>59</b>
21.1	LEFT: .....	59
21.2	RIGHT: .....	97
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>		<b>135</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>		<b>138</b>

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass

## 2 GENERAL INFORMATION

<b>Applicant</b>	Shenzhen RB-LINK Intelligent Technology Co., Ltd
<b>Address</b>	Room 401, Building C, Runhe Industrial Park, Zhentou Road, Nandong, Huangpu Community, Xinqiao Street, Baoan District, Shenzhen
<b>Manufacturer</b>	Shenzhen RB-LINK Intelligent Technology Co., Ltd
<b>Address</b>	Room 401, Building C, Runhe Industrial Park, Zhentou Road, Nandong, Huangpu Community, Xinqiao Street, Baoan District, Shenzhen
<b>Factory</b>	Shenzhen RB-LINK Intelligent Technology Co., Ltd
<b>Address</b>	Room 401, Building C, Runhe Industrial Park, Zhentou Road, Nandong, Huangpu Community, Xinqiao Street, Baoan District, Shenzhen
<b>Product Name</b>	True wireless earbuds
<b>Test Model No.</b>	T9
<b>Extension model</b>	A32, A32 Plus, A32 Pro, A32 +
<b>Note</b>	All products are the same except for different model names.

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	A32-L-AD6976_V2.2 A32-R-AD6976_V2.2
<b>Software Version</b>	A32_AD6976D4
<b>Operation Frequency:</b>	2402MHz-2480MHz
<b>Modulation Type:</b>	GFSK, pi/4DQPSK
<b>Test sample no.:</b>	BLA-EMC-202307-A09(Left) BLA-EMC-202307-A09(Right)
<b>Channel Spacing:</b>	1MHz
<b>Number of Channels:</b>	79
<b>Antenna Type:</b>	Chip Antenna
<b>Antenna Gain:</b>	2.78dBi (Provided by the applicant)

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

#### 4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	3.7Vdc

#### 5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE )
Remark: Full battery is used during all test except ac conducted emission, DH1, DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK modulation were all pre-scanned only GFSK worse case is reported.	

#### 6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB



## 7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A

## 8 LABORATORY LOCATION

All tests were performed at:  
BlueAsia of Technical Services(Shenzhen) Co.,Ltd.  
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province,  
China  
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

## 9 TEST INSTRUMENTS LIST

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber 1	SKET	966	N/A	2020/11/10	2023/11/9
Chamber 2	SKET	966	N/A	2021/07/20	2024/07/19
Spectrum	R&S	FSP40	100817	2022/09/15	2023/09/14
Receiver	R&S	ESR7	101199	2022/09/15	2023/09/14
Receiver	R&S	ESPI7	101477	2022/07/16	2023/07/15
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2022/09/15	2023/09/14
Horn Antenna	Schwarzbeck	BBHA9120D	01892 P:00331	2022/09/13	2025/09/12
Amplifier	SKET	LNPA_30M01G-30	SK2021060801	2022/07/16	2023/07/15
Amplifier	SKET	PA-000318G-45	N/A	2022/09/13	2023/09/12
Amplifier	SKET	LNPA_18G40G-50	SK2022071301	2022/07/14	2023/07/13
Filter group	SKET	2.4G/5G Filter group r	N/A	2022/07/16	2023/07/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2022/9/14	2025/9/13
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

<b>Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>S/N</b>	<b>Cal.Date</b>	<b>Cal.Due</b>
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2022/09/14	2023/09/13
LISN	R&S	ENV216	3560.6550.15	2022/09/14	2023/09/13
LISN	AT	AT166-2	AKK1806000003	2022/09/14	2023/09/13
ISN	TESEQ	ISNT8-cat6	53580	2022/09/14	2023/09/13
Single-channel vehicle artificial power network	Schwarzbeck	NNBM 8124	01045	2022/08/17	2023/08/16
Single-channel vehicle artificial power network	Schwarzbeck	NNBM 8124	01075	2022/08/17	2023/08/16
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

<b>Test Equipment Of RF Conducted Test</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>S/N</b>	<b>Cal.Date</b>	<b>Cal.Due</b>
Spectrum	R&S	FSP40	100817	2022/09/15	2023/09/14
Spectrum	Agilent	N9020A	MY49100060	2022/09/07	2023/09/06
Spectrum	KEYSIGHT	N9030A	MY52350152	2022/07/01	2023/06/30
				2023/6/31	2024/6/0
Spectrum	KEYSIGHT	N9010A	MY54330814	2022/07/01	2023/06/30
				2023/6/31	2024/6/0
Signal Generator	Agilent	N5182A	MY47420955	2022/09/07	2023/09/06
Signal Generator	Agilent	E8257D	MY44320250	2022/07/01	2023/06/30
				2023/6/31	2024/6/0
Signal Generator	Agilent	N5181A	MY46240904	2022/08/02	2023/08/01
Signal Generator	R&S	CMW500	132429	2022/09/07	2023/09/06
BluetoothTester	Anritsu	MT8852B	06262047872	2022/09/07	2023/09/06
Power probe	DARE	RPR3006W	14I00889SN042	2022/09/07	2023/09/06
DCPowersupply	zhaoxin	KXN-305D	20K305D1221363	2022/09/14	2023/09/13
DCPowersupply	zhaoxin	RXN-1505D	19R1505D050168	2022/09/14	2023/09/13
2.4GHz/5GHz RF Test software	MTS	MTS 8310	Version 2.0.0.0	N/A	N/A
Audio Analyzer	Audioprecision	N/A	ATSI-41094	2022/7/1	2023/6/30
				2023/6/31	2024/6/0

## 10 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

### 10.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.78dBi.


## 11 CONDUCTED SPURIOUS EMISSIONS

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 11.1 LIMITS

<b>Limit:</b>	<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).</p>
---------------	---

### 11.2 BLOCK DIAGRAM OF TEST SETUP



### 11.3 TEST DATA


**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia

## 12 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### 12.1 BLOCK DIAGRAM OF TEST SETUP



### 12.2 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


### 13 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

#### 13.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

#### 13.2 BLOCK DIAGRAM OF TEST SETUP





### 13.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia

## 14 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	BT mode
Test Mode (Final Test)	BT mode
Tester	Jozu
Temperature	25°C
Humidity	60%

### 14.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 14.2 BLOCK DIAGRAM OF TEST SETUP



Remark:  
 E.U.T: Equipment Under Test  
 LISN: Line Impedance Stabilization Network  
 Test table height=0.8m

### 14.3 PROCEDURE


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
  - 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
  - 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
- Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

### 14.4 TEST DATA

[TestMode: BT mode]; [Line: Line]; [Power: AC120V/60Hz]



Site	Phase: <b>L1</b>	Temperature: (C)
Limit: FCC Class B Conduction(QP)	Power:	Humidity: %RH
EUT: True wireless earbuds	Distance: RBW: 9 KHz	
M/N: T9	VBW: 30 KHz	Sweep Time: 10 ms
Mode: TX mode		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	cm	degree	Comment
1		0.2540	20.09	10.60	30.69	61.63	-30.94	QP		
2		0.2540	14.52	10.60	25.12	51.63	-26.51	AVG		
3		0.5740	28.52	10.08	38.60	56.00	-17.40	QP		
4	*	0.5740	21.19	10.08	31.27	46.00	-14.73	AVG		
5		1.3220	18.43	10.17	28.60	56.00	-27.40	QP		
6		1.3220	13.02	10.17	23.19	46.00	-22.81	AVG		
7		2.5700	17.28	10.26	27.54	56.00	-28.46	QP		
8		2.5700	11.32	10.26	21.58	46.00	-24.42	AVG		
9		4.7220	15.28	10.04	25.32	56.00	-30.68	QP		
10		4.7220	8.08	10.04	18.12	46.00	-27.88	AVG		
11		12.9140	3.76	10.01	13.77	60.00	-46.23	QP		
12		12.9140	-2.04	10.01	7.97	50.00	-42.03	AVG		


\*:Maximum data    x:Over limit    !:over margin      <Reference Only

Receiver: ESPI\_1      Spectrum Analyzer: ESPI

L.I.S.N:      Engineer Signature:

**Test Result: Pass**

[TestMode: BT mode]; [Line: Nutral] ;[Power:AC120V/60Hz]



Site	Phase: <b>N</b>	Temperature: (C)
Limit: FCC Class B Conduction(QP)	Power:	Humidity: %RH
EUT: True wireless earbuds	Distance: RBW: 9 KHz	Sweep Time: 10 ms
M/N: T9	VBW: 30 KHz	
Mode: TX mode		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	cm	degree	Comment
1		0.5820	21.95	10.04	31.99	56.00	-24.01	QP		
2	*	0.5820	15.37	10.04	25.41	46.00	-20.59	AVG		
3		1.2660	14.13	10.04	24.17	56.00	-31.83	QP		
4		1.2660	8.36	10.04	18.40	46.00	-27.60	AVG		
5		2.3100	13.25	10.08	23.33	56.00	-32.67	QP		
6		2.3100	6.21	10.08	16.29	46.00	-29.71	AVG		
7		3.5460	11.47	9.96	21.43	56.00	-34.57	QP		
8		3.5460	4.17	9.96	14.13	46.00	-31.87	AVG		
9		7.7900	9.27	9.88	19.15	60.00	-40.85	QP		
10		7.7900	0.96	9.88	10.84	50.00	-39.16	AVG		
11		15.8940	-2.09	10.02	7.93	60.00	-52.07	QP		
12		15.8940	-4.67	10.02	5.35	50.00	-44.65	AVG		

\*:Maximum data    x:Over limit    !:over margin

(Reference Only)

Receiver: ESPI\_1

Spectrum Analyzer: ESPI

L.I.S.N:

Engineer Signature:

**Test Result: Pass**

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

BlueAsia

## 15 RADIATED SPURIOUS EMISSIONS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 15.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 15.2 BLOCK DIAGRAM OF TEST SETUP



## 15.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.




- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

### 15.4 TEST DATA


[TestMode: TX below 1G]; [Polarity: Horizontal]



\*:Maximum data    x:Over limit    !:over margin

**Test Result: Pass**

[TestMode: TX below 1G]; [Polarity: Vertical]




\*:Maximum data    x:Over limit    !:over margin

**Test Result: Pass**

Left:

[TestMode: TX low channel]; [Polarity: Horizontal]



Site:      Polarization: **Horizontal**      Temperature: (C)  
 Limit: FCC Part15 (PK)      Power:      Humidity: %RH  
 EUT: True wireless earbuds  
 M/N: T9  
 Mode: TX-L--L  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	41.00	4.51	45.51	74.00	-28.49	peak	
2		5888.000	39.45	6.71	46.16	74.00	-27.84	peak	
3		7206.000	38.27	7.41	45.68	74.00	-28.32	peak	
4		8249.750	39.66	8.54	48.20	74.00	-25.80	peak	
5		9608.000	37.02	11.59	48.61	74.00	-25.39	peak	
6	*	10999.25	38.16	13.82	51.98	74.00	-22.02	peak	


\*:Maximum data    x:Over limit    !:over margin      <Reference Only

Receiver:      ESPI\_1      Spectrum Analyzer:      FSP40  
 Antenna:      EZ 9120D 1G-18G new      Engineer Signature:

**Test Result: Pass**



[TestMode: TX mid channel]; [Polarity: Horizontal]



Site:      Polarization: **Horizontal**      Temperature: (C)  
 Limit: FCC Part15 (PK)      Power:      Humidity: %RH  
 EUT: True wireless earbuds  
 M/N: T9  
 Mode: TX-M--L  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.000	38.69	4.60	43.29	74.00	-30.71	peak	
2		5876.250	39.68	6.66	46.34	74.00	-27.66	peak	
3		7323.000	37.55	7.82	45.37	74.00	-28.63	peak	
4		8426.000	39.44	9.01	48.45	74.00	-25.55	peak	
5		9764.000	36.98	11.76	48.74	74.00	-25.26	peak	
6	*	11798.25	39.14	13.00	52.14	74.00	-21.86	peak	

\*:Maximum data    x:Over limit    !:over margin      <Reference Only

Receiver:      ESPI\_1      Spectrum Analyzer:      FSP40  
 Antenna:      EZ 9120D 1G-18G new      Engineer Signature:

**Test Result: Pass**