





## 7.6. Radiated Spurious Emission Measurement

### 7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [Uv/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 7.6.2. Test Procedure Used

ANSI C63.10 - 2013 Section 6.3 (General Requirements)

ANSI C63.10 - 2013 Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 Section 6.6 (Standard test method above 1GHz)

### 7.6.3. Test Setting

**Table 1 - RBW as a function of frequency**

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

**Quasi-Peak Measurements below 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

**Peak Measurements above 1GHz**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

**Average Measurements above 1GHz (Method VB)**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle  $\geq 98\%$ , set VBW = 10 Hz.  
If the EUT duty cycle is  $< 98\%$ , set VBW  $\geq 1/T$ . T is the minimum transmission duration.
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize

### 7.6.4. Test Setup

#### Below 1GHz Test Setup:




#### Above 1GHz Test Setup:



### 7.6.5. Test Result

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	VULB 9162	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Stanley
Test Mode	802.11n-20MHz_TX_CH 6 ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	52.250	13.57	20.34	33.91	-6.09	40.00	150	271	QP
2	95.930	16.74	17.72	34.46	-9.04	43.50	100	110	QP
3	* 262.350	20.14	19.97	40.11	-5.89	46.00	200	254	QP
4	416.950	11.54	23.24	34.78	-11.22	46.00	100	10	QP
5	509.650	13.45	25.03	38.49	-7.51	46.00	100	301	QP
6	740.500	3.86	28.62	32.48	-13.52	46.00	200	86	QP

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	VULB 9162	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Stanley
Test Mode	802.11n-20MHz_TX_CH 6 ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	42.670	12.80	19.88	32.68	-7.32	40.00	150	159	QP
2		87.670	12.80	15.93	28.73	-11.27	40.00	100	244	QP
3		192.770	14.14	17.70	31.83	-11.67	43.50	200	273	QP
4		298.570	12.29	20.46	32.75	-13.25	46.00	100	340	QP
5		389.120	13.72	22.92	36.63	-9.37	46.00	150	36	QP
6		492.410	10.38	24.70	35.09	-10.91	46.00	100	184	QP

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	VULB 9162	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Stanley
Test Mode	802.11n-20MHz_TX_CH 6 ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	69.540	14.40	15.70	30.10	-9.90	40.00	150	58	QP
2		182.800	14.84	16.65	31.49	-12.01	43.50	100	257	QP
3		282.110	12.77	20.10	32.87	-13.13	46.00	200	41	QP
4		404.210	10.42	23.12	33.54	-12.46	46.00	100	157	QP
5		524.600	7.02	25.22	32.25	-13.75	46.00	150	344	QP
6		731.790	5.79	28.45	34.24	-11.76	46.00	100	233	QP

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	VULB 9162	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Stanley
Test Mode	802.11n-20MHz_TX_CH 6 ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	51.980	12.47	20.38	32.85	-7.15	40.00	100	299	QP
2	160.600	11.19	15.50	26.70	-16.80	43.50	150	348	QP
3	203.410	18.51	17.89	36.40	-7.10	43.50	200	53	QP
4	291.710	15.94	20.38	36.32	-9.68	46.00	150	120	QP
5	397.170	10.17	23.04	33.20	-12.80	46.00	200	176	QP
6	* 487.720	15.08	24.57	39.66	-6.34	46.00	150	324	QP

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4824.000	56.47	-1.10	55.37	-18.63	74.00	212	260	Peak
2	* 4824.000	54.96	-1.10	53.86	-0.14	54.00	212	260	Average
3	7236.000	48.36	3.90	52.26	-21.74	74.00	212	0	Peak
4	9648.000	44.80	3.21	48.01	-25.99	74.00	212	317	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4824.000	56.26	-1.10	55.16	-18.84	74.00	200	296	Peak
2	* 4824.000	54.22	-1.10	53.12	-0.88	54.00	200	296	Average
3	7236.000	49.60	3.90	53.50	-20.50	74.00	200	15	Peak
4	9648.000	41.68	3.21	44.90	-29.10	74.00	200	11	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4874.000	56.41	-0.97	55.44	-18.56	74.00	234	238	Peak
2	* 4874.000	54.79	-0.97	53.82	-0.18	54.00	238	263	Average
3	7311.000	47.44	3.92	51.35	-22.65	74.00	238	0	Peak
4	9748.000	43.14	3.24	46.39	-27.61	74.00	238	313	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	53.25	-0.97	52.29	-21.71	74.00	200	293	Peak
2	* 7311.000	49.37	3.92	53.28	-20.72	74.00	200	0	Peak
3	9748.000	41.97	3.24	45.22	-28.78	74.00	200	281	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4924.000	56.37	-0.84	55.53	-18.47	74.00	200	262	Peak
2	* 4924.000	54.69	-0.84	53.85	-0.15	54.00	200	262	Average
3	7386.000	46.52	3.93	50.45	-23.55	74.00	200	31	Peak
4	9848.000	42.22	3.27	45.49	-28.51	74.00	200	0	Peak

Note:

- " \*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Pre-amplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	52.56	-0.84	51.73	-22.27	74.00	200	286	Peak
2	* 7386.000	50.04	3.93	53.97	-20.03	74.00	200	350	Peak
3	9848.000	41.54	3.27	44.81	-29.19	74.00	200	310	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	51.82	-1.10	50.72	-23.28	74.00	200	261	Peak
2	* 7236.000	51.45	3.90	55.35	-18.65	74.00	200	249	Peak
3	9648.000	44.51	3.21	47.73	-26.27	74.00	200	324	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	50.35	-1.10	49.25	-24.75	74.00	100	283	Peak
2	* 7236.000	52.44	3.90	56.34	-17.66	74.00	100	21	Peak
3	9648.000	42.00	3.21	45.22	-28.78	74.00	100	138	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	57.99	-0.97	57.02	-16.98	74.00	200	155	Peak
2	4874.000	44.52	-0.97	43.55	-10.45	54.00	200	155	Average
3 *	7311.000	60.41	3.92	64.33	-9.67	74.00	200	32	Peak
4 *	7311.000	46.36	3.92	50.28	-3.72	54.00	200	32	Average
5	9748.000	46.95	3.24	50.19	-23.81	74.00	100	315	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	58.59	-0.97	57.62	-16.38	74.00	200	300	Peak
2	4874.000	45.55	-0.97	44.58	-9.42	54.00	200	300	Average
3	* 7311.000	61.95	3.92	65.87	-8.13	74.00	100	359	Peak
4	* 7311.000	47.87	3.92	51.79	-2.21	54.00	100	359	Average
5	9748.000	43.96	3.24	47.21	-26.79	74.00	100	16	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	51.35	-0.84	50.52	-23.48	74.00	200	257	Peak
2	* 7386.000	46.89	3.93	50.83	-23.17	74.00	200	42	Peak
3	9848.000	42.36	3.27	45.63	-28.37	74.00	200	360	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	50.17	-0.84	49.33	-24.67	74.00	100	0	Peak
2	* 7386.000	55.32	3.93	59.25	-14.75	74.00	100	360	Peak
3	* 7386.000	39.42	3.93	43.35	-10.65	54.00	100	360	Average
4	9848.000	41.96	3.27	45.23	-28.77	74.00	100	244	Peak

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	49.27	-1.10	48.17	-25.83	74.00	200	261	Peak
2	* 7236.000	48.29	3.90	52.19	-21.81	74.00	200	14	Peak
3	9648.000	42.11	3.21	45.33	-28.67	74.00	200	309	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	49.64	-1.10	48.54	-25.46	74.00	100	30	Peak
2	* 7236.000	51.29	3.90	55.19	-18.81	74.00	100	356	Peak
3	9648.000	41.86	3.21	45.07	-28.93	74.00	100	74	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	54.38	-0.97	53.41	-20.59	74.00	200	260	Peak
2	* 7311.000	58.34	3.92	62.26	-11.74	74.00	200	24	Peak
3	* 7311.000	44.36	3.92	48.28	-5.72	54.00	200	24	Average
4	9748.000	45.29	3.24	48.53	-25.47	74.00	200	323	Peak

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	53.25	-0.97	52.28	-21.72	74.00	100	26	Peak
2	* 7311.000	60.09	3.92	64.01	-9.99	74.00	100	0	Peak
3	* 7311.000	45.84	3.92	49.76	-4.24	54.00	100	0	Average
4	9748.000	42.82	3.24	46.06	-27.94	74.00	100	26	Peak

Note:

- " \*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	49.56	-0.84	48.73	-25.27	74.00	200	260	Peak
2	* 7386.000	45.65	3.93	49.59	-24.41	74.00	200	13	Peak
3	9848.000	41.63	3.27	44.89	-29.11	74.00	200	21	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	49.16	-0.84	48.33	-25.67	74.00	100	0	Peak
2	* 7386.000	47.99	3.93	51.92	-22.08	74.00	100	360	Peak
3	9848.000	41.81	3.27	45.08	-28.92	74.00	100	190	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4824.000	56.49	-1.10	55.39	-18.61	74.00	210	312	Peak
2	*	4824.000	54.91	-1.10	53.81	-0.19	54.00	210	312	Average
3		7236.000	48.08	3.90	51.98	-22.02	74.00	210	310	Peak
4		9648.000	42.32	3.21	45.53	-28.47	74.00	210	218	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preampifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	53.06	-1.10	51.97	-22.03	74.00	100	240	Peak
2	* 7236.000	49.31	3.90	53.21	-20.79	74.00	100	28	Peak
3	9648.000	41.37	3.21	44.58	-29.42	74.00	100	172	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4874.000	56.83	-0.97	55.86	-18.14	74.00	108	286	Peak
2	*	4874.000	54.78	-0.97	53.81	-0.19	54.00	108	286	Average
3		7311.000	48.95	3.92	52.87	-21.13	74.00	300	252	Peak
4		9748.000	42.35	3.24	45.60	-28.40	74.00	300	34	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preampifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	53.51	-0.97	52.55	-21.45	74.00	100	48	Peak
2	* 7311.000	51.05	3.92	54.97	-19.03	74.00	100	352	Peak
3	* 7311.000	45.99	3.92	49.91	-4.09	54.00	100	352	Average
4	9748.000	42.24	3.24	45.48	-28.52	74.00	100	246	Peak

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamp(lifier)(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	52.73	-0.84	51.89	-22.11	74.00	100	284	Peak
2	7386.000	46.35	3.93	50.28	-23.72	74.00	300	257	Peak
3	9848.000	42.96	3.27	46.23	-27.77	74.00	300	0	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4924.000	56.30	-0.84	55.46	-18.54	74.00	107	34	Peak
2	*	4924.000	54.73	-0.84	53.89	-0.11	54.00	107	34	Average
3		7386.000	48.64	3.93	52.57	-21.43	74.00	107	0	Peak
4		9848.000	41.82	3.27	45.09	-28.91	74.00	107	268	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamp(lifier)(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	53.55	-1.10	52.45	-21.55	74.00	100	289	Peak
2	* 7236.000	55.84	3.90	59.75	-14.25	74.00	100	305	Peak
3	9648.000	42.99	3.21	46.21	-27.79	74.00	100	0	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	52.32	-1.10	51.22	-22.78	74.00	100	51	Peak
2	* 7236.000	54.56	3.90	58.46	-15.54	74.00	100	15	Peak
3	9648.000	42.13	3.21	45.35	-28.65	74.00	100	357	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	61.20	-0.97	60.23	-13.77	74.00	100	288	Peak
2	4874.000	47.94	-0.97	46.97	-7.03	54.00	100	288	Average
3	* 7311.000	62.09	3.92	66.01	-7.99	74.00	100	304	Peak
4	* 7311.000	48.20	3.92	52.12	-1.88	54.00	100	304	Average
5	9748.000	44.14	3.24	47.39	-26.61	74.00	100	20	Peak

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Pre-amplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	58.95	-0.97	57.98	-16.02	74.00	100	46	Peak
2	4874.000	46.18	-0.97	45.21	-8.79	54.00	100	46	Average
3	* 7311.000	63.18	3.92	67.10	-6.90	74.00	100	9	Peak
4	* 7311.000	49.91	3.92	53.83	-0.17	54.00	100	9	Average
5	9748.000	42.41	3.24	45.65	-28.35	74.00	100	179	Peak

Note:

- " \*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	50.76	-0.84	49.92	-24.08	74.00	100	288	Peak
2	* 7386.000	56.25	3.93	60.18	-13.82	74.00	100	304	Peak
3	* 7386.000	41.21	3.93	45.14	-8.86	54.00	100	304	Average
4	9848.000	41.80	3.27	45.07	-28.93	74.00	100	58	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamp(lifier)(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	52.58	-0.84	51.74	-22.26	74.00	100	40	Peak
2	* 7386.000	58.76	3.93	62.69	-11.31	74.00	100	360	Peak
3	* 7386.000	43.89	3.93	47.82	-6.18	54.00	100	360	Average
4	9848.000	41.57	3.27	44.83	-29.17	74.00	100	76	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preampifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	50.39	-1.10	49.29	-24.71	74.00	100	289	Peak
2	* 7236.000	52.23	3.90	56.14	-17.86	74.00	300	292	Peak
3	9648.000	42.41	3.21	45.62	-28.38	74.00	300	299	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	51.74	-1.10	50.64	-23.36	74.00	100	298	Peak
2	* 7236.000	53.21	3.90	57.12	-16.88	74.00	100	360	Peak
3	9648.000	41.33	3.21	44.54	-29.46	74.00	100	290	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	61.21	-0.97	60.24	-13.76	74.00	100	291	Peak
2	4874.000	47.85	-0.97	46.88	-7.12	54.00	100	291	Average
3	* 7311.000	63.97	3.92	67.89	-6.11	74.00	100	302	Peak
4	* 7311.000	48.37	3.92	52.29	-1.71	54.00	100	302	Average
5	9748.000	46.30	3.24	49.54	-24.46	74.00	100	26	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	58.41	-0.97	57.44	-16.56	74.00	100	36	Peak
2	4874.000	46.09	-0.97	45.12	-8.88	54.00	100	36	Average
3	* 7311.000	63.78	3.92	67.70	-6.30	74.00	100	4	Peak
4	* 7311.000	49.92	3.92	53.84	-0.16	54.00	100	4	Average
5	9748.000	42.76	3.24	46.00	-28.00	74.00	100	20	Peak

Note:

- " \*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preampfier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	47.57	-0.84	46.73	-27.27	74.00	100	30	Peak
2	* 7386.000	54.00	3.93	57.93	-16.07	74.00	100	57	Peak
3	* 7386.000	37.65	3.93	41.58	-12.42	54.00	100	57	Average
4	9848.000	41.41	3.27	44.68	-29.32	74.00	100	179	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preampifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	50.41	-0.84	49.57	-24.43	74.00	100	29	Peak
2	* 7386.000	56.42	3.93	60.35	-13.65	74.00	100	360	Peak
3	* 7386.000	39.96	3.93	43.89	-10.11	54.00	100	360	Average
4	9848.000	41.38	3.27	44.64	-29.36	74.00	100	13	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB) – Preampifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 7.7. Radiated Restricted Band Edge Measurement

### 7.7.1. Test Limit

**For 15.205 requirement:**

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 7.7.2. Test Procedure Used

ANSI C63.10 - 2013 Section 6.3 (General Requirements)

ANSI C63.10 - 2013 Section 6.6 (Standard test method above 1GHz)

### 7.7.3. Test Setting

#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


### Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle  $\geq 98\%$ , set VBW = 10 Hz.

If the EUT duty cycle is  $< 98\%$ , set  $VBW \geq 1/T$ . T is the minimum transmission duration.

4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize


#### 7.7.4. Test Setup





### 7.7.5. Test Result

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2380.375	27.11	30.15	57.26	-16.74	74.00	230	257	Peak
2		2390.000	25.42	30.18	55.60	-18.40	74.00	230	257	Peak
3		2410.625	75.74	30.22	105.96	N/A	N/A	230	257	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2382.000	15.91	30.16	46.06	-7.94	54.00	230	257	Average
2		2390.000	14.86	30.18	45.04	-8.96	54.00	230	257	Average
3		2410.750	72.51	30.22	102.73	N/A	N/A	230	257	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2381.625	26.76	30.16	56.92	-17.08	74.00	105	21	Peak
2		2390.000	25.51	30.18	55.69	-18.31	74.00	105	21	Peak
3		2410.750	72.51	30.22	102.73	N/A	N/A	105	21	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2384.375	15.05	30.16	45.21	-8.79	54.00	105	21	Average
2		2390.000	14.35	30.18	44.53	-9.47	54.00	105	21	Average
3		2410.875	69.38	30.22	99.60	N/A	N/A	105	21	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.470	26.64	30.18	56.81	-17.19	74.00	230	256	Peak
2	2390.000	25.06	30.18	55.24	-18.76	74.00	230	256	Peak
3	2438.250	75.08	30.26	105.34	N/A	N/A	230	256	Peak
4	2483.500	25.45	30.32	55.77	-18.23	74.00	230	256	Peak
5	* 2493.920	26.79	30.33	57.12	-16.88	74.00	230	256	Peak

Note:

- " \*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2370.990	14.30	30.13	44.43	-9.57	54.00	230	256	Average
2	2390.000	13.78	30.18	43.96	-10.04	54.00	230	256	Average
3	2438.250	71.89	30.26	102.15	N/A	N/A	230	256	Average
4	2483.500	14.02	30.32	44.34	-9.66	54.00	230	256	Average
5	* 2491.450	15.00	30.33	45.33	-8.67	54.00	230	256	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2380.110	26.67	30.15	56.82	-17.18	74.00	100	77	Peak
2	2390.000	24.63	30.18	54.81	-19.19	74.00	100	77	Peak
3	2435.590	71.26	30.25	101.52	N/A	N/A	100	77	Peak
4	2483.500	24.96	30.32	55.28	-18.72	74.00	100	77	Peak
5	* 2493.540	26.64	30.33	56.97	-17.03	74.00	100	77	Peak

Note:

- " \*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
- Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.090	13.78	30.17	43.96	-10.04	54.00	100	77	Average
2	2390.000	13.62	30.18	43.80	-10.20	54.00	100	77	Average
3	2435.780	68.07	30.26	98.32	N/A	N/A	100	77	Average
4	2483.500	13.65	30.32	43.97	-10.03	54.00	100	77	Average
5	* 2488.410	14.14	30.32	44.46	-9.54	54.00	100	77	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.340	75.17	30.29	105.46	N/A	N/A	230	255	Peak
2	2483.500	25.92	30.32	56.23	-17.77	74.00	230	255	Peak
3	* 2495.380	27.78	30.33	58.11	-15.89	74.00	230	255	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2462.980	72.03	30.29	102.32	N/A	N/A	230	255	Average
2	2483.500	14.18	30.32	44.50	-9.50	54.00	230	255	Average
3	* 2486.320	15.31	30.32	45.63	-8.37	54.00	230	255	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.640	71.21	30.29	101.50	N/A	N/A	100	66	Peak
2	2483.500	24.96	30.32	55.27	-18.73	74.00	100	66	Peak
3	* 2486.500	26.48	30.32	56.81	-17.19	74.00	100	66	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-09
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.880	68.09	30.29	98.37	N/A	N/A	100	66	Average
2	2483.500	13.31	30.32	43.62	-10.38	54.00	100	66	Average
3	* 2484.640	14.17	30.32	44.49	-9.51	54.00	100	66	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.750	39.11	30.18	69.29	-4.71	74.00	230	258	Peak
2	* 2390.000	41.31	30.18	71.49	-2.51	74.00	230	258	Peak
3	2413.125	78.59	30.23	108.82	N/A	N/A	230	258	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	22.06	30.18	52.24	-1.76	54.00	230	258	Average
2	* 2390.000	23.67	30.18	53.85	-0.15	54.00	230	258	Average
3	2411.000	69.13	30.22	99.36	N/A	N/A	230	258	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2387.500	36.38	30.17	66.55	-7.45	74.00	100	21	Peak
2	* 2390.000	36.95	30.18	67.13	-6.87	74.00	100	21	Peak
3	2410.750	74.33	30.22	104.55	N/A	N/A	100	21	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	19.04	30.18	49.22	-4.78	54.00	100	21	Average
2	* 2390.000	20.35	30.18	50.53	-3.47	54.00	100	21	Average
3	2410.875	65.43	30.22	95.65	N/A	N/A	100	21	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 2_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2389.000	43.47	30.18	73.65	-0.35	74.00	240	256	Peak
2		2390.000	40.44	30.18	70.62	-3.38	74.00	240	256	Peak
3		2418.250	80.07	30.23	110.31	N/A	N/A	240	256	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 2_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.875	23.20	30.18	53.38	-0.62	54.00	240	256	Average
2	* 2390.000	23.69	30.18	53.87	-0.13	54.00	240	256	Average
3	2416.000	71.09	30.23	101.32	N/A	N/A	240	256	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 2_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2387.875	40.01	30.17	70.18	-3.82	74.00	170	93	Peak
2		2390.000	34.21	30.18	64.39	-9.61	74.00	170	93	Peak
3		2418.500	77.56	30.23	107.79	N/A	N/A	170	93	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 2_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.750	19.31	30.18	49.48	-4.52	54.00	170	93	Average
2	* 2390.000	19.71	30.18	49.89	-4.11	54.00	170	93	Average
3	2418.250	68.29	30.23	98.52	N/A	N/A	170	93	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2389.040	30.96	30.18	61.14	-12.86	74.00	230	257	Peak
2	2390.000	28.17	30.18	58.35	-15.65	74.00	230	257	Peak
3	2435.780	80.33	30.26	110.59	N/A	N/A	230	257	Peak
4	2483.500	29.42	30.32	59.73	-14.27	74.00	230	257	Peak
5	2484.800	30.77	30.32	61.09	-12.91	74.00	230	257	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.660	15.48	30.18	45.65	-8.35	54.00	230	257	Average
2	2390.000	15.53	30.18	45.71	-8.29	54.00	230	257	Average
3	2438.820	71.12	30.26	101.38	N/A	N/A	230	257	Average
4	2483.500	16.07	30.32	46.39	-7.61	54.00	230	257	Average
5	* 2486.130	16.33	30.32	46.65	-7.35	54.00	230	257	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2386.380	30.87	30.17	61.04	-12.96	74.00	100	76	Peak
2		2390.000	26.85	30.18	57.03	-16.97	74.00	100	76	Peak
3		2437.870	76.75	30.26	107.00	N/A	N/A	100	76	Peak
4		2483.500	26.31	30.32	56.63	-17.37	74.00	100	76	Peak
5		2486.320	28.98	30.32	59.31	-14.69	74.00	100	76	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.280	14.44	30.17	44.62	-9.38	54.00	100	76	Average
2	2390.000	14.32	30.18	44.50	-9.50	54.00	100	76	Average
3	2438.250	67.15	30.26	97.41	N/A	N/A	100	76	Average
4	* 2483.500	14.65	30.32	44.97	-9.03	54.00	100	76	Average
5	2484.420	14.60	30.32	44.92	-9.08	54.00	100	76	Average

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 10_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2458.060	80.46	30.28	110.75	N/A	N/A	240	254	Peak
2	2483.500	42.20	30.32	72.52	-1.48	74.00	240	254	Peak
3	* 2485.240	43.15	30.32	73.47	-0.53	74.00	240	254	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 10_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2458.180	70.55	30.28	100.84	N/A	N/A	240	254	Average
2	* 2483.500	23.52	30.32	53.84	-0.16	54.00	240	254	Average
3	2484.700	22.21	30.32	52.53	-1.47	54.00	240	254	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 10_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2455.720	77.60	30.28	107.88	N/A	N/A	176	111	Peak
2	2483.500	37.95	30.32	68.27	-5.73	74.00	176	111	Peak
3	* 2485.300	39.35	30.32	69.67	-4.33	74.00	176	111	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 10_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2456.140	68.18	30.28	98.46	N/A	N/A	176	111	Average
2	* 2483.500	19.88	30.32	50.20	-3.80	54.00	176	111	Average
3	2484.760	19.23	30.32	49.55	-4.45	54.00	176	111	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.100	78.33	30.29	108.62	N/A	N/A	230	256	Peak
2	* 2483.500	43.57	30.32	73.88	-0.12	74.00	230	256	Peak
3	2484.640	38.72	30.32	69.04	-4.96	74.00	230	256	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2462.920	69.08	30.29	99.37	N/A	N/A	230	256	Average
2	* 2483.500	23.28	30.32	53.60	-0.40	54.00	230	256	Average
3	2484.520	21.10	30.32	51.42	-2.58	54.00	230	256	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.160	73.98	30.29	104.27	N/A	N/A	100	65	Peak
2	* 2483.500	38.74	30.32	69.06	-4.94	74.00	100	65	Peak
3	2484.520	35.44	30.32	65.76	-8.24	74.00	100	65	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.940	64.52	30.29	94.80	N/A	N/A	100	65	Average
2	* 2483.500	18.16	30.32	48.47	-5.53	54.00	100	65	Average
3	2484.520	17.06	30.32	47.38	-6.62	54.00	100	65	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.125	40.77	30.17	70.94	-3.06	74.00	230	257	Peak
2	* 2390.000	41.94	30.18	72.12	-1.88	74.00	230	257	Peak
3	2412.000	77.55	30.22	107.77	N/A	N/A	230	257	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	22.22	30.18	52.40	-1.60	54.00	230	257	Average
2	* 2390.000	23.64	30.18	53.82	-0.18	54.00	230	257	Average
3	2410.750	68.12	30.22	98.34	N/A	N/A	230	257	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2387.250	37.43	30.17	67.60	-6.40	74.00	100	22	Peak
2	* 2390.000	38.55	30.18	68.73	-5.27	74.00	100	22	Peak
3	2409.750	74.03	30.22	104.25	N/A	N/A	100	22	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	19.53	30.18	49.71	-4.29	54.00	100	22	Average
2	* 2390.000	20.72	30.18	50.90	-3.10	54.00	100	22	Average
3	2410.625	64.70	30.22	94.92	N/A	N/A	100	22	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 2_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2387.250	43.33	30.17	73.50	-0.50	74.00	240	256	Peak
2	2390.000	40.89	30.18	71.07	-2.93	74.00	240	256	Peak
3	2418.500	80.06	30.23	110.29	N/A	N/A	240	256	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 2_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.875	22.66	30.18	52.84	-1.16	54.00	240	256	Average
2	* 2390.000	23.71	30.18	53.89	-0.11	54.00	240	256	Average
3	2415.875	70.87	30.23	101.10	N/A	N/A	240	256	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 2_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2386.750	36.56	30.17	66.73	-7.27	74.00	171	94	Peak
2	* 2390.000	38.57	30.18	68.75	-5.25	74.00	171	94	Peak
3	2416.625	77.18	30.23	107.41	N/A	N/A	171	94	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 2_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.875	19.52	30.18	49.70	-4.30	54.00	171	94	Average
2	* 2390.000	20.56	30.18	50.74	-3.26	54.00	171	94	Average
3	2418.250	68.38	30.23	98.61	N/A	N/A	171	94	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2384.480	30.22	30.16	60.39	-13.61	74.00	230	257	Peak
2	2390.000	27.87	30.18	58.05	-15.95	74.00	230	257	Peak
3	2436.920	79.86	30.26	110.11	N/A	N/A	230	257	Peak
4	2483.500	28.99	30.32	59.31	-14.69	74.00	230	257	Peak
5	* 2485.180	30.67	30.32	60.99	-13.01	74.00	230	257	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.040	15.45	30.18	45.63	-8.37	54.00	230	257	Average
2	2390.000	15.29	30.18	45.47	-8.53	54.00	230	257	Average
3	2438.250	70.75	30.26	101.01	N/A	N/A	230	257	Average
4	* 2483.500	16.28	30.32	46.59	-7.41	54.00	230	257	Average
5	2484.420	16.21	30.32	46.53	-7.47	54.00	230	257	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2385.810	28.19	30.17	58.36	-15.64	74.00	100	77	Peak
2		2390.000	26.21	30.18	56.39	-17.61	74.00	100	77	Peak
3		2435.780	76.18	30.26	106.43	N/A	N/A	100	77	Peak
4		2483.500	28.02	30.32	58.33	-15.67	74.00	100	77	Peak
5		2487.840	27.32	30.32	57.65	-16.35	74.00	100	77	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.850	14.48	30.18	44.66	-9.34	54.00	100	77	Average
2	2390.000	13.89	30.18	44.07	-9.93	54.00	100	77	Average
3	2438.250	66.80	30.26	97.05	N/A	N/A	100	77	Average
4	2483.500	14.10	30.32	44.42	-9.58	54.00	100	77	Average
5	* 2485.370	14.57	30.32	44.89	-9.11	54.00	100	77	Average

Note:

- " \*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 10_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2456.860	79.80	30.28	110.09	N/A	N/A	240	256	Peak
2	2483.500	41.20	30.32	71.51	-2.49	74.00	240	256	Peak
3	* 2485.000	43.53	30.32	73.85	-0.15	74.00	240	256	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 10_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2457.820	70.32	30.28	100.60	N/A	N/A	240	256	Average
2	* 2483.500	23.56	30.32	53.88	-0.12	54.00	240	256	Average
3	2484.640	22.56	30.32	52.88	-1.12	54.00	240	256	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 10_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2456.920	77.70	30.28	107.98	N/A	N/A	176	128	Peak
2	2483.500	37.65	30.32	67.97	-6.03	74.00	176	128	Peak
3	* 2486.020	39.96	30.32	70.28	-3.72	74.00	176	128	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 10_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2455.960	68.42	30.28	98.70	N/A	N/A	176	128	Average
2	* 2483.500	20.89	30.32	51.21	-2.79	54.00	176	128	Average
3	2484.700	20.60	30.32	50.92	-3.08	54.00	176	128	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2461.720	77.44	30.29	107.73	N/A	N/A	230	254	Peak
2	2483.500	41.41	30.32	71.73	-2.27	74.00	230	254	Peak
3	* 2484.100	43.54	30.32	73.86	-0.14	74.00	230	254	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.040	67.64	30.29	97.93	N/A	N/A	230	254	Average
2	* 2483.500	21.12	30.32	51.44	-2.56	54.00	230	254	Average
3	2484.700	20.00	30.32	50.32	-3.68	54.00	230	254	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2461.780	73.24	30.29	103.53	N/A	N/A	100	70	Peak
2	* 2483.500	37.86	30.32	68.18	-5.82	74.00	100	70	Peak
3	2484.520	37.00	30.32	67.32	-6.68	74.00	100	70	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.580	63.33	30.29	93.62	N/A	N/A	100	70	Average
2	* 2483.500	17.95	30.32	48.26	-5.74	54.00	100	70	Average
3	2484.700	16.94	30.32	47.26	-6.74	54.00	100	70	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2371.500	26.73	30.13	56.86	-17.14	74.00	220	288	Peak
2	2390.000	25.27	30.18	55.44	-18.56	74.00	220	288	Peak
3	2413.375	71.76	30.23	101.98	N/A	N/A	220	288	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2385.625	14.39	30.17	44.56	-9.44	54.00	220	288	Average
2		2390.000	13.28	30.18	43.46	-10.54	54.00	220	288	Average
3		2413.125	68.66	30.23	98.89	N/A	N/A	220	288	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	27.04	30.17	57.21	-16.79	74.00	104	298	Peak
2		24.98	30.18	55.16	-18.84	74.00	104	298	Peak
3		71.11	30.23	101.33	N/A	N/A	104	298	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2386.375	14.58	30.17	44.75	-9.25	54.00	104	298	Average
2		2390.000	13.53	30.18	43.71	-10.29	54.00	104	298	Average
3		2413.125	67.95	30.23	98.18	N/A	N/A	104	298	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2363.010	26.35	30.10	56.45	-17.55	74.00	247	287	Peak
2	2390.000	24.53	30.18	54.71	-19.29	74.00	247	287	Peak
3	2438.250	72.09	30.26	102.35	N/A	N/A	247	287	Peak
4	2483.500	25.08	30.32	55.40	-18.60	74.00	247	287	Peak
5	* 2489.170	26.18	30.33	56.51	-17.49	74.00	247	287	Peak

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2386.570	13.71	30.17	43.88	-10.12	54.00	247	287	Average
2	2390.000	13.42	30.18	43.60	-10.40	54.00	247	287	Average
3	2438.060	68.95	30.26	99.21	N/A	N/A	247	287	Average
4	2483.500	13.62	30.32	43.94	-10.06	54.00	247	287	Average
5	* 2498.290	13.98	30.34	44.32	-9.68	54.00	247	287	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2371.180	26.34	30.13	56.46	-17.54	74.00	114	235	Peak
2	2390.000	24.24	30.18	54.42	-19.58	74.00	114	235	Peak
3	2438.250	71.75	30.26	102.01	N/A	N/A	114	235	Peak
4	2483.500	23.77	30.32	54.09	-19.91	74.00	114	235	Peak
5	* 2495.250	26.54	30.33	56.88	-17.12	74.00	114	235	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2383.340	13.75	30.16	43.92	-10.08	54.00	114	235	Average
2	2390.000	13.61	30.18	43.79	-10.21	54.00	114	235	Average
3	2435.970	68.60	30.26	98.85	N/A	N/A	114	235	Average
4	2483.500	13.13	30.32	43.45	-10.55	54.00	114	235	Average
5	* 2489.550	14.08	30.33	44.40	-9.60	54.00	114	235	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.160	71.67	30.29	101.96	N/A	N/A	194	289	Peak
2	2483.500	26.44	30.32	56.76	-17.24	74.00	194	289	Peak
3	* 2498.320	27.30	30.34	57.64	-16.36	74.00	194	289	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.040	68.48	30.29	98.77	N/A	N/A	194	289	Average
2	2483.500	13.39	30.32	43.71	-10.29	54.00	194	289	Average
3	* 2486.140	14.32	30.32	44.64	-9.36	54.00	194	289	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.580	71.37	30.29	101.66	N/A	N/A	110	234	Peak
2	2483.500	25.07	30.32	55.39	-18.61	74.00	110	234	Peak
3	* 2486.920	27.41	30.32	57.74	-16.26	74.00	110	234	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-10
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11b_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.760	68.14	30.29	98.43	N/A	N/A	110	234	Average
2	2483.500	13.52	30.32	43.84	-10.16	54.00	110	234	Average
3	* 2486.260	14.28	30.32	44.60	-9.40	54.00	110	234	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2383.125	38.90	30.16	69.06	-4.94	74.00	223	289	Peak
2	* 2390.000	41.95	30.18	72.13	-1.87	74.00	223	289	Peak
3	2413.125	76.01	30.23	106.23	N/A	N/A	223	289	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	22.42	30.18	52.60	-1.40	54.00	223	289	Average
2	* 2390.000	23.63	30.18	53.81	-0.19	54.00	223	289	Average
3	2413.250	66.04	30.23	96.26	N/A	N/A	223	289	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	39.25	30.18	69.43	-4.57	74.00	104	298	Peak
2	* 2390.000	40.00	30.18	70.18	-3.82	74.00	104	298	Peak
3	2413.250	74.57	30.23	104.79	N/A	N/A	104	298	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	20.99	30.18	51.16	-2.84	54.00	104	298	Average
2	* 2390.000	22.52	30.18	52.70	-1.30	54.00	104	298	Average
3	2410.750	65.44	30.22	95.66	N/A	N/A	104	298	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 2_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2388.500	41.80	30.18	71.98	-2.02	74.00	200	306	Peak
2		2390.000	37.94	30.18	68.12	-5.88	74.00	200	306	Peak
3		2418.000	75.49	30.23	105.72	N/A	N/A	200	306	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 2_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	20.25	30.18	50.43	-3.57	54.00	200	306	Average
2	* 2390.000	21.05	30.18	51.23	-2.77	54.00	200	306	Average
3	2415.625	66.16	30.23	96.39	N/A	N/A	200	306	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 2_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2388.750	43.64	30.18	73.82	-0.18	74.00	108	242	Peak
2		2390.000	40.01	30.18	70.19	-3.81	74.00	108	242	Peak
3		2418.000	77.56	30.23	107.79	N/A	N/A	108	242	Peak

Note:

1. "\*" , means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 2_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	21.55	30.18	51.72	-2.28	54.00	108	242	Average
2	* 2390.000	22.45	30.18	52.63	-1.37	54.00	108	242	Average
3	2415.875	67.83	30.23	98.06	N/A	N/A	108	242	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2385.430	30.40	30.17	60.56	-13.44	74.00	244	286	Peak
2		2390.000	27.59	30.18	57.77	-16.23	74.00	244	286	Peak
3		2438.440	77.73	30.26	107.99	N/A	N/A	244	286	Peak
4		2483.500	26.01	30.32	56.33	-17.67	74.00	244	286	Peak
5		2485.370	26.82	30.32	57.14	-16.86	74.00	244	286	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.040	14.70	30.18	44.88	-9.12	54.00	244	286	Average
2	* 2390.000	14.97	30.18	45.15	-8.85	54.00	244	286	Average
3	2437.680	68.19	30.26	98.45	N/A	N/A	244	286	Average
4	2483.500	14.44	30.32	44.76	-9.24	54.00	244	286	Average
5	2485.940	14.65	30.32	44.97	-9.03	54.00	244	286	Average

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
- Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2383.910	28.29	30.16	58.45	-15.55	74.00	127	236	Peak
2	2390.000	27.33	30.18	57.51	-16.49	74.00	127	236	Peak
3	2438.250	76.96	30.26	107.22	N/A	N/A	127	236	Peak
4	2483.500	26.27	30.32	56.59	-17.41	74.00	127	236	Peak
5	2485.560	26.89	30.32	57.21	-16.79	74.00	127	236	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2382.580	14.40	30.16	44.56	-9.44	54.00	127	236	Average
2	2390.000	14.24	30.18	44.42	-9.58	54.00	127	236	Average
3	2438.250	67.84	30.26	98.09	N/A	N/A	127	236	Average
4	* 2483.500	14.79	30.32	45.11	-8.89	54.00	127	236	Average
5	2485.370	14.75	30.32	45.07	-8.93	54.00	127	236	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 10_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2458.180	75.98	30.28	106.26	N/A	N/A	198	282	Peak
2	* 2483.500	38.90	30.32	69.22	-4.78	74.00	198	282	Peak
3	2484.940	38.80	30.32	69.12	-4.88	74.00	198	282	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 10_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2455.840	66.51	30.28	96.79	N/A	N/A	198	282	Average
2	* 2483.500	21.21	30.32	51.53	-2.47	54.00	198	282	Average
3	2484.520	20.09	30.32	50.41	-3.59	54.00	198	282	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 10_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2458.000	79.19	30.28	109.48	N/A	N/A	100	245	Peak
2	2483.500	41.51	30.32	71.83	-2.17	74.00	100	245	Peak
3	* 2485.060	41.64	30.32	71.96	-2.04	74.00	100	245	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 10_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2455.960	69.41	30.28	99.70	N/A	N/A	100	245	Average
2	* 2483.500	23.58	30.32	53.90	-0.10	54.00	100	245	Average
3	2484.520	22.65	30.32	52.97	-1.03	54.00	100	245	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2462.980	76.17	30.29	106.46	N/A	N/A	192	290	Peak
2	* 2483.500	43.54	30.32	73.86	-0.14	74.00	192	290	Peak
3	2484.640	41.03	30.32	71.35	-2.65	74.00	192	290	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2462.680	66.40	30.29	96.69	N/A	N/A	192	290	Average
2	* 2483.500	22.34	30.32	52.66	-1.34	54.00	192	290	Average
3	2484.640	20.30	30.32	50.62	-3.38	54.00	192	290	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.220	75.26	30.29	105.55	N/A	N/A	113	235	Peak
2	* 2483.500	39.75	30.32	70.07	-3.93	74.00	113	235	Peak
3	2486.140	38.41	30.32	68.74	-5.26	74.00	113	235	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11g_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.820	65.86	30.29	96.15	N/A	N/A	113	235	Average
2	* 2483.500	21.25	30.32	51.57	-2.43	54.00	113	235	Average
3	2484.640	19.44	30.32	49.76	-4.24	54.00	113	235	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	41.04	30.18	71.21	-2.79	74.00	224	290	Peak
2	* 2390.000	42.99	30.18	73.17	-0.83	74.00	224	290	Peak
3	2414.250	74.53	30.23	104.76	N/A	N/A	224	290	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.750	21.68	30.18	51.86	-2.14	54.00	224	290	Average
2	* 2390.000	23.64	30.18	53.82	-0.18	54.00	224	290	Average
3	2413.125	65.78	30.23	96.00	N/A	N/A	224	290	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.750	40.32	30.18	70.50	-3.50	74.00	108	298	Peak
2	* 2390.000	41.29	30.18	71.47	-2.53	74.00	108	298	Peak
3	2411.125	73.88	30.22	104.11	N/A	N/A	108	298	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 1_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	22.48	30.18	52.66	-1.34	54.00	108	298	Average
2	* 2390.000	23.07	30.18	53.25	-0.75	54.00	108	298	Average
3	2413.375	64.85	30.23	95.08	N/A	N/A	108	298	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 2_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2388.750	40.77	30.18	70.94	-3.06	74.00	200	307	Peak
2		2390.000	37.34	30.18	67.52	-6.48	74.00	200	307	Peak
3		2415.125	75.45	30.23	105.67	N/A	N/A	200	307	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 2_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	21.45	30.18	51.62	-2.38	54.00	200	307	Average
2	* 2390.000	22.07	30.18	52.25	-1.75	54.00	200	307	Average
3	2415.750	66.22	30.23	96.45	N/A	N/A	200	307	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 2_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2388.875	41.75	30.18	71.93	-2.07	74.00	104	243	Peak
2		2390.000	40.70	30.18	70.88	-3.12	74.00	104	243	Peak
3		2417.250	77.28	30.23	107.51	N/A	N/A	104	243	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 2_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2389.000	22.25	30.18	52.43	-1.57	54.00	104	243	Average
2	* 2390.000	23.63	30.18	53.81	-0.19	54.00	104	243	Average
3	2418.375	67.65	30.23	97.88	N/A	N/A	104	243	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	2388.660	30.34	30.18	60.51	-13.49	74.00	245	286	Peak
2		2390.000	28.66	30.18	58.84	-15.16	74.00	245	286	Peak
3		2438.820	77.56	30.26	107.82	N/A	N/A	245	286	Peak
4		2483.500	28.15	30.32	58.47	-15.53	74.00	245	286	Peak
5		2485.370	28.84	30.32	59.16	-14.84	74.00	245	286	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2386.950	15.10	30.17	45.27	-8.73	54.00	245	286	Average
2	* 2390.000	15.62	30.18	45.80	-8.20	54.00	245	286	Average
3	2435.780	68.58	30.26	98.84	N/A	N/A	245	286	Average
4	2483.500	15.17	30.32	45.49	-8.51	54.00	245	286	Average
5	2484.990	15.04	30.32	45.36	-8.64	54.00	245	286	Average

Note:

- "\*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2386.570	27.65	30.17	57.82	-16.18	74.00	114	236	Peak
2	2390.000	26.98	30.18	57.16	-16.84	74.00	114	236	Peak
3	2438.440	77.04	30.26	107.30	N/A	N/A	114	236	Peak
4	2483.500	28.31	30.32	58.62	-15.38	74.00	114	236	Peak
5	* 2484.230	32.86	30.32	63.17	-10.83	74.00	114	236	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2386.950	15.07	30.17	45.24	-8.76	54.00	114	236	Average
2	2390.000	14.42	30.18	44.60	-9.40	54.00	114	236	Average
3	2438.250	67.88	30.26	98.14	N/A	N/A	114	236	Average
4	2483.500	14.72	30.32	45.04	-8.96	54.00	114	236	Average
5	* 2484.040	15.17	30.32	45.49	-8.51	54.00	114	236	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 10_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2454.100	77.15	30.28	107.43	N/A	N/A	172	278	Peak
2	2483.500	39.06	30.32	69.38	-4.62	74.00	172	278	Peak
3	* 2485.120	40.88	30.32	71.20	-2.80	74.00	172	278	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 10_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2456.140	67.74	30.28	98.02	N/A	N/A	172	278	Average
2	* 2483.500	20.80	30.32	51.12	-2.88	54.00	172	278	Average
3	2484.520	20.08	30.32	50.40	-3.60	54.00	172	278	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 10_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2455.840	77.88	30.28	108.16	N/A	N/A	100	245	Peak
2	2483.500	42.32	30.32	72.64	-1.36	74.00	100	245	Peak
3	* 2484.760	42.60	30.32	72.92	-1.08	74.00	100	245	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 10_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2455.540	68.85	30.28	99.13	N/A	N/A	100	245	Average
2	* 2483.500	23.56	30.32	53.87	-0.13	54.00	100	245	Average
3	2484.700	21.93	30.32	52.25	-1.75	54.00	100	245	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2461.720	75.32	30.29	105.61	N/A	N/A	194	290	Peak
2	* 2483.500	43.51	30.32	73.83	-0.17	74.00	194	290	Peak
3	2484.700	41.94	30.32	72.26	-1.74	74.00	194	290	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Horizontal	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.040	65.69	30.29	95.98	N/A	N/A	194	290	Average
2	* 2483.500	22.83	30.32	53.15	-0.85	54.00	194	290	Average
3	2484.580	21.03	30.32	51.35	-2.65	54.00	194	290	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.460	74.25	30.29	104.54	N/A	N/A	110	235	Peak
2	* 2483.500	40.81	30.32	71.13	-2.87	74.00	110	235	Peak
3	2484.520	40.19	30.32	70.51	-3.49	74.00	110	235	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-14
Factor	DRH18-E	Temp. / Humidity	22°C /60%
Polarity	Vertical	Site / Test Engineer	AC2 / Marvin
Test Mode	802.11n-20MHz_TX_CH 11_ANT 1	Test Voltage	AC 120V/60Hz



No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2461.000	65.07	30.29	95.35	N/A	N/A	110	235	Average
2	* 2483.500	21.65	30.32	51.96	-2.04	54.00	110	235	Average
3	2484.580	19.81	30.32	50.12	-3.88	54.00	110	235	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



## 7.8. AC Conducted Emissions Measurement


### 7.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 7.8.2. Test Setup



### 7.8.3. Test Result

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-20
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	26.4°C /52%
Polarity	Line1	Site / Test Engineer	SR2 / Amber
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	0.154	41.60	9.62	51.22	-14.54	65.75	QP
2	0.154	23.06	9.62	32.68	-23.07	55.75	Average
3	* 0.186	41.30	9.62	50.92	-13.29	64.21	QP
4	* 0.186	26.52	9.62	36.14	-18.07	54.21	Average
5	0.267	27.17	9.63	36.80	-24.41	61.21	QP
6	0.267	16.57	9.63	26.20	-25.01	51.21	Average
7	0.514	29.64	9.64	39.28	-16.72	56.00	QP
8	0.514	20.32	9.64	29.96	-16.04	46.00	Average
9	2.985	20.15	9.71	29.86	-26.14	56.00	QP
10	2.985	14.89	9.71	24.60	-21.40	46.00	Average
11	18.171	19.92	9.92	29.84	-30.16	60.00	QP
12	18.171	14.01	9.92	23.93	-26.07	50.00	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-20
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	26.4°C /52%
Polarity	Neutral	Site / Test Engineer	SR2 / Amber
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	* 0.150	44.90	9.62	54.52	-11.48	66.00	QP
2	* 0.150	27.68	9.62	37.30	-18.70	56.00	Average
3	0.181	36.07	9.62	45.70	-18.72	64.42	QP
4	0.181	20.36	9.62	29.98	-24.44	54.42	Average
5	0.289	27.94	9.63	37.56	-22.98	60.54	QP
6	0.289	8.18	9.63	17.81	-32.73	50.54	Average
7	0.519	26.85	9.64	36.50	-19.50	56.00	QP
8	0.519	20.39	9.64	30.03	-15.97	46.00	Average
9	2.580	20.52	9.70	30.22	-25.78	56.00	QP
10	2.580	16.86	9.70	26.57	-19.43	46.00	Average
11	11.777	18.31	9.89	28.20	-31.80	60.00	QP
12	11.777	12.95	9.89	22.84	-27.16	50.00	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-20
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	26.4°C /52%
Polarity	Line1	Site / Test Engineer	SR2 / Amber
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	* 0.154	43.60	9.62	53.22	-12.53	65.75	QP
2	* 0.154	28.18	9.62	37.80	-17.95	55.75	Average
3	0.195	39.37	9.62	48.99	-14.83	63.82	QP
4	0.195	21.49	9.62	31.11	-22.71	53.82	Average
5	0.537	27.83	9.64	37.47	-18.53	56.00	QP
6	0.537	21.32	9.64	30.96	-15.04	46.00	Average
7	2.287	19.55	9.70	29.25	-26.75	56.00	QP
8	2.287	14.68	9.70	24.37	-21.63	46.00	Average
9	5.599	13.07	9.76	22.83	-37.17	60.00	QP
10	5.599	7.69	9.76	17.45	-32.55	50.00	Average
11	18.202	19.74	9.92	29.66	-30.34	60.00	QP
12	18.202	14.01	9.92	23.93	-26.07	50.00	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-20
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	26.4°C /52%
Polarity	Neutral	Site / Test Engineer	SR2 / Amber
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	* 0.154	43.24	9.62	52.86	-12.89	65.75	QP
2	* 0.154	27.56	9.62	37.18	-18.58	55.75	Average
3	0.181	33.30	9.62	42.92	-21.50	64.42	QP
4	0.181	18.10	9.62	27.73	-26.69	54.42	Average
5	0.231	29.74	9.62	39.36	-23.05	62.41	QP
6	0.231	17.65	9.62	27.27	-25.14	52.41	Average
7	0.519	26.09	9.64	35.73	-20.27	56.00	QP
8	0.519	20.00	9.64	29.64	-16.36	46.00	Average
9	2.571	21.66	9.70	31.36	-24.64	56.00	QP
10	2.571	16.53	9.70	26.23	-19.77	46.00	Average
11	12.501	19.84	9.90	29.74	-30.26	60.00	QP
12	12.501	13.80	9.90	23.70	-26.30	50.00	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-20
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	26.4°C /52%
Polarity	Line1	Site / Test Engineer	SR2 / Amber
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 240V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	* 0.159	43.51	9.62	53.13	-12.39	65.52	QP
2	* 0.159	28.84	9.62	38.47	-17.05	55.52	Average
3	0.195	33.93	9.62	43.56	-20.26	63.82	QP
4	0.195	20.02	9.62	29.65	-24.18	53.82	Average
5	0.285	29.31	9.63	38.93	-21.74	60.67	QP
6	0.285	17.04	9.63	26.67	-24.00	50.67	Average
7	0.559	28.63	9.65	38.27	-17.73	56.00	QP
8	0.559	21.93	9.65	31.58	-14.42	46.00	Average
9	2.503	22.20	9.70	31.91	-24.09	56.00	QP
10	2.503	17.19	9.70	26.89	-19.11	46.00	Average
11	18.184	28.51	9.92	38.42	-21.58	60.00	QP
12	18.184	22.54	9.92	32.45	-17.55	50.00	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-20
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	26.4°C /52%
Polarity	Neutral	Site / Test Engineer	SR2 / Amber
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 240V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	*	0.154	41.11	9.62	50.73	-15.02	65.75	QP
2	*	0.154	24.83	9.62	34.45	-21.30	55.75	Average
3		0.204	34.66	9.62	44.28	-19.17	63.45	QP
4		0.204	18.93	9.62	28.56	-24.89	53.45	Average
5		0.294	25.71	9.63	35.33	-25.08	60.41	QP
6		0.294	14.41	9.63	24.04	-26.37	50.41	Average
7		0.564	27.26	9.65	36.90	-19.10	56.00	QP
8		0.564	20.58	9.65	30.22	-15.78	46.00	Average
9		2.562	22.69	9.70	32.39	-23.61	56.00	QP
10		2.562	17.81	9.70	27.51	-18.49	46.00	Average
11		18.814	24.24	9.98	34.22	-25.78	60.00	QP
12		18.814	16.14	9.98	26.13	-23.87	50.00	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-20
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	26.4°C /52%
Polarity	Line1	Site / Test Engineer	SR2 / Amber
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 240V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	0.150	38.70	9.62	48.32	-17.68	66.00	QP
2	0.150	24.60	9.62	34.22	-21.78	56.00	Average
3	0.186	37.37	9.62	47.00	-17.22	64.21	QP
4	0.186	23.03	9.62	32.65	-21.57	54.21	Average
5	0.285	27.68	9.63	37.31	-23.36	60.67	QP
6	0.285	15.45	9.63	25.07	-25.59	50.67	Average
7	* 0.555	29.55	9.64	39.19	-16.81	56.00	QP
8	* 0.555	23.62	9.64	33.27	-12.73	46.00	Average
9	2.526	21.78	9.70	31.48	-24.52	56.00	QP
10	2.526	16.90	9.70	26.60	-19.40	46.00	Average
11	18.225	28.41	9.92	38.32	-21.68	60.00	QP
12	18.225	21.38	9.92	31.29	-18.71	50.00	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).



EUT	Smart Wire-Free Security Camera	Date of Test	2023-06-20
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	26.4°C /52%
Polarity	Neutral	Site / Test Engineer	SR2 / Amber
Test Mode	802.11n-20MHz_TX_CH 6_ANT 1	Test Voltage	AC 240V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	0.159	40.04	9.62	49.66	-15.86	65.52	QP
2	0.159	23.53	9.62	33.15	-22.36	55.52	Average
3	0.177	36.44	9.62	46.06	-18.57	64.63	QP
4	0.177	19.27	9.62	28.89	-25.74	54.63	Average
5	0.276	30.69	9.63	40.31	-20.62	60.94	QP
6	0.276	12.08	9.63	21.70	-29.23	50.94	Average
7	* 0.559	27.48	9.65	37.13	-18.87	56.00	QP
8	* 0.559	21.07	9.65	30.71	-15.29	46.00	Average
9	2.521	21.93	9.70	31.63	-24.37	56.00	QP
10	2.521	17.81	9.70	27.51	-18.49	46.00	Average
11	18.801	23.18	9.98	33.16	-26.84	60.00	QP
12	18.801	15.16	9.98	25.14	-24.86	50.00	Average

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

## **8. CONCLUSION**

The data collected relate only the item(s) tested and show that the device is compliance with Part 15C of the FCC Rules.

## **Appendix A : Test Setup Photograph**

Refer to “2303TW0108-UT” file.

## **Appendix B : External Photograph**

Refer to “2303TW0108-UE” file.

## **Appendix C : Internal Photograph**

Refer to “2303TW0108-UI” file.

————— The End —————