

#### FCC RF EXPOSURE REPORT

For

Kasa Smart Wi-Fi Plug Mini

**MODEL NUMBER: EP10** 

FCC ID: 2AXJ4EP10

#### REPORT NUMBER: 4789626792.1-3

**ISSUE DATE: September 24, 2020** 

Prepared for

TP-Link Corporation Limited Room 901, 9/F. , New East Ocean Centre, 9 Science Museum Road, Tsim Sha Tsui, Kowloon, Hong Kong

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China Tel: +86 769-22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



### TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	3
2.	TEST METHODOLOGY	4
3.	FACILITIES AND ACCREDITATION	4
4.	REQUIREMENT	5



# 1. ATTESTATION OF TEST RESULTS

Applicant information	
Company Name:	TP-Link Corporation Limited
Address:	Room 901, 9/F. , New East Ocean Centre, 9 Science Museum Road, Tsim Sha Tsui, Kowloon, Hong Kong

#### Manufacturer Information

Company Name:	TP-Link Corporation Limited
Address:	Room 901, 9/F., New East Ocean Centre, 9 Science Museum
	Road, Tsim Sha Tsui, Kowloon, Hong Kong

#### **EUT Information**

EUT Name: Model: Brand Name: Sample Status: Sample ID: Sample Received Date: Date of Tested: Kasa Smart Wi-Fi Plug Mini EP10 tp-link Normal 3307872 July 29, 2020 July 30~August 6, 2020

APPLICABLE STANDARDS			
STANDARD	TEST RESULTS		
FCC 47CFR§2.1091	PASS		
KDB-447498 D01 V06			

Prepared By:

Kebo. zhang

Kebo Zhang Project Engineer

Approved By:

Stephen Guo Laboratory Manager Checked By:

Shemmy les

Shawn Wen Laboratory Leader



# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

## 3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.
	<b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules
Accreditation Certificate	ISED(Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



# 4. REQUIREMENT

#### LIMIT

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure					
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f2)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/150	30	
1500-100,000			1.0	30	
Note 1: f = frequency in MHz, * means Plane-wave equivalent power density					

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm<sup>2</sup> is available for this EUT.

#### **MPE CALCULATION METHOD**

### <u>S =PG/(4πR<sup>2</sup>)</u>

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



Radio Frequency Radiation Exposure Evaluation

WIFI 2.4G (Worst case)					
Operating	Max. Power	Max. Antenna Gain		Power density	Limit
Mode	(dBm)	(dBi)	(num)	(mW/ cm <sup>2</sup> )	
2.4G wifi	20	0.93	1.239	0.0246	1

Note:

- 1. The calculated distance is 20cm.
- 2. The Power comes from operation description.
- 3. Therefor the maximum calculations of above situations are less than the "1" limit.

# **END OF REPORT**