



FCC RF EXPOSURE REPORT

FCC ID: 2AXJ4KS200

Project No. : 2205C096

Equipment: Kasa Smart Wi-Fi Light Switch, Single Pole

Brand Name : tp-link
Test Model : KS200
Series Model : N/A

Applicant: TP-Link Corporation Limited

Address : Room 901, 9/F., New East Ocean Centre, 9 Science Museum Road,

Tsim Sha Tsui, Kowloon, Hong Kong

Manufacturer: TP-Link Corporation Limited

Address : Room 901, 9/F., New East Ocean Centre, 9 Science Museum Road,

Tsim Sha Tsui, Kowloon, Hong Kong

Date of Receipt : May 20, 2022

Date of Test : May 23, 2022 ~ Jul. 14, 2022

Issued Date : Jul. 25, 2022

Report Version : R01

Test Sample : Engineering Sample No.: DG2022052063 for BLE, DG2022052066 for

2.4G WIFI.

Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091

FCC Title 47 Part 2.1091

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by : Chella Zheng

Approved by : Chay Cai

IIIC-MRA



BTL Inc.

No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com



REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-3-2205C096	R00	Original Report	Jul. 15, 2022	Invalid
BTL-FCCP-3-2205C096	R01	Updated the test results of BLE.	Jul. 25, 2022	Valid



1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

BTL's Registration Number for FCC: 357015 BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

Ant.	t. Brand P/N		Antenna Type	Connector	Gain (dBi)
1	tp-link	6035500079	Internal	N/A	2.98

Note: The antenna gain is provided by the manufacturer.

3. TEST RESULTS

For BLE:

4	Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)		Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
	2.98	1.9861	5.22	3.3266	0.00132	1	Complies

For 2.4GHz:

4	ntenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW) Power Densit (S) (mW/cm²		Limit of Power Density (S) (mW/cm²)	Test Result
	2.98	1.9861	23.47	222.3310	0.08789	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.