

# RF Exposure Evaluation Statement

**Product Name:** Westgate Resorts Owner Tablet

**Model No.:** T802

**FCC ID:** 2AXKI-T802

## 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.1.3 EUT RF Exposure

Operational Mode: EDR (8-DPSK worst case)						
Channel Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
2402MHz	2.23	$\pm 1$	3.23	2.10	0.65	3.0
2441MHz	3.31	$\pm 1$	4.31	2.70	0.84	
2480MHz	3.52	$\pm 1$	4.52	2.83	0.89	
Operational Mode: BLE (worst case)						
2402	4.88	$\pm 1$	5.88	3.87	1.20	3.0
2442	5.01	$\pm 1$	6.01	3.99	1.25	
2480	5.01	$\pm 1$	6.01	3.99	1.26	
Operational Mode: 802.11n40 (worst case)						
2422	5.91	$\pm 1$	6.91	4.91	1.52	3.0
2437	4.95	$\pm 1$	5.95	3.94	1.23	
2452	5.99	$\pm 1$	6.99	5.00	1.57	
Conclusion: the calculated value $\leq 3.0$ , SAR is exempted.						