

# TEST REPORT

**Product Name** : Westgate Resorts Owner Tablet  
**Brand Mark** : Westgate Resorts  
**Model No.** : T802  
**FCC ID** : 2AXKI-T802  
**Report Number** : BLA-EMC-202107-A2501  
**Date of Sample Receipt** : 2021/7/8  
**Date of Test** : 2021/7/8 to 2021/7/27  
**Date of Issue** : 2021/7/27  
**Test Standard** : 47 CFR Part 15, Subpart C 15.247  
**Test Result** : Pass

Prepared for:

**Shenzhen Weihejia Electronic Technology Co.,LTD**  
11st floor, Taijiale technology Industrial park, Tongguan Road, Tianliao  
community, Gongming agency, Guangming new district, Shenzhen, China

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**  
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,  
Shenzhen, Guangdong Province, China  
**TEL: +86-755-23059481**

Compiled by:

*Jozu.*

Review by:

*Sueels*

Approved by:

*Bluezhong*

Date:

2021/7/27



**REPORT REVISE RECORD**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
00	2021/7/27	Original

BlueAsia

## TABLE OF CONTENTS

<b>1</b>	<b>TEST SUMMARY .....</b>	<b>5</b>
<b>2</b>	<b>GENERAL INFORMATION .....</b>	<b>6</b>
<b>3</b>	<b>GENERAL DESCRIPTION OF E.U.T. ....</b>	<b>6</b>
<b>4</b>	<b>TEST ENVIRONMENT .....</b>	<b>7</b>
<b>5</b>	<b>TEST MODE .....</b>	<b>7</b>
<b>6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>7</b>
<b>7</b>	<b>DESCRIPTION OF SUPPORT UNIT.....</b>	<b>8</b>
<b>8</b>	<b>LABORATORY LOCATION.....</b>	<b>8</b>
<b>9</b>	<b>TEST INSTRUMENTS LIST .....</b>	<b>9</b>
<b>10</b>	<b>CONDUCTED BAND EDGES MEASUREMENT.....</b>	<b>13</b>
10.1	LIMITS .....	13
10.2	BLOCK DIAGRAM OF TEST SETUP .....	13
10.3	TEST DATA.....	14
<b>11</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>15</b>
11.1	CONCLUSION .....	15
<b>12</b>	<b>CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>16</b>
12.1	LIMITS .....	16
12.2	BLOCK DIAGRAM OF TEST SETUP .....	16
12.3	TEST DATA.....	17
<b>13</b>	<b>DWELL TIME.....</b>	<b>18</b>
13.1	LIMITS .....	18
13.2	BLOCK DIAGRAM OF TEST SETUP .....	18
13.3	TEST DATA.....	19
<b>14</b>	<b>HOPPING CHANNEL NUMBER .....</b>	<b>20</b>
14.1	LIMITS .....	20
14.2	BLOCK DIAGRAM OF TEST SETUP .....	20
14.3	TEST DATA.....	20
<b>15</b>	<b>CARRIER FREQUENCIES SEPARATION .....</b>	<b>21</b>
15.1	LIMITS .....	21

15.2	BLOCK DIAGRAM OF TEST SETUP .....	21
15.3	TEST DATA.....	21
<b>16</b>	<b>20DB BANDWIDTH.....</b>	<b>22</b>
16.1	BLOCK DIAGRAM OF TEST SETUP .....	22
16.2	TEST DATA.....	22
<b>17</b>	<b>CONDUCTED PEAK OUTPUT POWER .....</b>	<b>23</b>
17.1	LIMITS .....	23
17.2	BLOCK DIAGRAM OF TEST SETUP .....	23
17.3	TEST DATA.....	24
<b>18</b>	<b>CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....</b>	<b>25</b>
18.1	LIMITS .....	25
18.2	BLOCK DIAGRAM OF TEST SETUP .....	25
18.3	PROCEDURE .....	25
18.4	TEST DATA.....	27
<b>19</b>	<b>RADIATED SPURIOUS EMISSIONS.....</b>	<b>29</b>
19.1	LIMITS .....	29
19.2	BLOCK DIAGRAM OF TEST SETUP .....	30
19.3	PROCEDURE .....	30
19.4	TEST DATA.....	32
<b>20</b>	<b>RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....</b>	<b>40</b>
20.1	LIMITS .....	40
20.2	BLOCK DIAGRAM OF TEST SETUP .....	41
20.3	PROCEDURE .....	41
20.4	TEST DATA.....	43
<b>21</b>	<b>APPENDIX.....</b>	<b>47</b>
	<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>94</b>
	<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>96</b>

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass

## 2 GENERAL INFORMATION

<b>Applicant</b>	Shenzhen Weihejia Electronic Technology Co.,LTD
<b>Address</b>	11st floor, Taijjale technology Industrial park, Tongguan Road, Tianliao community, Gongming agency, Guangming new district, Shenzhen, China
<b>Manufacturer</b>	ShenZhen WeiHejia Electronics Technology CO.,LTD
<b>Address</b>	11st floor, Taijjale technology Industrial park, Tongguan Road, Tianliao community, Gongming agency, Guangming new district, Shenzhen, China
<b>Factory</b>	ShenZhen WeiHejia Electronics Technology CO.,LTD
<b>Address</b>	11st floor, Taijjale technology Industrial park, Tongguan Road, Tianliao community, Gongming agency, Guangming new district, Shenzhen, China
<b>Product Name</b>	Westgate Resorts Owner Tablet
<b>Test Model No.</b>	T802

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	A863-68T5A
<b>Software Version</b>	Android 11.0
<b>Operation Frequency:</b>	2402MHz-2480MHz
<b>Modulation Type:</b>	GFSK, pi/4DQPSK, 8DPSK
<b>Channel Spacing:</b>	1MHz
<b>Number of Channels:</b>	79
<b>Antenna Type:</b>	Internal Antenna
<b>Antenna Gain:</b>	2.1 dBi

#### 4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25 °C	DC3.7V

#### 5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
BT	Keep the battery of the EUT in BT mode
TX	Keep the EUT in transmitting mode
TX mode (SE) below 1G	Keep the EUT in transmitting mode
Remark: Only the data of the worst mode would be recorded in this report.	

#### 6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

## 7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
N/A	N/A	N/A	N/A	N/A

## 8 LABORATORY LOCATION

All tests were performed at:  
BlueAsia of Technical Services(Shenzhen) Co., Ltd.  
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province,  
China  
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673  
No tests were sub-contracted.



## 9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Band Edges Measurement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Dwell Time					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Hopping Channel Number					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Carrier Frequencies Separation**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of 20dB Bandwidth**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Conducted Peak Output Power**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11

Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11
------------------	---------	--------	------------	------------	------------

**Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

**Test Equipment Of Radiated Spurious Emissions**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

<b>Test Equipment Of Radiated Emissions which fall in the restricted bands</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>S/N</b>	<b>Cal.Date</b>	<b>Cal.Due</b>
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A


## 10 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### 10.1 LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

### 10.2 BLOCK DIAGRAM OF TEST SETUP



### 10.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia

## 11 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


### 11.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.1dBi.




## 12 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### 12.1 LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

### 12.2 BLOCK DIAGRAM OF TEST SETUP





### 12.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia


### 13 DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

#### 13.1 LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

#### 13.2 BLOCK DIAGRAM OF TEST SETUP



### 13.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia


## 14 HOPPING CHANNEL NUMBER

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.3
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 14.1 LIMITS

<b>Frequency range(MHz)</b>	<b>Number of hopping channels (minimum)</b>
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

### 14.2 BLOCK DIAGRAM OF TEST SETUP



### 14.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


## 15 CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### 15.1 LIMITS

<b>Limit:</b>	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W
---------------	--

### 15.2 BLOCK DIAGRAM OF TEST SETUP




### 15.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

## 16 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### 16.1 BLOCK DIAGRAM OF TEST SETUP



### 16.2 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


## 17 CONDUCTED PEAK OUTPUT POWER

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 17.1 LIMITS

<b>Frequency range(MHz)</b>	<b>Output power of the intentional radiator(watt)</b>
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

### 17.2 BLOCK DIAGRAM OF TEST SETUP



### 17.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia



## 18 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	BT
Test Mode (Final Test)	BT
Tester	Jozu
Temperature	25°C
Humidity	60%

### 18.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 18.2 BLOCK DIAGRAM OF TEST SETUP



Remark:  
 E.U.T: Equipment Under Test  
 LISN: Line Impedance Stabilization Network  
 Test table height=0.8m

### 18.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.


- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia



[TestMode: BT]; [Line: Line]

**Conducted Emission Measurement**


Site:      Phase: **L1**      Temperature:      Humidity: %

Limit: FCC Class B Conduction(QP)      Power:      Humidity: %

EUT: Tablet PC

M/N: BT mode

Mode: T802

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.3379	30.32	9.85	40.17	59.25	-19.08	QP	
2		0.3379	19.81	9.85	29.66	49.25	-19.59	AVG	
3	*	0.5420	34.05	9.87	43.92	56.00	-12.08	QP	
4		0.5420	22.52	9.87	32.39	46.00	-13.61	AVG	
5		0.6660	29.90	9.88	39.78	56.00	-16.22	QP	
6		0.6660	18.80	9.88	28.68	46.00	-17.32	AVG	
7		0.8380	26.19	9.90	36.09	56.00	-19.91	QP	
8		0.8380	16.02	9.90	25.92	46.00	-20.08	AVG	
9		1.2300	27.59	9.92	37.51	56.00	-18.49	QP	
10		1.2300	16.57	9.92	26.49	46.00	-19.51	AVG	
11		2.3540	24.38	9.95	34.33	56.00	-21.67	QP	
12		2.3540	12.55	9.95	22.50	46.00	-23.50	AVG	

\*:Maximum data    x:Over limit    !:over margin

(Reference Only)

**Test Result: Pass**

## 19 RADIATED SPURIOUS EMISSIONS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX mode (SE) below 1G; TX mode (SE) above 1G
<b>Test Mode (Final Test)</b>	TX mode (SE) below 1G; TX mode (SE) above 1G
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 19.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 19.2 BLOCK DIAGRAM OF TEST SETUP



## 19.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

### 19.4 TEST DATA

[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC 202107-A25
EUT: Tablet PC	Test Engineer: Charlie
M/N: T802	Temperature: 25℃
S/N:	Humidity: 45%RH
Test Mode: BT mode	Test Voltage: AC 230V/50Hz
Note:	Test Data: 2021-07-27 15:43:23




No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	36.184MHz	40.0	25.3	-14.7	1.6	23.7	QP	Ver	100.0	112.0
2*	60.919MHz	40.0	22.8	-17.2	-0.5	23.3	QP	Ver	100.0	348.0
3*	134.518MHz	43.5	24.1	-19.4	0.7	23.4	QP	Ver	100.0	0.0
4*	253.585MHz	46.0	23.2	-22.8	0.5	22.7	QP	Ver	100.0	307.0
5*	525.428MHz	46.0	30.8	-15.2	1.7	29.1	QP	Ver	100.0	75.0
6*	997.939MHz	54.0	37.8	-16.2	1.6	36.2	QP	Ver	100.0	313.0

**Test Result: Pass**



[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]


Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC 202107-A25
EUT: Tablet PC	Test Engineer: Charlie
M/N: T802	Temperature: 25°C
S/N:	Humidity: 45%RH
Test Mode: BT mode	Test Voltage: AC 230V/50Hz
Note:	Test Data: 2021-07-27 15:45:41



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	46.975MHz	40.0	24.4	-15.6	0.5	23.9	QP	Hor	100.0	207.0
2*	138.761MHz	43.5	24.2	-19.3	0.6	23.6	QP	Hor	100.0	0.0
3*	272.985MHz	46.0	24.2	-21.8	0.9	23.3	QP	Hor	100.0	116.0
4*	383.201MHz	46.0	31.6	-14.4	4.9	26.7	QP	Hor	100.0	282.0
5*	642.555MHz	46.0	33.3	-12.7	1.8	31.5	QP	Hor	100.0	129.0
6*	957.684MHz	46.0	38.0	-8.0	2.3	35.7	QP	Hor	100.0	0.0

**Test Result: Pass**

[TestMode: TX lowest channel]; [Polarity: Horizontal]



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-L		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4804.000	43.60	3.71	47.31	74.00	-26.69	peak		
2		7206.000	41.41	5.96	47.37	74.00	-26.63	peak		
3	*	9608.000	40.27	9.29	49.56	74.00	-24.44	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX lowest channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-L		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4804.000	49.31	3.71	53.02	74.00	-20.98	peak		
2		7206.000	41.85	5.96	47.81	74.00	-26.19	peak		
3		7206.000	41.85	5.96	47.81	74.00	-26.19	peak		
4		9608.000	40.24	9.29	49.53	74.00	-24.47	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX middle channel]; [Polarity: Horizontal]



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-M		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4882.000	42.72	3.36	46.08	74.00	-27.92	peak		
2		7323.000	41.08	6.43	47.51	74.00	-26.49	peak		
3	*	9764.000	40.56	9.63	50.19	74.00	-23.81	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX middle channel]; [Polarity: Vertical]




Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	*	4877.500	49.70	3.37	53.07	74.00	-20.93	peak	
2		7323.000	41.27	6.43	47.70	74.00	-26.30	peak	
3		9764.000	39.24	9.63	48.87	74.00	-25.13	peak	

\*:Maximum data    x:Over limit    !:over margin      <Reference Only

**Test Result: Pass**

[TestMode: TX highest channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-H		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4960.000	42.07	3.75	45.82	74.00	-28.18	peak		
2		7440.000	41.04	6.86	47.90	74.00	-26.10	peak		
3	*	9920.000	39.18	10.16	49.34	74.00	-24.66	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX highest channel]; [Polarity: Horizontal]



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4960.000	42.41	3.75	46.16	74.00	-27.84	peak		
2		7440.000	42.11	6.86	48.97	74.00	-25.03	peak		
3	*	9920.000	40.56	10.16	50.72	74.00	-23.28	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

## 20 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.10.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%


### 20.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



## 20.2 BLOCK DIAGRAM OF TEST SETUP



## 20.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1:  $Level = Read\ Level + Cable\ Loss + Antenna\ Factor - Preamp\ Factor$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

### 20.4 TEST DATA

[TestMode: TX lowest channel]; [Polarity: Horizontal]



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-L		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	45.97	-4.61	41.36	74.00	-32.64	peak		
2	*	2390.000	46.68	-4.27	42.41	74.00	-31.59	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX lowest channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-L		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	46.47	-4.61	41.86	74.00	-32.14	peak		
2	*	2390.000	49.07	-4.27	44.80	74.00	-29.20	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX highest channel]; [Polarity: Horizontal]



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-H		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	57.54	-3.84	53.70	74.00	-20.30	peak		
2	*	2483.500	41.51	-3.84	37.67	54.00	-16.33	AVG		
3		2500.000	44.94	-3.78	41.16	74.00	-32.84	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX highest channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Tablet PC	Distance:	
M/N: T802		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	62.21	-3.84	58.37	74.00	-15.63	peak		
2	*	2483.500	42.42	-3.84	38.58	54.00	-15.42	AVG		
3		2500.000	47.61	-3.78	43.83	74.00	-30.17	peak		

\*:Maximum data    x:Over limit    !:over margin


<Reference Only

**Test Result: Pass**


**21 APPENDIX**
**Appendix1**
**Maximum Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	0.391	0.391	21	Pass
NVNT	1-DH1	2441	Ant1	0.534	0.534	21	Pass
NVNT	1-DH1	2480	Ant1	0.584	0.584	21	Pass
NVNT	2-DH1	2402	Ant1	2.351	2.351	21	Pass
NVNT	2-DH1	2441	Ant1	2.504	2.504	21	Pass
NVNT	2-DH1	2480	Ant1	2.477	2.477	21	Pass
NVNT	3-DH1	2402	Ant1	2.226	2.226	21	Pass
NVNT	3-DH1	2441	Ant1	3.305	3.305	21	Pass
NVNT	3-DH1	2480	Ant1	3.522	3.522	21	Pass


Power NVNT 1-DH1 2402MHz Ant1



Power NVNT 1-DH1 2441MHz Ant1




Power NVNT 1-DH1 2480MHz Ant1




Power NVNT 2-DH1 2402MHz Ant1







Power NVNT 2-DH1 2441MHz Ant1




Power NVNT 2-DH1 2480MHz Ant1




Power NVNT 3-DH1 2402MHz Ant1



Power NVNT 3-DH1 2441MHz Ant1





Power NVNT 3-DH1 2480MHz Ant1




**-20dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant1	0.864	0	Pass
NVNT	1-DH1	2441	Ant1	0.842	0	Pass
NVNT	1-DH1	2480	Ant1	0.854	0	Pass
NVNT	2-DH1	2402	Ant1	1.251	0	Pass
NVNT	2-DH1	2441	Ant1	1.264	0	Pass
NVNT	2-DH1	2480	Ant1	1.299	0	Pass
NVNT	3-DH1	2402	Ant1	1.141	0	Pass
NVNT	3-DH1	2441	Ant1	1.216	0	Pass
NVNT	3-DH1	2480	Ant1	1.223	0	Pass


**-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1**

**-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1**




-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1




-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1




-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1




-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1




-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1







**Occupied Channel Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.801218679
NVNT	1-DH1	2441	Ant1	0.8355434192
NVNT	1-DH1	2480	Ant1	0.8289567736
NVNT	2-DH1	2402	Ant1	1.153575431
NVNT	2-DH1	2441	Ant1	1.138986892
NVNT	2-DH1	2480	Ant1	1.145491449
NVNT	3-DH1	2402	Ant1	1.083158924
NVNT	3-DH1	2441	Ant1	1.144009161
NVNT	3-DH1	2480	Ant1	1.153941511


OBW NVNT 1-DH1 2402MHz Ant1




OBW NVNT 1-DH1 2441MHz Ant1




OBW NVNT 1-DH1 2480MHz Ant1




OBW NVNT 2-DH1 2402MHz Ant1




OBW NVNT 2-DH1 2441MHz Ant1




OBW NVNT 2-DH1 2480MHz Ant1




OBW NVNT 3-DH1 2402MHz Ant1



OBW NVNT 3-DH1 2441MHz Ant1




OBW NVNT 3-DH1 2480MHz Ant1




**Band Edge**

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	No-Hopping	-55.8	-20	Pass
NVNT	1-DH1	2480	Ant1	No-Hopping	-55.2	-20	Pass
NVNT	2-DH1	2402	Ant1	No-Hopping	-54.65	-20	Pass
NVNT	2-DH1	2480	Ant1	No-Hopping	-55.84	-20	Pass
NVNT	3-DH1	2402	Ant1	No-Hopping	-55.46	-20	Pass
NVNT	3-DH1	2480	Ant1	No-Hopping	-53.93	-20	Pass


Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Emission




Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Emission




Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Emission







Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Emission




Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Emission




BlueAsia


**Band Edge(Hopping)**

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	Hopping	-33.73	-20	Pass
NVNT	1-DH1	2480	Ant1	Hopping	-49.63	-20	Pass
NVNT	2-DH1	2402	Ant1	Hopping	-50.25	-20	Pass
NVNT	2-DH1	2480	Ant1	Hopping	-49.52	-20	Pass
NVNT	3-DH1	2402	Ant1	Hopping	-49.85	-20	Pass
NVNT	3-DH1	2480	Ant1	Hopping	-49.41	-20	Pass


Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Emission







Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Emission




**Conducted RF Spurious Emission**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	-44.42	-20	Pass
NVNT	1-DH1	2441	Ant1	-44.26	-20	Pass
NVNT	1-DH1	2480	Ant1	-45.08	-20	Pass
NVNT	2-DH1	2402	Ant1	-44.71	-20	Pass
NVNT	2-DH1	2441	Ant1	-45.39	-20	Pass
NVNT	2-DH1	2480	Ant1	-45.26	-20	Pass
NVNT	3-DH1	2402	Ant1	-45.2	-20	Pass
NVNT	3-DH1	2441	Ant1	-45.55	-20	Pass
NVNT	3-DH1	2480	Ant1	-45.14	-20	Pass


Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref



Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission







Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Ref




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Ref




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Ref




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Ref





Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Emission




**Carrier Frequencies Separation**

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2441.026	2441.98	0.954	0.842	Pass
NVNT	2-DH1	Ant1	2440.864	2441.8525	0.9885	0.843	Pass
NVNT	3-DH1	Ant1	2440.9375	2441.9695	1.032	0.811	Pass

**CFS NVNT 1-DH1 2441MHz Ant1**

**CFS NVNT 2-DH1 2441MHz Ant1**




CFS NVNT 3-DH1 2441MHz Ant1



**Number of Hopping Channel**


Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH1	Ant1	79	15	Pass
NVNT	2-DH1	Ant1	79	15	Pass
NVNT	3-DH1	Ant1	79	15	Pass

**Hopping No. NVNT 1-DH1 2441MHz Ant1**




**Hopping No. NVNT 2-DH1 2441MHz Ant1**






Hopping No. NVNT 3-DH1 2441MHz Ant1




**Dwell Time**

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.383	122.56	320	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.639	262.24	160	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.888	309.016	107	31600	400	Pass


Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated




Dwell NVNT 1-DH3 2441MHz Ant1 One Burst



Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated




## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

**Conducted Emissions at AC Power Line (150kHz-30MHz)**




**Radiated Spurious Emissions**






BlueAsia


### APPENDIX B: PHOTOGRAPHS OF EUT





















----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.