

 <p>Model No: ATX2410-EQ Input Power: 5VDC, 500mA FCC ID: 2AXL8-ATX2410V4P1</p> <p>This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation (FCC Title 47, Subpart C, Part 15.249). This device contains FCC ID: O7P-362.</p> <p>MAC-ID X1:Y1:X2:Y2:X3:Y3 SN: 123456-4321</p> 		 <p>Model No: ATX2410-GW Input Power: 5VDC, 500mA FCC ID: 2AXL8-ATX2410V4P1</p> <p>This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation (FCC Title 47, Subpart C, Part 15.249). This device contains FCC ID: O7P-362.</p> <p>MAC-ID X1:Y1:X2:Y2:X3:Y3 SN: 123456-4321</p> 
 <p>Model No: ATX2410-EQ Input Power: 5VDC, 500mA FCC ID: 2AXL8-ATX2410V4P1</p> <p>This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation (FCC Title 47, Subpart C, Part 15.249). This device contains FCC ID: O7P-362.</p> <p>MAC-ID X1:Y1:X2:Y2:X3:Y3 SN: 123456-4321</p> 		 <p>Model No: ATX2410-GW Input Power: 5VDC, 500mA FCC ID: 2AXL8-ATX2410V4P1</p> <p>This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation (FCC Title 47, Subpart C, Part 15.249). This device contains FCC ID: O7P-362.</p> <p>MAC-ID X1:Y1:X2:Y2:X3:Y3 SN: 123456-4321</p> 

The actual labels are 2-3/8" X 1-1/4".

The contents of the QR Code are:

MN=>ATX2410-GW; MAC=>X1:Y1:X2:Y2:X3:Y3; SN=>123456-4321;

