

FCC TEST REPORT

Client Name : Suzhou EAVision Robotic Technologies Co., Ltd.

Address : Unit 1-A, No.3 Workshop, 28 Xiasheng Road, SIP
Suzhou, Jiangsu China 215000

Product Name : VD32 Remote Control

Date : Nov. 23, 2020



Shenzhen Anbotech Compliance Laboratory Limited



Contents

1. General Information.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	6
1.4. Description of Test Modes.....	6
1.5. List of channels.....	7
1.6. Description Of Test Setup.....	8
1.7. Test Equipment List.....	9
1.8. Measurement Uncertainty.....	10
1.9. Description of Test Facility.....	10
2. Summary of Test Results.....	11
3. Conducted Emission Test.....	12
3.1. Test Standard and Limit.....	12
3.2. Test Setup.....	12
3.3. Test Procedure.....	12
3.4. Test Data.....	12
4. Radiation Spurious Emission and Band Edge.....	17
4.1. Test Standard and Limit.....	17
4.2. Test Setup.....	17
4.3. Test Procedure.....	18
4.4. Test Data.....	19
5. Maximum Peak Output Power Test.....	27
5.1. Test Standard and Limit.....	27
5.2. Test Setup.....	27
5.3. Test Procedure.....	27
5.4. Test Data.....	27
6. 20DB Occupy Bandwidth Test.....	30
6.1. Test Standard.....	30
6.2. Test Setup.....	30
6.3. Test Procedure.....	30
6.4. Test Data.....	30
7. Carrier Frequency Separation Test.....	33
7.1. Test Standard and Limit.....	33
7.2. Test Setup.....	33
7.3. Test Procedure.....	33
7.4. Test Data.....	33
8. Number of Hopping Channel Test.....	36
8.1. Test Standard and Limit.....	36



8.2. Test Setup.....	36
8.3. Test Procedure.....	36
8.4. Test Data.....	36
9. Dwell Time Test.....	38
9.1. Test Standard and Limit.....	38
9.2. Test Setup.....	38
9.3. Test Procedure.....	38
9.4. Test Data.....	38
10. 100kHz Bandwidth of Frequency Band Edge Requirement.....	40
10.1. Test Standard and Limit.....	40
10.2. Test Setup.....	40
10.3. Test Procedure.....	40
10.4. Test Data.....	40
11. Antenna Requirement.....	44
11.1. Test Standard and Requirement.....	44
11.2. Antenna Connected Construction.....	44
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	45
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	45
APPENDIX III -- INTERNAL PHOTOGRAPH.....	45



TEST REPORT

Applicant : Suzhou EAVision Robotic Technologies Co., Ltd.
Manufacturer : SIYI Technology (Shenzhen) Co., Ltd.
Product Name : VD32 Remote Control
Model No. : VD32
Trade Mark : SIYI
Rating(s) : Input: DC 5V, 2A(with DC 3.7V, 8000 mAh Battery inside)

Test Standard(s) : FCC Part15 Subpart C, Section 15.247

Test Method(s) : ANSI C63.10: 2013

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of receipt

Oct. 16, 2020

Date of Test

Oct. 16~Nov. 18, 2020

Prepared by

Yilia Zhong

(Engineer / Yilia Zhong)

Reviewer

Bibo Zhang

(Supervisor / Bibo Zhang)

Approved & Authorized Signer

Kingkong Jin

(Manager / Kingkong Jin)

1. General Information

1.1. Client Information

Applicant	:	Suzhou EAVision Robotic Technologies Co., Ltd.
Address	:	Unit 1-A, No.3 Workshop, 28 Xiasheng Road, SIP Suzhou, Jiangsu China 215000
Manufacturer	:	SIYI Technology (Shenzhen) Co., Ltd.
Address	:	Room 608-610, Huaide-yinshan Mansion (beside national road 107), Fuwei Community, Fuyong Community, Baoan District, Shenzhen, China
Factory	:	SIYI Technology (Shenzhen) Co., Ltd.
Address	:	Room 608-610, Huaide-yinshan Mansion (beside national road 107), Fuwei Community, Fuyong Community, Baoan District, Shenzhen, China

1.2. Description of Device (EUT)

Product Name	:	VD32 Remote Control	
Model No.	:	VD32	
Trade Mark	:	SIYI	
Test Power Supply	:	AC 120V, 60Hz for adapter/ AC 240V, 60Hz for adapter/ DC 3.7V Battery inside	
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)	
Product Description	:	Operation Frequency:	BDR+EDR: 2402~2480MHz 2.4G: 2410~2474MHz
	:	Transfer Rate:	BDR+EDR:1/2/3 Mbits/s
	:	Number of Channel:	BDR+EDR:79 Channels 2.4G: 20 Channels
	:	Modulation Type:	BDR+EDR: GFSK, $\pi/4$ -DQPSK, 8-DPSK 2.4G: GFSK
	:	Antenna Type:	BDR+EDR: PCB Antenna 2.4G: Cylindrical Antenna
	:	Antenna Gain(Peak):	3 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2) This report is for 2.4G module.			

1.3. Auxiliary Equipment Used During Test

Adapter	M/N: A2013 Input: 100-240V-0.7A 50-60Hz Output: 3.6-5.5V 3A / 6.5-9V 2A / 9-12V 1.5A
---------	--

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

TEST MODE:

Mode 1	GFSK	CH01	TX+ Charging Mode/TX Only
Mode 2		CH10	
Mode 3		CH20	

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The data rate was set in 1Mbps for radiated emission due to the highest RF output power.




1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	2410	05	2426	09	2441	13	2453	17	2465
02	2414	06	2430	10	2444	14	2456	18	2468
03	2418	07	2434	11	2447	15	2459	19	2471
04	2422	08	2438	12	2450	16	2462	20	2474

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT built-in battery-powered, fully-charged battery use of the test battery.

1.6. Description Of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 26, 2020	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 26, 2020	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 26, 2020	1 Year
4.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 26, 2020	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 26, 2020	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	Oct. 26, 2020	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 02, 2020	2 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 02, 2020	2 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 02, 2020	2 Year
10.	Horn Antenna	A-INFO	LB-180400- KF	J211060628	Nov. 02, 2020	2 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 26, 2020	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Oct. 26, 2020	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Oct. 26, 2020	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Oct. 26, 2020	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 26, 2020	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 26, 2020	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 26, 2020	1 Year
19.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 26, 2020	1 Year
20.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 26, 2020	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotech Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(1)	Conducted Peak Output Power	PASS
15.247(a)(1)	20dB Occupied Bandwidth	PASS
15.247(a)(1)	Carrier Frequencies Separation	PASS
15.247(a)(1)	Hopping Channel Number	PASS
15.247(a)(1)	Dwell Time	PASS
15.247(d)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

During the test, pre-scan the GFSK modulation, and found Low channel(TX+Charging Mode) which is the worst case, only the worst case is recorded in the report.

Please to see the following pages.

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 24.6°C Hum.: 48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.3780	11.63	19.93	31.56	48.32	-16.76	AVG	
2	0.6140	16.93	20.01	36.94	46.00	-9.06	AVG	
3	0.6180	26.33	20.02	46.35	56.00	-9.65	QP	
4	0.8980	22.02	20.09	42.11	56.00	-13.89	QP	
5	1.3860	10.12	20.13	30.25	46.00	-15.75	AVG	
6	1.3980	21.59	20.13	41.72	56.00	-14.28	QP	
7	1.7180	8.90	20.13	29.03	46.00	-16.97	AVG	
8	1.7260	21.34	20.13	41.47	56.00	-14.53	QP	
9	2.7260	9.85	20.15	30.00	46.00	-16.00	AVG	
10	2.9860	21.66	20.16	41.82	56.00	-14.18	QP	
11	4.2540	19.86	20.19	40.05	56.00	-15.95	QP	
12	4.2540	8.67	20.19	28.86	46.00	-17.14	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.: 24.6°C Hum.: 48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.3860	3.57	19.93	23.50	48.15	-24.65	AVG	
2	0.6220	24.28	20.02	44.30	56.00	-11.70	QP	
3	0.6900	22.68	20.04	42.72	56.00	-13.28	QP	
4	0.6900	5.55	20.04	25.59	46.00	-20.41	AVG	
5	1.1140	2.27	20.12	22.39	46.00	-23.61	AVG	
6	1.1860	21.30	20.12	41.42	56.00	-14.58	QP	
7	1.4819	20.09	20.13	40.22	56.00	-15.78	QP	
8	1.7100	21.56	20.13	41.69	56.00	-14.31	QP	
9	2.7540	21.45	20.15	41.60	56.00	-14.40	QP	
10	2.7540	2.74	20.15	22.89	46.00	-23.11	AVG	
11	4.7260	1.18	20.20	21.38	46.00	-24.62	AVG	
12	27.6820	6.88	20.27	27.15	50.00	-22.85	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 24.6°C Hum.: 48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.6100	23.44	20.01	43.45	56.00	-12.55	QP	
2	0.6580	21.25	20.03	41.28	56.00	-14.72	QP	
3	0.6900	5.25	20.04	25.29	46.00	-20.71	AVG	
4	0.8980	21.17	20.09	41.26	56.00	-14.74	QP	
5	1.1260	2.14	20.12	22.26	46.00	-23.74	AVG	
6	1.4620	21.20	20.13	41.33	56.00	-14.67	QP	
7	1.4620	1.28	20.13	21.41	46.00	-24.59	AVG	
8	1.6980	21.21	20.13	41.34	56.00	-14.66	QP	
9	2.4780	1.76	20.15	21.91	46.00	-24.09	AVG	
10	2.7460	21.60	20.15	41.75	56.00	-14.25	QP	
11	4.7619	1.30	20.20	21.50	46.00	-24.50	AVG	
12	27.2460	6.62	20.28	26.90	50.00	-23.10	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: Mode 1
 Test Specification: AC 240V, 60Hz for adapter
 Comment: Neutral Line
 Tem.: 24.6°C Hum.: 48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.3860	11.27	19.93	31.20	48.15	-16.95	AVG	
2	0.6140	17.68	20.01	37.69	46.00	-8.31	AVG	
3	0.6220	27.07	20.02	47.09	56.00	-8.91	QP	
4	1.1460	21.95	20.12	42.07	56.00	-13.93	QP	
5	1.3860	10.84	20.13	30.97	46.00	-15.03	AVG	
6	1.4900	20.88	20.13	41.01	56.00	-14.99	QP	
7	1.8180	20.56	20.14	40.70	56.00	-15.30	QP	
8	1.9460	9.53	20.14	29.67	46.00	-16.33	AVG	
9	2.7420	22.08	20.15	42.23	56.00	-13.77	QP	
10	2.7540	10.22	20.15	30.37	46.00	-15.63	AVG	
11	4.6140	20.32	20.20	40.52	56.00	-15.48	QP	
12	4.6140	9.04	20.20	29.24	46.00	-16.76	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1) The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Shenzhen Anbotech Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

Tel: (86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotech.com

Code: AB-RF-05-a

Hotline
400-003-0500
www.anbotech.com

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, pre-scan the GFSK modulation, and found Middle channel(TX Only) which is the worst case, only the worst case is recorded in the report.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.




Report No.: 18220WC00148802

FCC ID: 2AXLB-VD32T

Page 20 of 45

Test Results (30~1000MHz)


Test Mode: Mode 2
Power Source: DC 3.7V Battery inside
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 21.9°C/49%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	48.6719	29.81	-14.69	15.12	40.00	-24.88	QP	100	0	
2	91.8163	48.25	-20.37	27.88	43.50	-15.62	QP	100	360	
3	129.0146	53.04	-20.58	32.46	43.50	-11.04	QP	100	0	
4	254.7284	44.35	-18.41	25.94	46.00	-20.06	QP	100	360	
5	315.4808	34.69	-13.89	20.80	46.00	-25.20	QP	100	0	
6	768.7481	30.29	-4.83	25.46	46.00	-20.54	QP	100	360	

Test Results (30~1000MHz)

Test Mode: Mode 2
Power Source: DC 3.7V Battery inside
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 21.9°C/49%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.1347	41.16	-13.59	27.57	40.00	-12.43	QP	100	0	
2	47.9940	41.86	-14.55	27.31	40.00	-12.69	QP	100	360	
3	91.8363	53.56	-15.62	37.94	43.50	-5.56	QP	100	0	
4	130.3789	49.21	-19.42	29.79	43.50	-13.71	QP	100	360	
5	225.3080	34.25	-16.23	18.02	46.00	-27.98	QP	100	0	
6	689.5644	30.18	-6.18	24.00	46.00	-22.00	QP	100	360	



Test Results (1GHz-25GHz)

Test Mode: CH01					Test channel: Lowest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4820.00	36.60	34.04	6.58	34.09	43.13	74.00	-30.87	V
7230.00	31.36	37.11	7.73	34.50	41.70	74.00	-32.30	V
9640.00	31.05	39.31	9.23	34.79	44.80	74.00	-29.20	V
12050.00	*					74.00		V
14460.00	*					74.00		V
4820.00	40.74	34.04	6.58	34.09	47.27	74.00	-26.73	H
7230.00	33.06	37.11	7.73	34.50	43.40	74.00	-30.60	H
9640.00	30.41	39.31	9.23	34.79	44.16	74.00	-29.84	H
12050.00	*					74.00		H
14460.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4820.00	25.55	34.04	6.58	34.09	32.08	54.00	-21.92	V
7230.00	20.13	37.11	7.73	34.50	30.47	54.00	-23.53	V
9640.00	19.25	39.31	9.23	34.79	33.00	54.00	-21.00	V
12050.00	*					54.00		V
14460.00	*					54.00		V
4820.00	29.70	34.04	6.58	34.09	36.23	54.00	-17.77	H
7230.00	22.26	37.11	7.73	34.50	32.60	54.00	-21.40	H
9640.00	18.92	39.31	9.23	34.79	32.67	54.00	-21.33	H
12050.00	*					54.00		H
14460.00	*					54.00		H



Test Results (1GHz-25GHz)

Test Mode: CH10					Test channel: Middle			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4888.00	38.07	34.38	6.69	34.09	45.05	74.00	-28.95	V
7332.00	32.33	37.22	7.78	34.53	42.80	74.00	-31.20	V
9776.00	31.92	39.46	9.35	34.80	45.93	74.00	-28.07	V
12220.00	*					74.00		V
14664.00	*					74.00		V
4888.00	42.51	34.38	6.69	34.09	49.49	74.00	-24.51	H
7332.00	34.16	37.22	7.78	34.53	44.63	74.00	-29.37	H
9776.00	31.41	39.46	9.35	34.80	45.42	74.00	-28.58	H
12220.00	*					74.00		H
14664.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4888.00	26.75	34.38	6.69	34.09	33.73	54.00	-20.27	V
7332.00	20.95	37.22	7.78	34.53	31.42	54.00	-22.58	V
9776.00	19.97	39.46	9.35	34.80	33.98	54.00	-20.02	V
12220.00	*					54.00		V
14664.00	*					54.00		V
4888.00	31.07	34.38	6.69	34.09	38.05	54.00	-15.95	H
7332.00	23.17	37.22	7.78	34.53	33.64	54.00	-20.36	H
9776.00	19.77	39.46	9.35	34.80	33.78	54.00	-20.22	H
12220.00	*					54.00		H
14664.00	*					54.00		H




Test Results (1GHz-25GHz)


Test Mode: CH20					Test channel: Highest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4948.00	36.60	34.72	6.79	34.09	44.02	74.00	-29.98	V
7422.00	31.36	37.34	7.82	34.57	41.95	74.00	-32.05	V
9896.00	31.05	39.62	9.46	34.81	45.32	74.00	-28.68	V
12370.00	*					74.00		V
14844.00	*					74.00		V
4968.00	40.74	34.72	6.79	34.09	48.16	74.00	-25.84	H
7442.00	33.06	37.34	7.82	34.57	43.65	74.00	-30.35	H
9916.00	30.41	39.62	9.46	34.81	44.68	74.00	-29.32	H
12390.00	*					74.00		H
14864.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4948.00	25.61	34.72	6.79	34.09	33.03	54.00	-20.97	V
7422.00	20.17	37.34	7.82	34.57	30.76	54.00	-23.24	V
9896.00	19.29	39.62	9.46	34.81	33.56	54.00	-20.44	V
12370.00	*					54.00		V
14844.00	*					54.00		V
4968.00	29.77	34.72	6.79	34.09	37.19	54.00	-16.81	H
7442.00	22.31	37.34	7.82	34.57	32.90	54.00	-21.10	H
9916.00	18.97	39.62	9.46	34.81	33.24	54.00	-20.76	H
12390.00	*					54.00		H
14864.00	*					54.00		H

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:





Remark:


1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	125mW

5.2. Test Setup



5.3. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
2. Spectrum Setting:
 - RBW > the 20 dB bandwidth of the emission being measured
 - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 - VBW ≥ RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold

5.4. Test Data


Test Item : Max. peak output power
Test Voltage : DC 3.7V Battery inside
Test Result : PASS

Test Mode : CH Low ~ CH High
Temperature : 23.1℃
Humidity : 52%RH

Channel Frequency (MHz)	Peak Power output (dBm)	Limit (dBm)	Results	Modulation
2410	14.682	20.96	PASS	GFSK
2444	10.790	20.96	PASS	GFSK
2474	11.646	20.96	PASS	GFSK




Test Mode: GFSK---Low



Test Mode: GFSK---Middle





Test Mode: GFSK---High




6. 20DB Occupy Bandwidth Test

6.1. Test Standard

Test Standard	FCC Part15 C Section 15.247 (a)(1)
---------------	------------------------------------

6.2. Test Setup



6.3. Test Procedure

Using the following spectrum analyzer settings:

1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

6.4. Test Data

Test Item	: 20dB BW
Test Voltage	: DC 3.7V Battery inside
Test Result	: PASS

Test Mode	: CH Low ~ CH High
Temperature	: 23.1℃
Humidity	: 52%RH

Channel	Frequency(MHz)	20dB Down BW(kHz)	Modulation Mode
Low	2410	1524	GFSK
Middle	2444	1497	GFSK
High	2474	1505	GFSK



Test Mode: Low



Test Mode: Middle





Test Mode: High




7. Carrier Frequency Separation Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>25KHz or >two-thirds of the 20 dB bandwidth

7.2. Test Setup



7.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

7.4. Test Data

Test Item : Frequency Separation
 Test Voltage : DC 3.7V Battery inside
 Test Result : PASS

Test Mode : CH Low ~ CH High
 Temperature : 23.1℃
 Humidity : 52%RH

Channel	Frequency (MHz)	Separation Read Value (kHz)	Limit (kHz)
Low	2410	3996	1016.0
Middle	2444	3000	998.0
High	2474	3024	1003.3
Remark: The limit is 2/3 of 20dB BW.			



Test Mode: Low



Test Mode: Middle



Test Mode: High




8. Number of Hopping Channel Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>15 channels

8.2. Test Setup



8.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:


1. Span= the frequency band of operation
2. Set the RBW = 100kHz.
3. Set the VBW = 300kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

8.4. Test Data

Test Item	: Number of Hopping Frequency
Test Voltage	: DC 3.7V Battery inside
Test Result	: PASS

Test Mode	: CH Low ~ CH High
Temperature	: 23.1℃
Humidity	: 52%RH

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel
2402-2480MHz	20	>15



9. Dwell Time Test

9.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	0.4 sec

9.2. Test Setup



9.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span= zero span, centered on a hopping channel
2. Set the RBW = 1 MHz.
3. Set the VBW = 1 MHz.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

9.4. Test Data

Test Item : Time of Occupancy
Test Voltage : DC 3.7V Battery inside
Test Result : PASS

Test Mode : CH Low ~ CH High
Temperature : 23.1℃
Humidity : 52%RH



Channel	Burst width (ms)	Total hopping number in 8s	Total dwell time (s)	Limit (s)	Rusult
Hopping	0.470	8	0.00376	≤0.4	Pass

Note:

(1) Total dwell time=Burst width*Total hopping number

(2)There are total 20 channels were active at any time. So the test period is 0.4*20s=8s.

Test Mode: Hopping




10. 100kHz Bandwidth of Frequency Band Edge Requirement

10.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

10.2. Test Setup



10.3. Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:


1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

10.4. Test Data

Test Item	:	Band edge
Test Voltage	:	DC 3.7V Battery inside
Test Result	:	PASS

Test Mode	:	CH Low ~ CH High
Temperature	:	23.1℃
Humidity	:	52%RH


For Hopping Mode




For Non-Hopping Mode




Lowest




Highest



Test Mode: Low



Test Mode: Mid



Test Mode: High

11. Antenna Requirement

11.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna

11.2. Antenna Connected Construction

The antenna is Cylindrical Antenna which permanently attached, and the best case gain of the antenna is 3 dBi. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files for Test Setup Photos of the EUT.

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files for External Photos of the EUT.

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files for Internal Photos of the EUT.

----- End of Report -----

