

# TEST REPORT

Product Name: LED Deck Light  
FCC ID: 2AXLV-HZT-1003J  
Trademark: N/A  
Model Number: HZT-1003J  
Prepared For: ShenZhen HuaZhiTai Technology Co.,LTD  
Address: 3F, E Block, Nanlian Hengyu Science And Technology Park, No.1 Ruiji Road, Longgang District, Shenzhen City, Guangdong Province, China.  
Manufacturer: ShenZhen HuaZhiTai Technology Co.,LTD  
Address: 3F, E Block, Nanlian Hengyu Science And Technology Park, No.1 Ruiji Road, Longgang District, Shenzhen City, Guangdong Province, China.  
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.  
Address: Floor 1&2, Building A, No. 26 of Xinghe Road, Xinqiao Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong China  
Sample Received Date: Mar. 20, 2022  
Sample tested Date: Mar. 20, 2022 to Mar. 30, 2022  
Issue Date: Mar. 30, 2022  
Report No.: CTB220330029RFX  
Test Standards: FCC Part15.231  
ANSI C63.10:2013  
Test Results: PASS  
Remark: This is 433MHz radio test report.

Compiled by:



Chen Zheng

Reviewed by:



Arron Liu

Approved by:



Bin Mei / Director

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

## TABLE OF CONTENT

Test Report Declaration	Page
<b>1. VERSION</b> .....	3
<b>2. TEST SUMMARY</b> .....	4
<b>3. MEASUREMENT UNCERTAINTY</b> .....	5
<b>4. PRODUCT INFORMATION AND TEST SETUP</b> .....	6
4.1 Product Information .....	6
4.2 Test Setup Configuration .....	6
4.3 Support Equipment .....	6
4.4 Test Mode .....	7
4.5 Test Environment .....	7
<b>5. TEST FACILITY AND TEST INSTRUMENT USED</b> .....	8
5.1 Test Facility .....	8
5.2 Test Instrument Used .....	8
<b>6. AC POWER LINE CONDUCTED EMISSION</b> .....	10
6.1 Block Diagram Of Test Setup .....	10
6.2 Limit .....	10
6.3 Test procedure .....	10
6.4 Test Result .....	12
<b>7. RADIATED EMISSION</b> .....	13
7.1 Block Diagram Of Test Setup .....	13
7.2 Limit .....	13
7.3 Test procedure .....	14
7.4 Test Result .....	15
<b>8. DWELL TIME</b> .....	21
8.1 Block Diagram Of Test Setup .....	21
8.2 Limit .....	21
8.3 Test procedure .....	21
8.4 Test Result .....	22
<b>9. OCCUPIED BANDWIDTH</b> .....	23
9.1 Block Diagram Of Test Setup .....	23
9.2 Limit .....	23
9.3 Test procedure .....	23
9.4 Test Result .....	24
<b>10. ANTENNA REQUIREMENT</b> .....	25
<b>11. EUT PHOTOGRAPHS</b> .....	26
<b>12. EUT TEST SETUP PHOTOGRAPHS</b> .....	27

*(Note: N/A means not applicable)*

## 1. VERSION

Report No.	Issue Date	Description	Approved
CTB220330029RFX	Mar.29, 2022	Original	Valid

## 2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	N/A
<b>Radiated Emission</b>	47 CFR Part 15 Subpart C Section 15.209; 15.231(b)	ANSI C63.10-2013	PASS
<b>Dwell Time</b>	47 CFR Part 15 Subpart C Section 15.231 (a)	ANSI C63.10-2013	PASS
<b>Occupied Bandwidth</b>	47 CFR Part 15 Subpart C Section 15.231(c)	ANSI C63.10-2013	PASS
<b>Antenna requirement</b>	47 CFR Part 15 Subpart C Section 15.203	ANSI C63.10-2013	PASS

Note: N/A is test does not applicable since device is powered by battery.

### 3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

Item	Uncertainty
Occupancy bandwidth	$U=\pm 54.3\text{Hz}$
Conducted output power Above 1G	$U=\pm 1.0\text{dB}$
Conducted output power below 1G	$U=\pm 0.9\text{dB}$
Power Spectral Density , Conduction	$U=\pm 1.0\text{dB}$
Conduction spurious emissions	$U=\pm 2.8\text{dB}$
Out of band emission	$U=\pm 54\text{Hz}$
3m chamber Radiated spurious emission(9KHz-30MHz)	$U=\pm 4.8\text{dB}$
3m chamber Radiated spurious emission(30MHz-1GHz)	$U=\pm 4.3\text{dB}$
3m chamber Radiated spurious emission(1GHz-18GHz)	$U=\pm 4.5\text{dB}$
humidity uncertainty	$U=\pm 5.3\%$
Temperature uncertainty	$U=\pm 0.59^{\circ}\text{C}$
Supply voltages	$U=\pm 3\%$
Time	$U=\pm 5\%$

## 4. PRODUCT INFORMATION AND TEST SETUP

### 4.1 Product Information

Model(s):	HZT-1003J
Model Description:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	433.93MHz
Type of Modulation:	ASK
Antenna installation:	PCB Antenna
Antenna Gain:	1dBi
Ratings:	Battery DC 3V

### 4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

### 4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series	Note
1					

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer’s requirements and conditions for the intended use.

#### 4.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, that device using new battery during test, the worst data were recorded and reported.

Test mode
Keep the EUT in transmitting mode with modulation.

#### 4.5 Test Environment

Humidity(%):	55
Atmospheric Pressure(kPa):	101.1
Normal Voltage(DC):	3V
Normal Temperature(°C)	25

## 5. TEST FACILITY AND TEST INSTRUMENT USED

### 5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Floor 1&2, Building A, No. 26 of Xinhe Road, Xinqiao Street, Baoan District, Shenzhen China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

### 5.2 Test Instrument Used

No.	Equipment	Manufacturer	Model No.	Serial No.	Calibrated date	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	2021.09.27	2022.08.05
2	Power Sensor	Agilent	U2021XA	MY56120032	2021.09.27	2022.08.05
3	Power Sensor	Agilent	U2021XA	MY56120034	2021.09.27	2022.08.05
4	Communication test set	R&S	CMW500	108058	2021.09.27	2022.08.05
5	Spectrum Analyzer	R&S	FSP40	100550	2021.09.27	2022.08.05
6	Signal Generator	Agilent	N5181A	MY49060920	2021.09.27	2022.08.16
7	Signal Generator	Agilent	N5182A	MY47420195	2021.09.27	2022.08.05
8	Communication test set	Agilent	E5515C	MY50102567	2021.09.27	2022.08.16
9	band rejection filter	Shenxiang	MSF2400-2483.5MS-1154	20181015001	2021.09.27	2022.08.05
10	band rejection filter	Shenxiang	MSF5150-5850 MS-1155	20181015001	2021.09.27	2022.08.05
11	band rejection filter	Xingbo	XBLBQ-DZA120	190821-1-1	2021.09.27	2022.08.05
12	BT&WI-FI Automatic test software	Microwave	MTS8310	Ver. 2.0.0.0	2021.09.27	2022.08.05
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	2021.09.27	2022.08.05
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	2021.09.27	2022.08.05
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	2021.09.27	2022.08.05
16	966 chamber	C.R.T.	966 Room	966	2021.09.27	2024.08.11
17	Receiver	R&S	ESPI	100362	2021.09.27	2022.08.05
18	Amplifier	HP	8447E	2945A02747	2021.09.27	2022.08.05
19	Amplifier	Agilent	8449B	3008A01838	2021.09.27	2022.08.05




20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	869	2021.09.27	2022.08.07
21	Horn Antenna	Schwarzbeck	BBHA9120D	1911	2021.09.27	2022.08.08
22	Software	Fala	EZ-EMC	FA-03A2 RE	2021.09.27	2022.08.05
23	3-Loop Antenna	Daze	ZN30401	17014	2021.09.27	2022.08.05
24	loop antenna	ZHINAN	ZN30900A	/	2021.09.27	2022.08.05
25	Horn antenna	A/H/System	SAS-574	588	2021.09.27	2022.08.05
26	Amplifier	AEROFLEX	/	S/N/ 097	2021.09.27	2022.08.05

### Radiated emission

No.	Equipment	Manufacturer	Model No.	Serial No.	Calibrated date	Calibrated until
1	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	1911	2021.09.27	2022.08.05
2	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	869	2021.09.27	2022.08.05
3	Amplifier	Agilent	8449B	3008A01838	2021.09.27	2022.08.05
4	Amplifier	HP	8447E	2945A02747	2021.09.27	2022.08.05
5	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESPI7	100362	2021.09.27	2022.08.05
6	Coaxial cable	ETS	RFC-SNS-100-NMS-80 NI	/	2021.09.27	2022.08.05
7	Coaxial cable	ETS	RFC-SNS-100-NMS-20 NI	/	2021.09.27	2022.08.05
8	Coaxial cable	ETS	RFC-SNS-100-SMS-20 NI	/	2021.09.27	2022.08.05
9	Coaxial cable	ETS	RFC-NNS-100-NMS-300 NI	/	2021.09.27	2022.08.05
10	Communication test set	Agilent	E5515C	MY50102567	2021.09.27	2022.08.05
11	Communication test set	R&S	CMW500	108058	2021.09.27	2022.08.05
12	EZ-EMC	Frad	EMC-con3A1.1	/	/	/

## 6. AC POWER LINE CONDUCTED EMISSION

### 6.1 Block Diagram Of Test Setup



### 6.2 Limit

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreasing linearly with the logarithm of the frequency

### 6.3 Test procedure

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50 $\Omega$ /50 $\mu$ H + 5 $\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference

plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
- 6) All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
- 7) If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.

## 6.4 Test Result

N/A

NOTE: This EUT is powered by the battery only, this test item is not applicable

## 7. RADIATED EMISSION

### 7.1 Block Diagram Of Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1GHz

### 7.2 Limit

Spurious Emissions:

Frequency	Field strength (dB $\mu$ V/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	$20\log 2400/F$ (kHz) + 80	-	3
0.490MHz-1.705MHz	$20\log 24000/F$ (kHz) + 40	-	3
1.705MHz-30MHz	$20\log 30$ + 40	-	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

**Field Strength of Fundamental Limit:**

Fundamental and harmonics emission limits Frequency(MHz)	Field strength of Fundamental((microvolts/meter)	Field strength of spurious emissions(microvolts/meter)
40.66-40.70	2280	225
70-130	1250	125
130-174	1250 to 3750**	125 to 375**
174-260	3750	375
260-470	3750 to 12500**	375 to 1250**
Above 470	12500	1250

\*\* linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz,  $\mu\text{V}/\text{m}$  at 3 meters =  $56.81818(F) - 6136.3636$ ; for the band 260-470 MHz,  $\mu\text{V}/\text{m}$  at 3 meters =  $41.6667(F) - 7083.3333$ . The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

Frequency	Limit (dB $\mu\text{V}/\text{m}$ @3m)	Remark
433.93MHz	80.8	Average Value
	100.8	Peak Value

### 7.3 Test procedure

**Below 1GHz test procedure as below:**

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**Above 1GHz test procedure as below:**

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter( Above 18GHz the distance is 1 meter and table is 1.5 meter).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel
- Repeat above procedures until all frequencies measured was complete.

Receiver set:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30KHz	Quasi-peak


30MHz-1GHz	Quasi-peak	100 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Remark: By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, and test data recorded in this report.

## 7.4 Test Result

### 7.4.1 Calculation of average factor

The output field strengths of specification in accordance with the FCC rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector. The duty cycle is measured in 100 ms or the repetition cycle period, whichever is a shorter time frame. The duty cycle is measured by placing the spectrum analyzer to set zero span at 100kHz resolution bandwidth.



<p><b>Pulse</b></p>	<p>Agilent Spectrum Analyzer - Sweep SA          11:01:19 AM Mar 29, 2022          Sweep Time 45.00 ms          PNO: Wide IFGain:Low Trig: Free Run Atten: 16 dB          Avg Type: Log-Pwr          Ref Offset 0.5 dB          Ref 5.00 dBm          10 dB/div Log          Center 433.925000 MHz Res BW 100 kHz #VBW 100 kHz Span 0 Hz Sweep 45.00 ms (1001 pts)          Marker 1 Δ 296.000 μs ΔMkr1 296.0 μs 0.72 dB</p>
<p><b>On-time1</b></p>	<p>Agilent Spectrum Analyzer - Sweep SA          11:14:00 AM Mar 29, 2022          Marker 1 Δ 296.000 μs          PNO: Wide IFGain:Low Trig: Free Run Atten: 16 dB          Avg Type: Log-Pwr          Ref Offset 0.5 dB          Ref 5.00 dBm          10 dB/div Log          Center 433.925000 MHz Res BW 100 kHz #VBW 100 kHz Span 0 Hz Sweep 8.000 ms (1001 pts)          ΔMkr1 296.0 μs 0.72 dB</p>
<p><b>On-time2</b></p>	<p>Agilent Spectrum Analyzer - Sweep SA          11:13:41 AM Mar 29, 2022          Marker 1 Δ 1.000000 ms          PNO: Wide IFGain:Low Trig: Free Run Atten: 16 dB          Avg Type: Log-Pwr          Ref Offset 0.5 dB          Ref 5.00 dBm          10 dB/div Log          Center 433.925000 MHz Res BW 100 kHz #VBW 100 kHz Span 0 Hz Sweep 8.000 ms (1001 pts)          ΔMkr1 1.000 ms 1.83 dB</p>



<b>Average factor:</b>	
Calculate Formula:	Average value=Peak value + PDCF
	PDCF=20 log(Duty cycle)
	Duty cycle = T on time / T period
Calculated average factor:	Ton time = 0.296×12+1.0×13=16.552(ms) T period=41.40(ms)
	PDCF = 20 log(16.552/41.40)=-7.96dB

## 7.4.2 Radiated Spurious Emission

### Frequency Range (9 kHz-30MHz)


Frequency (MHz)	Level@3m (dB $\mu$ V/m)	Limit@3m (dB $\mu$ V/m)
--	--	--
--	--	--
--	--	--
--	--	--

**Note:** 1. Emission Level=Reading+ Cable loss-Antenna factor-Amp factor

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement


**About 30MHz-1GHz Test Results:**

Antenna polarity: H



Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
30.0000	41.38	-7.54	33.84	40	-6.16	QP
34.5173	33.92	-6.58	27.34	40	-12.66	QP
85.1486	37.69	-9.75	27.94	40	-12.06	QP
96.2672	46.10	-9.05	37.05	43.5	-6.45	QP
141.5777	32.92	-5.45	27.47	43.5	-16.03	QP
434.0687	74.18	-0.85	73.33	100.8	-27.47	Peak
869.1369	41.91	6.15	48.06	80.8	-32.74	Peak
948.7610	32.42	5.91	38.33	46.00	-7.67	QP

Antenna polarity: V



Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
42.6000	27.62	-5.37	22.25	40	-17.75	QP
57.3923	28.19	-6.03	22.16	40	-17.84	QP
95.4270	31.44	-9.14	22.30	43.5	-21.20	QP
157.2829	27.38	-5.55	21.83	43.5	-21.67	QP
434.0687	74.72	-0.85	73.87	100.8	-26.93	Peak
628.3745	27.19	2.97	30.16	46	-15.84	QP
869.1369	38.82	6.15	44.97	80.8	-35.83	Peak
948.7610	27.80	5.91	33.71	46	-12.29	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

**For average Emission**

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
433.93	73.33	-7.96	65.37	80.8	-15.43	Horizontal
867.85	48.06	-7.96	40.10	60.8	-20.70	Horizontal
433.93	73.87	-7.96	65.91	80.8	-14.89	Vertical
867.85	44.97	-7.96	37.01	60.8	-23.79	Vertical

Notes: Average emission Level = Peak Level + Duty cycle factor

**Above 1GHz Test Results**


Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit		Margin dB		Polarization
				PK	AV	PK	AV	
1301.71	51.06	-7.96	43.10	74	54	-22.94	-10.90	Vertical
1735.26	48.84	-7.96	40.88	80.8	60.8	-31.96	-19.92	Vertical
2603.56	44.12	-7.96	36.16	80.8	60.8	-36.68	-24.64	Vertical
3037.43	40.01	-7.96	32.05	80.8	60.8	-40.79	-28.75	Vertical
3471.35	40.81	-7.96	32.85	80.8	60.8	-39.99	-27.95	Vertical
3905.24	40.10	-7.96	32.14	74	54	-33.90	-21.86	Vertical
1301.71	49.80	-7.96	41.84	74	54	-24.20	-12.16	Horizontal
1735.26	46.83	-7.96	38.87	80.8	60.8	-33.97	-21.93	Horizontal
2603.56	42.93	-7.96	34.97	80.8	60.8	-37.87	-25.83	Horizontal
3037.43	40.44	-7.96	32.48	80.8	60.8	-40.36	-28.32	Horizontal
3471.35	41.84	-7.96	33.88	80.8	60.8	-38.96	-26.92	Horizontal
3905.24	41.27	-7.96	33.31	74	54	-32.73	-20.69	Horizontal

Notes: Average emission Level = Peak Level + Duty cycle factor

Remark: Other emissions for frequency 1GHz~25GHz are attenuated 20dB below the limit, so it does not record in report.

## 8. DWELL TIME

### 8.1 Block Diagram Of Test Setup



### 8.2 Limit

According to FCC 15.231(a) requirement:

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.


### 8.3 Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

### 8.4 Test Result


#### DWELL TIME

Transmitting time(S)	Limit (S)	Results
1.110	≤5	Pass



## 9. OCCUPIED BANDWIDTH

### 9.1 Block Diagram Of Test Setup



### 9.2 Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.


$$\text{B.W (20dBc) Limit} = 0.25\% * f(\text{MHz}) = 0.25\% * 433.925\text{MHz} = 1.0848\text{MHz}$$

### 9.3 Test procedure

1. Set RBW = 3KHz.
2. Set the video bandwidth (VBW)  $\geq$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

### 9.4 Test Result

20dB bandwidth (kHz)	Limit (MHz)	Results
18.42	1.0848	Pass





## 10. ANTENNA REQUIREMENT

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**EUT Antenna:**

The antenna is PCB Antenna and no consideration of replacement. The best case gain of the antenna is 1dBi.

# 11. EUT PHOTOGRAPHS

## External Photos EUT Photo 1



## EUT Photo 2



## 12. EUT TEST SETUP PHOTOGRAPHS

Radiated Emission

Below 1GHz



Above 1GHz



\*\*\*\*\* END OF REPORT \*\*\*\*\*

