



MPE ESTIMATION

FCC ID: 2AXMF-ATT

1, Per FCC Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices, the limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

Mode	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
2.4G WIFI	2462	14.41	14±1(15)	31.62	3.16	2.07	0.01302
BLE	2480	2.82	2±1(3)	2.00	3.18	2.08	0.00083

$$Pd = \frac{Pout * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2401170385-1E/2E**, antenna gain=3.16dBi(2.4G WIFI), 3.18dBi(BLE)

2.4G WIFI and BLE cannot supported Simultaneous transmitter

When the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01302 mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----