

**FCC ID: 2AXP2-GK27**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.402	-5.7	0.27	-5 $\pm$ 1	-4	0.40	<5	0.12340	3.00	YES
	2.440	-5.74	0.27	-5 $\pm$ 1	-4	0.40	<5	0.12437	3.00	YES
	2.480	-6.28	0.24	-6 $\pm$ 1	-5	0.32	<5	0.09960	3.00	YES
BLE(2M)	2.402	-5.68	0.27	-5 $\pm$ 1	-4	0.40	<5	0.12340	3.00	YES
	2.440	-5.72	0.27	-5 $\pm$ 1	-4	0.40	<5	0.12437	3.00	YES
	2.480	-6.27	0.24	-6 $\pm$ 1	-5	0.32	<5	0.09960	3.00	YES

SRD 2.4G

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-1.76	0.67	-2 $\pm$ 1	-1	0.79	<5	0.24622	3.00	YES
	2.446	-2.45	0.57	-2 $\pm$ 1	-1	0.79	<5	0.24846	3.00	YES
	2.479	-3.13	0.49	-3 $\pm$ 1	-2	0.63	<5	0.19869	3.00	YES

Note: This product does not support the requirements under 2.4G multiple sources.

**Conclusion:**

For the max result :  $0.24846 \leq 3.0$  for 1g SAR, SAR is not required.

*Alex Li*

**Signature:**

**Date:** 6/18/2024

**NAME AND TITLE** (Please print or type): Alex li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.