

FCC ID: 2AXP2-IW22

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

SRD 2.4G:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK(1M)	2.405	-3.89	0.41	-4±1	-3	0.50	<5	0.15545	3.00	YES
	2.451	-5.55	0.28	-5±1	-4	0.40	<5	0.12465	3.00	YES
	2.476	-4.71	0.34	-4±1	-3	0.50	<5	0.15773	3.00	YES
GFSK(2M)	2.405	-3.87	0.41	-4±1	-3	0.50	<5	0.15545	3.00	YES
	2.451	-5.47	0.28	-5±1	-4	0.40	<5	0.12465	3.00	YES
	2.476	-4.7	0.34	-4±1	-3	0.50	<5	0.15773	3.00	YES

BLE:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.402	-4.08	0.39	-4±1	-3	0.50	<5	0.15535	3.00	YES
	2.44	-4.1	0.39	-4±1	-3	0.50	<5	0.15658	3.00	YES
	2.480	-4.95	0.32	-4±1	-3	0.50	<5	0.15785	3.00	YES
BLE(2M)	2.402	-4.15	0.38	-4±1	-3	0.50	<5	0.15535	3.00	YES
	2.44	-4.02	0.40	-4±1	-3	0.50	<5	0.15658	3.00	YES
	2.480	-4.92	0.32	-4±1	-3	0.50	<5	0.15785	3.00	YES

Conclusion:

For the max result : $0.15785 \leq 3.0$ for 1g SAR, SAR is not required.



Signature:

Date: 12/5/2022

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao’an District, Shenzhen P.R. China.