



RF Exposure Evaluation

FCC ID: 2AXQX-4001360

1. Client Information

Applicant	:	Marpac, LLC
Address	:	2015 Capital Drive, Wilmington, NC 28405
Manufacturer	:	Shen zhen Hi-FiD Electronics Tech Co., Ltd
Address	:	4F~ 5F B7 & 3F B17, Hengfeng Industrial Town, Zhoushi Road, Bao'an District, Shenzhen City, China. 518126.

2. General Description of EUT

EUT Name	:	Hushh Dreamseeker, Hushh+	
Model(s)	:	4001360	
Product Description	:	Operation Frequency:	Bluetooth 5.0:2402MHz~2480MHz
	:	Number of Channel:	Bluetooth (BLE):40 channels Bluetooth (BDR+EDR): 79 channels
	:	Antenna Gain:	0.5dBi Ceramic Antenna
	:	Modulation Type:	GFSK π/4-DQPSK 8-DPSK
	:	Bit Rate of Transmitter:	1/2/3Mbps
Power Rating	:	Input: 5V ⁺ , 1A DC 3.7V by 1800mAh Li-ion battery	
Software Version	:	----	
Hardware Version	:	----	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.

Note: More test information about the EUT please refer the RF Test Report.

The RF Exposure Evaluation for FCC:

SAR Test Exclusion Calculations

FCC: According to 447498 D04 Interim General RF Exposure Guidance v01.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

1. Calculation:

Test separation: 5mm					
Bluetooth (GFSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P _{th} (mW)
2402	-4.839	-5±1	-4	0.398	3
2441	-5.275	-5±1	-4	0.398	3
2480	-6.074	-6±1	-5	0.316	3
Bluetooth (π/4-DQPSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P _{th} (mW)
2402	-3.9	-4±1	-3	0.501	3
2441	-4.42	-4±1	-3	0.501	3
2480	-5.261	-5±1	-4	0.398	3
Bluetooth (8-DPSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P _{th} (mW)
2402	-3.297	-3±1	-2	0.631	3
2441	-3.788	-4±1	-3	0.501	3
2480	-4.691	-5±1	-4	0.398	3
Bluetooth LE 1Mbps					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P _{th} (mW)
2402	-4.92	-5±1	-4	0.398	3
2440	-5.593	-6±1	-5	0.316	3
2480	-6.179	-6±1	-5	0.316	3

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D04, No SAR is required.

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----