

FCC SAR Exclusion Report

Product name : Desksense
Applicant : Head Electronics B.V.
FCC ID : 2AXRUP190201

Test report No. : 200801041 005 FCC RF exposure V2.0

Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

Telefication is a registered Conformity Assessment body (CA B) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

Test Site	Telefication BV
Test Site location	Wilmersdorf 50 7327 AC Apeldoorn The Netherlands Tel. +3188998 3393

Revision History

Version	Date	Remarks	By
V0.50	07-12-2020	First draft version	RT
V1.00	23-02-2021	Initial release version	PvW
V2.0	08-04-2021	Updated FCC ID	PvW

Table of Contents

Revision History	2
1 General Description	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Tested Equipment Under Test (EUT)	4
1.4 SAR Measurement Evaluation	5
1.4.1 Maximum Output Power	5
1.4.2 SAR Testing Exclusions	5
1.5 Summary	5

1 General Description

1.1 Applicant

Client name:	Head Electronics B.V
Address:	Ambachtsweg 17 Katwijk NETHERLANDS
Zip code:	2222 AH
Telephone:	+31 (0)6 25237695
E-mail:	t.klijn@head.nl
Contact name:	Tom Klijn

1.2 Manufacturer

Manufacturer name:	Head Electronics B.V.
Address:	Ambachtsweg 17 Katwijk NETHERLANDS
Zip code:	2222 AH
Telephone:	+31 (0)6 25237695
E-mail:	t.klijn@head.nl
Contact name:	Tom Klijn

1.3 Tested Equipment Under Test (EUT)

Product name:	Desksense
Brand name:	Head Electronics B.V.
Product type:	Wireless battery powered desk occupancy sensor
FCC ID:	2AXRUP190201
IC ID:	26960-DESKSENSE
Model:	P190201-1900001
Software version:	V2.0
Hardware version:	V07
Date of receipt	10-11-2020
Tests started:	23-11-2020

1.4 SAR Measurement Evaluation

1.4.1 Maximum Output Power

The maximum radiated power including tune-up tolerance is shown as below.

Mode	Max output power
LoRa	12.92 dBm*

* from Telefication report 200801041 004.

1.4.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

- For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(mW)}}{\text{Min. Test Separation Distance}_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(MHz)}}{150} \right) \right]_{(mW)}$$

- For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(mW)}$$

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
LoRa	12.92	19.588	10	1.86	No

Note:

- When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 , the SAR testing exclusion is applied.
- When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

1.5 Summary

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.