

# MPE REPORT

FCC ID: 2AXU9-DP100

Date of issue: Nov. 20, 2020


Report number:	MTi20092113-4E3
Sample description:	AI Disinfection Terminal
Model(s):	DP100, DP-200, DP-300, DP-400, DP-500
Applicant:	DIPENG APPLIANCES(GUANGZHOU)CO.,LTD.
Address:	6# Chashu Stree, Shilongken Liaobu Town, Dongguan City, Guangdong.P.R.China
Date of test:	Oct. 09, 2020 to Nov. 09, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.



<b>TEST RESULT CERTIFICATION</b>	
Applicant's name:	DIPENG APPLIANCES(GUANGZHOU)CO.,LTD.
Address:	6# Chashu Stree, Shilongken Liaobu Town, Dongguan City, Guangdong.P.R.China
Manufacture's name:	DIPENG APPLIANCES(GUANGZHOU)CO.,LTD.
Address:	6# Chashu Stree, Shilongken Liaobu Town, Dongguan City, Guangdong.P.R.China
Product name:	AI Disinfection Terminal
Trademark:	
Model and/or type reference:	DP100
Serial model:	DP-200, DP-300, DP-400, DP-500
RF exposure procedures:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


Tested by:



Danny Xu

Nov. 09, 2020

Reviewed by:



Leo Su

Nov. 20, 2020

Approved by:



Tom Xue

Nov. 20, 2020



## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*300/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1415926

$R$  = distance between observation point and center of the radiator in cm (20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

### WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

802.11n HT40: 2422-2452MHz,

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: FPC Antenna;

WIFI antenna gain: 3dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(3/10)}=2$

Channel Freq. (MHz)	modulation	conduct ed power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
		Ant A	Ant A	(dB m)	(mW)	Numeric		
2412	802.11b	15.28	15±1	16	39.810717	2	0.01584	1
2437		15.31	15±1	16	39.810717	2	0.01584	1
2462		15.26	15±1	16	39.810717	2	0.01584	1
2412	802.11g	10.97	12±1.5	13.5	22.387211	2	0.00891	1
2437		13.16	12±1.5	13.5	22.387211	2	0.00891	1
2462		11.27	12±1.5	13.5	22.387211	2	0.00891	1
2412	802.11n H20	10.95	12±2	14	25.118864	2	0.00999	1
2437		13.16	12±2	14	25.118864	2	0.00999	1
2462		11.41	12±2	14	25.118864	2	0.00999	1
2422	802.11n H40	12.90	13±1	14	25.118864	2	0.00999	1
2437		12.75	13±1	14	25.118864	2	0.00999	1
2452		12.92	13±1	14	25.118864	2	0.00999	1

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
		Ant A	Ant A	(dBm)	(mW)	Numeric		
2402	GFSK	-0.902	-1±1	0	1	2	0.0004	1
2440		-0.456	-1±1	0	1	2	0.0004	1
2480		-0.392	-1±1	0	1	2	0.0004	1

### Conclusion:

For the max result (WIFI+BLE):  $0.01584+0.0004=0.01386 \leq 1.0$  for 1g SAR, No SAR is required.



**----END OF REPORT----**