

## Maximum Permissible Exposure Report

### Product Information

EUT : NucBox3  
 Model Number : KB3  
 Model Declaration : N/A  
 Test Model : KB3  
 Power Supply : DC 12V by adapter  
 Hardware version : MX-GB08\_V300  
 Software version : Windows 11  
 Sample ID : TZ211102749-2#&TZ211102749-4#

### Bluetooth

Bluetooth Version : V4.2  
 Channel Number : 79 Channels for Bluetooth BR/EDR(DSS)  
 : 40 Channels for BLE (DTS)  
 Modulation Technology : GFSK,  $\pi/4$ -DQPSK, 8-DPSK for Bluetooth BR/EDR (DSS)  
 : GFSK for BLE (DTS)  
 Data Rates : Bluetooth BR/EDR (DSS): 1/2/3Mbps  
 : BLE (DTS): 1Mbps  
 Antenna Type And Gain : Internal Antenna 1:  
 : 4.42dBi

### WiFi

WLAN : Supported IEEE 802.11a/b/g/n/ac  
 IEEE 802.11b:2412-2462MHz  
 IEEE 802.11g:2412-2462MHz  
 IEEE 802.11n HT20:2412-2462MHz / 5180-5240MHz  
 WLAN FCC Operation Frequency : IEEE 802.11n HT40: 2422-2452MHz / 5190-5230MHz  
 : IEEE 802.11a: 5180-5240MHz  
 IEEE 802.11ac VHT20: 5180-5240MHz  
 IEEE 802.11ac VHT40: 5190-5230MHz  
 IEEE 802.11ac VHT80: 5210MHz  
 WLAN Modulation Technology : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)  
 : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)  
 : IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)  
 : IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)  
 : IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)  
 Antenna Type And Gain : Antenna 1:  
 : 4.42dBi(Max.), for TX/RX (WLAN 2.4G Band)  
 : 2.74dBi(Max.), for TX/RX (WLAN 5.2G Band)  
 : Antenna 2:  
 : 4.18dBi(Max.), for TX/RX (WLAN 2.4G Band)  
 : 4.99dBi(Max.), for TX/RX (WLAN 5.2G Band)  
 : 802.11n/ac support 2T2R.[Antenna 1 and Antenna 2]

*Note: Antenna position refer to EUT Photos.*

## 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 3. Limit

#### 3.1 Refer evaluation method

ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

#### 3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 5. Antenna Information

This Product can only use antennas certificated as follows provided by manufacturer;

Antenna Gain and type refer to Product information

## 6. Conducted Power

2.4G Band:

Bluetooth(BDR+EDR)

TestMode	Antenna	Channel	Result[dBm]
DH5	Ant1	2402	4.65
		2441	4.9
		2480	4.13
2DH5	Ant1	2402	1.02
		2441	1.47
		2480	0.58
3DH5	Ant1	2402	1.23
		2441	1.6
		2480	0.89

Bluetooth(BLE)

TestMode	Antenna	Channel	Result[dBm]
BLE_1M	Ant1	2402	3.07
		2440	3.43
		2480	2.57

WiFi 2.4GHz Band

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	11.43	≤30	PASS
	Ant2	2412	12.27	≤30	PASS
	Ant1	2437	13.38	≤30	PASS
	Ant2	2437	11.92	≤30	PASS
	Ant1	2462	13.15	≤30	PASS
	Ant2	2462	12.80	≤30	PASS
11G	Ant1	2412	10.31	≤30	PASS
	Ant2	2412	10.38	≤30	PASS
	Ant1	2437	10.32	≤30	PASS
	Ant2	2437	10.72	≤30	PASS
	Ant1	2462	8.91	≤30	PASS
	Ant2	2462	11.12	≤30	PASS
11N20MIMO	Ant1	2412	6.24	≤30	PASS
	Ant2	2412	6.39	≤30	PASS
	total	2412	9.3	≤30	PASS
	Ant1	2437	7.70	≤30	PASS
	Ant2	2437	4.48	≤30	PASS
	total	2437	9.4	≤30	PASS
	Ant1	2462	8.97	≤30	PASS
	Ant2	2462	5.34	≤30	PASS
11N40MIMO	total	2462	10.5	≤30	PASS
	Ant1	2422	5.15	≤30	PASS
	Ant2	2422	4.68	≤30	PASS
	total	2422	7.9	≤30	PASS
	Ant1	2437	6.14	≤30	PASS
	Ant2	2437	4.79	≤30	PASS
	total	2437	8.5	≤30	PASS
	Ant1	2452	6.41	≤30	PASS
	Ant2	2452	4.76	≤30	PASS
	total	2452	8.7	≤30	PASS

5G Band  
UNII-1 Band

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11A	Ant1	5180	8.77	≤23.98	PASS
	Ant2	5180	8.09	≤23.98	PASS
	Ant1	5200	9.04	≤23.98	PASS
	Ant2	5200	8.36	≤23.98	PASS
	Ant1	5240	9.56	≤23.98	PASS
	Ant2	5240	8.75	≤23.98	PASS
11N20MIMO	Ant1	5180	4.28	≤23.98	PASS
	Ant2	5180	8.27	≤23.98	PASS
	total	5180	11.7	≤22.82	PASS
	Ant1	5200	3.90	≤23.98	PASS
	Ant2	5200	3.44	≤23.98	PASS
	total	5200	6.7	≤22.82	PASS
	Ant1	5240	4.67	≤23.98	PASS
	Ant2	5240	3.94	≤23.98	PASS
11N40MIMO	total	5240	7.3	≤22.82	PASS
	Ant1	5190	2.89	≤23.98	PASS
	Ant2	5190	3.44	≤23.98	PASS
	total	5190	6.2	≤22.82	PASS
	Ant1	5230	4.10	≤23.98	PASS
	Ant2	5230	4.12	≤23.98	PASS
11AC20MIMO	total	5230	7.1	≤22.82	PASS
	Ant1	5180	3.75	≤23.98	PASS
	Ant2	5180	3.79	≤23.98	PASS
	total	5180	6.8	≤23.98	PASS
	Ant1	5200	3.82	≤23.98	PASS
	Ant2	5200	3.59	≤23.98	PASS
	total	5200	6.7	≤22.82	PASS
	Ant1	5240	4.78	≤23.98	PASS
Ant2	5240	4.10	≤23.98	PASS	
11AC40MIMO	total	5240	7.5	≤22.82	PASS
	Ant1	5190	3.44	≤23.98	PASS
	Ant2	5190	3.68	≤23.98	PASS
	total	5190	6.6	≤22.82	PASS
	Ant1	5230	4.17	≤23.98	PASS
	Ant2	5230	4.46	≤23.98	PASS
11AC80MIMO	total	5230	7.3	≤23.98	PASS
	Ant1	5210	1.84	≤23.98	PASS
	Ant2	5210	4.29	≤23.98	PASS
	total	5210	6.2	≤22.82	PASS

## 7. Manufacturing Tolerance

### Bluetooth(BDR+EDR)

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4.0	4.0	3.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0.5	0.5	0.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0.5	1.0	0.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

### Bluetooth(BLE)

GFSK(1Mbps) (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.5	2.5	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

### WiFi 2.4GHz Band – Antenna 1

IEEE 802.11b(Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	10.5	12.5	12.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	9.5	9.5	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	5.5	7.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	4.5	5.5	5.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

### WiFi 2.4GHz Band – Antenna 2

IEEE 802.11b (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11.5	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	9.5	10.0	10.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	5.5	3.5	4.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	4.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

## UNII-1 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	8.0	8.5	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	3.5	3.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	3.0	3.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	2.0	5.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	2.5	3.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	--	--
Target (dBm)	1.0	--	--
Tolerance $\pm$ (dB)	1.0	--	--

## UNII-1 Band – Antenna 2

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	7.5	7.5	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	7.5	2.5	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	3.0	3.0	3.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	2.5	3.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	3.0	3.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	--	--
Target (dBm)	3.5	--	--
Tolerance $\pm$ (dB)	1.0	--	--

## 8. Measurement Results

### 8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Bluetooth(BDR+EDR)

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
GFSK	5.00	3.1623	4.42	2.7669	100%	0.0017	1.0000
$\pi/4$ -DQPSK	1.50	1.4125	4.42	2.7669	100%	0.0008	1.0000
8-DPSK	2.00	1.5849	4.42	2.7669	100%	0.0009	1.0000

Bluetooth(BLE)

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
GFSK	3.50	2.2387	4.42	2.7669	100%	0.0012	1.0000

WiFi 2.4GHz Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11b	13.50	22.3872	4.42	2.7669	100%	0.0123	1.0000
IEEE 802.11g	10.50	11.2202	4.42	2.7669	100%	0.0062	1.0000
IEEE 802.11n HT20	9.00	7.9433	4.42	2.7669	100%	0.0044	1.0000
IEEE 802.11n HT40	6.50	4.4668	4.42	2.7669	100%	0.0025	1.0000

WiFi 2.4GHz Band – Ant 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11b	13.00	19.9526	4.18	2.6182	100%	0.0104	1.0000
IEEE 802.11g	11.50	14.1254	4.18	2.6182	100%	0.0074	1.0000
IEEE 802.11n HT20	6.50	4.4668	4.18	2.6182	100%	0.0023	1.0000
IEEE 802.11n HT40	5.00	3.1623	4.18	2.6182	100%	0.0016	1.0000

UNII-1 Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11a	10.00	10.0000	2.74	1.8793	100%	0.0037	1.0000
IEEE 802.11n HT20	5.00	3.1623	2.74	1.8793	100%	0.0012	1.0000
IEEE 802.11ac VHT20	5.00	3.1623	2.74	1.8793	100%	0.0012	1.0000
IEEE 802.11n HT40	6.50	4.4668	2.74	1.8793	100%	0.0017	1.0000
IEEE 802.11ac VHT40	4.50	2.8184	2.74	1.8793	100%	0.0011	1.0000
IEEE 802.11ac VHT80	2.00	1.5849	2.74	1.8793	100%	0.0006	1.0000

UNII-1 Band – Ant 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11a	9.00	7.9433	4.99	3.1550	100%	0.0050	1.0000
IEEE 802.11n HT20	8.50	7.0795	4.99	3.1550	100%	0.0044	1.0000
IEEE 802.11ac VHT20	4.50	2.8184	4.99	3.1550	100%	0.0018	1.0000
IEEE 802.11n HT40	4.50	2.8184	4.99	3.1550	100%	0.0018	1.0000
IEEE 802.11ac VHT40	4.50	2.8184	4.99	3.1550	100%	0.0018	1.0000
IEEE 802.11ac VHT80	4.50	2.8184	4.99	3.1550	100%	0.0018	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;



**8.2 Simultaneous Transmission MPE**

Bluetooth + Wi-Fi

Maximum MPE(mW/cm <sup>2</sup> ) WIFI Ant.1	Maximum MPE(mW/cm <sup>2</sup> ) WIFI Ant.2	ΣMPE (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Results
0.0123	0.0104	0.0227	1.0000	PASS

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

**9. Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----