

RF Exposure Evaluation Statement

Product Name: Tablet pc

Model No.: T100, T101, T102

FCC ID: 2AXUI-T100

1.1 RF Exposure Compliance Requirement

1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

1.1.3 EUT RF Exposure

Operational Mode: 2.4GWIIIF (802.11N40 worst case)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
2422 MHz	7.12	± 1	8.12	6.49	2.02	3.0
2437 MHz	6.42	± 1	7.42	5.52	1.72	
2452 MHz	6.55	± 1	7.55	5.69	1.78	
Operational Mode: BLE						
2402 MHz	1.92	± 1	2.92	1.96	0.61	3.0
2442 MHz	1.88	± 1	2.88	1.94	0.61	
2480 MHz	1.78	± 1	2.78	1.90	0.60	
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						