



RF Exposure Evaluation Report

For TAG&Find Wireless solutions Ltd.

Equipment Under Test:

***Compact UNF RFID reader with BLE connectivity
GearEye BLE transceiver***

Model: GearEye-A4

FCC ID: 2AXUS-GRY4

***From The Standards Institution
Of Israel
Industry Division
Electronics & Telematics Laboratory
EMC Branch***



1. Applicant information

Applicant:	TAG&Find Wireless solutions Ltd.
Address:	Golda Meir 21, Haifa, 3498223, Israel.
Sample for test selected by:	The customer
The date of tests:	6, 12 August, 15 September 2020

Equipment under test information

Description of Equipment Under Test (EUT):	Compact UNF RFID reader with BLE connectivity. GearEye BLE transceiver
Model:	GearEye-A4
Software version of radio unit:	GearEye-A4-2.3.1
Hardware version:	GearEye-A4
Manufactured by:	TAG&Find Wireless solutions Ltd.

2. Test performance

Location:	SII EMC Section
Purpose of test:	To prove the safety of radiation harmfulness to the human body for our product
Test specifications:	FCC KDB 447498 D01 General RF Exposure Guidance v06

This Test Report contains 3 pages and may be used only in full.

This Test Report applies only to the specimen tested and may not be applied to other specimens of the same product.

3. Summary of test:

Using the general SAR test exclusion guidance in Section 4.3.1 of KDB 447498 D01 v06, we show the device meeting the SAR exemption.

Electronics and
Telematics Laboratory

November 2020

Name: Eng. Yuri Rozenberg
Position: Head of EMC Branch.

Name: Michael Feldman.
Position: Test engineer.



4. FCC and ISEDC Exemption Limits for Routine Evaluation

FCC SAR test exclusions per KDB 447498

KDB 447498 D01 General RF Exposure Guidance v06 Section: 4.3.1.

Standalone SAR test exclusion considerations states:

For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,}$
where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds.

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

SAR Test Exclusion Threshold

Freq. [MHz]	d [mm]	Max. power [mW]	Calculation result	Exclusion threshold @ <5 mm	SAR Exclusion applicable (Yes/No)
2440	5	6.5	2.0	7.5	Yes

Summary: SAR test exclusion threshold is $<$ 7.5 for separation distance of 5 mm. Therefore, SAR test is not required.