

FCC PART 15C

TEST REPORT

For

Fujian Nexhome Intelligent Technology Co., Ltd.

7th floor, building 1, No.9, Gaoxin Avenue Shangjie Town, Minhou County, Fuzhou, China.

FCC ID: 2AXVC-10901T98S


| | |
|--|---|
| Report Type: Original Report | Product Name: Door unit |
| Report Number: | <u>RDG201117051-00A</u> |
| Report Date: | <u>2020-12-29</u> |
| Reviewed By: | Ivan Cao Assistant Manager  |
| Test Laboratory: | Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn |

TABLE OF CONTENTS

| | |
|--|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| TEST METHODOLOGY | 3 |
| MEASUREMENT UNCERTAINTY | 4 |
| TEST FACILITY | 4 |
| DECLARATIONS..... | 4 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| JUSTIFICATION | 5 |
| EUT EXERCISE SOFTWARE | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| BLOCK DIAGRAM OF TEST SETUP | 6 |
| SUMMARY OF TEST RESULTS..... | 7 |
| FCC§15.203 - ANTENNA REQUIREMENT..... | 8 |
| APPLICABLE STANDARD | 8 |
| ANTENNA CONNECTED CONSTRUCTION | 8 |
| FCC §15.207 – AC LINE CONDUCTED EMISSION | 9 |
| EUT SETUP..... | 9 |
| EMI TEST RECEIVER SETUP..... | 9 |
| TEST EQUIPMENT LIST AND DETAILS..... | 10 |
| TEST PROCEDURE | 10 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 10 |
| TEST RESULTS SUMMARY..... | 11 |
| TEST DATA | 11 |
| FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST | 14 |
| APPLICABLE STANDARD | 14 |
| EUT SETUP..... | 15 |
| EMI TEST RECEIVER SETUP..... | 15 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 15 |
| TEST EQUIPMENT LIST AND DETAILS..... | 16 |
| TEST RESULTS SUMMARY..... | 16 |
| TEST DATA | 16 |
| FCC§15.225(E) - FREQUENCY STABILITY..... | 22 |
| APPLICABLE STANDARD | 22 |
| TEST PROCEDURE | 22 |
| TEST EQUIPMENT LIST AND DETAILS..... | 22 |
| TEST DATA | 23 |
| FCC §15.215(C) – 20 DB EMISSION BANDWIDTH..... | 24 |
| APPLICABLE STANDARD | 24 |
| TEST PROCEDURE | 24 |
| TEST EQUIPMENT LIST AND DETAILS..... | 24 |
| TEST DATA | 24 |

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

| | |
|-----------------------------|--------------------|
| EUT Name: | Door unit |
| EUT Model: | DH-T98S |
| Operation Frequency: | 13.562 MHz |
| Modulation Type: | ASK |
| Rated Input Voltage: | DC 12V from system |
| Serial Number: | RDG201117051-RF-S1 |
| EUT Received Date: | 2020.11.18 |
| EUT Received Status: | Good |

Objective

This Type approval report is prepared on behalf of *Fujian Nexhome Intelligent Technology Co., Ltd.* in accordance with Part 2, Subpart J, and Part 15, Subparts A and C of the Federal Communications Commission's rules.

The objective is to determine the compliance of the EUT with FCC rules, sec 15.203, 15.205, 15.207, 15.209, 15.215 and 15.225.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: 2AXVC-10901T98S

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| Parameter | Measurement Uncertainty |
|-----------------------------------|---|
| Occupied Channel Bandwidth | ±5 % |
| radiated Emissions | 9kHz~30MHz: 4.12dB 30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB |
| Temperature | ±1 °C |
| Humidity | ±5% |
| DC and low frequency voltages | ±0.4% |
| Duty Cycle | 1% |
| AC Power Lines Conducted Emission | 3.12 dB (150 kHz to 30 MHz) |

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a test mode

The device operates in 13.562 MHz.

EUT Exercise Software

No software used in test.

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|---------------|----------------|----------------------|
| Hytera | Adapter | HKA02412020-XG | PS2015 |
| Nexhome | Control Board | Nexhome-TCB | TCB-202011 |
| HUAWEI | Router | HG8245Q2 | 2102311RGB6RH1000053 |

Support Cable List and Details

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From | To |
|-------------------|----------------|--------------|------------|---------|---------------|
| DC Cable | No | Yes | 1.4 | Adapter | Control Board |
| RJ45 Cable | Yes | No | 10 | EUT | Laptop |
| Power Cable | Yes | No | 0.3 | EUT | Control Board |
| Control Cable | Yes | No | 0.3 | EUT | Control Board |

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|----------------------------|----------------------------|---------------|
| §15.203 | Antenna Requirement | Compliance |
| §15.207 | AC Line Conducted Emission | Compliance |
| §15.225 §15.209 §15.205 | Radiated Emission Test | Compliance |
| §15.225(e) | Frequency Stability | Compliance |
| §15.215(c) | 20 dB Emission Bandwidth | Compliance |

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.


Antenna Connected Construction

The EUT has a PCB antenna arrangement for 13.562MHz, , which was permanently attached and fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 – AC LINE CONDUCTED EMISSION

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with an AC 120V/60Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|-----------|--------------------|------------------|----------------------|
| R&S | LISN | ENV 216 | 101614 | 2020-09-12 | 2021-09-12 |
| R&S | EMI Test Receiver | ESCI | 101121 | 2020-07-07 | 2021-07-07 |
| MICRO-COAX | Coaxial Cable | C-NJNJ-50 | C-0200-01 | 2020-09-05 | 2021-09-05 |
| R&S | Test Software | EMC32 | Version 9.10.00 | N/A | N/A |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase ("hot") line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

According FCC publication number 174176, for a device with a permanent antenna operating at or below 30 MHz, the measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) perform the AC line conducted tests with the permanent antenna to determine compliance with the Section 15.207 limits outside the transmitter's fundamental emission band; (2) retest with a dummy load in lieu of the permanent antenna to determine compliance with the Section 15.207 limits within the transmitter's fundamental emission band.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.


Test Data

Environmental Conditions

| | |
|---------------------------|-------------|
| Temperature: | 21.2°C |
| Relative Humidity: | 46 % |
| ATM Pressure: | 101.8kPa |
| Tester: | Walker Chen |
| Test Date: | 2020-11-30 |

Test mode: Transmitting


AC 120V, 60 Hz, Line:



Final_Result

| Frequency (MHz) | QuasiPeak (dB µ V) | Average (dB µ V) | Limit (dB µ V) | Margin (dB) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|--------------------|------------------|----------------|-------------|-----------------|------|------------|
| 0.154557 | 51.51 | --- | 65.75 | 14.24 | 9.000 | L1 | 9.6 |
| 0.166563 | --- | 34.04 | 55.13 | 21.09 | 9.000 | L1 | 9.6 |
| 0.168233 | --- | 34.45 | 55.05 | 20.60 | 9.000 | L1 | 9.6 |
| 0.183119 | 46.22 | --- | 64.34 | 18.12 | 9.000 | L1 | 9.6 |
| 0.191526 | 45.35 | --- | 63.97 | 18.62 | 9.000 | L1 | 9.6 |
| 0.219135 | 40.92 | --- | 62.85 | 21.93 | 9.000 | L1 | 9.6 |
| 0.297058 | 36.64 | --- | 60.32 | 23.68 | 9.000 | L1 | 9.6 |
| 0.491602 | 34.48 | --- | 56.14 | 21.66 | 9.000 | L1 | 9.6 |
| 0.496531 | --- | 28.33 | 46.06 | 17.73 | 9.000 | L1 | 9.6 |
| 2.666299 | --- | 25.75 | 46.00 | 20.25 | 9.000 | L1 | 9.7 |
| 15.819507 | --- | 32.22 | 50.00 | 17.78 | 9.000 | L1 | 10.2 |
| 15.898604 | --- | 32.29 | 50.00 | 17.71 | 9.000 | L1 | 10.2 |

AC120 V, 60 Hz, Neutral:



Final Result

| Frequency (MHz) | QuasiPeak (dB µ V) | Average (dB µ V) | Limit (dB µ V) | Margin (dB) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|--------------------|------------------|----------------|-------------|-----------------|------|------------|
| 0.151504 | 50.99 | --- | 65.92 | 14.93 | 9.000 | N | 9.6 |
| 0.160848 | --- | 34.79 | 55.42 | 20.63 | 9.000 | N | 9.6 |
| 0.169919 | 48.44 | --- | 64.96 | 16.52 | 9.000 | N | 9.6 |
| 0.175956 | --- | 30.55 | 54.67 | 24.12 | 9.000 | N | 9.6 |
| 0.188682 | 45.43 | --- | 64.09 | 18.66 | 9.000 | N | 9.6 |
| 0.511614 | 34.08 | --- | 56.00 | 21.92 | 9.000 | N | 9.6 |
| 0.516743 | --- | 27.10 | 46.00 | 18.90 | 9.000 | N | 9.6 |
| 14.034840 | --- | 28.88 | 50.00 | 21.12 | 9.000 | N | 9.8 |
| 15.740803 | --- | 33.79 | 50.00 | 16.21 | 9.000 | N | 9.9 |
| 15.819507 | 38.92 | --- | 60.00 | 21.08 | 9.000 | N | 9.9 |
| 15.978097 | --- | 33.91 | 50.00 | 16.09 | 9.000 | N | 9.9 |
| 15.978097 | 39.12 | --- | 60.00 | 20.88 | 9.000 | N | 9.9 |

FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

Applicable Standard

FCC Part 15.205, 15.209, 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.


As per FCC Part 15.209

(a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|------------------------|--|--------------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100** | 3 |
| 88-216 | 150** | 3 |
| 216-960 | 200** | 3 |
| Above 960 | 500 | 3 |

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

EUT Setup



The radiated emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 9 kHz to 1 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

| Frequency Range | RBW | Video B/W | Measurement |
|-------------------|---------|-----------|-------------|
| 9 kHz – 150 kHz | 200 Hz | 1 kHz | QP |
| 150 kHz – 30 MHz | 9 kHz | 30 kHz | QP |
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz | QP |

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP/Average measurement

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corr. Ampl.}$$

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|----------------|-------------------|-----------|---------------|------------------|----------------------|
| EMCO | Passive Loop | 6512 | 9706-1206 | 2020-03-05 | 2023-03-05 |
| Sunol Sciences | Antenna | JB3 | A060611-1 | 2020-11-10 | 2023-11-10 |
| R&S | EMI Test Receiver | ESR3 | 102453 | 2020-09-12 | 2021-09-12 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0075-01 | 2020-09-05 | 2021-09-05 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0400-01 | 2020-09-05 | 2021-09-05 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-1400-01 | 2020-05-06 | 2021-05-06 |
| HP | Amplifier | 8447D | 2727A05902 | 2020-09-05 | 2021-09-05 |
| Farad | Test Software | EZ-EMC | V1.1.4.2 | N/A | N/A |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209&15.225.


Test Data

Environmental Conditions

| Test Items | Radiation Below 1GHz |
|--------------------|----------------------|
| Temperature: | 25.2°C |
| Relative Humidity: | 45 % |
| ATM Pressure: | 102.2 kPa |
| Tester: | Jalon Liu |
| Test Date: | 2020-11-26 |


Test mode: Transmitting (the EUT has been tested in X,Y,Z axis,the X axis was the worst)

1) 9 kHz~150kHz:



| Frequency (MHz) | Reading (dBμV) | Detector | Corrected (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|----------------|----------|------------------|-----------------|----------------|-------------|
| 0.0090 | -15.23 | peak | 88.61 | 73.38 | 128.52 | 55.14 |
| 0.0154 | -11.02 | peak | 84.13 | 73.11 | 123.85 | 50.74 |
| 0.0187 | -8.36 | peak | 81.39 | 73.03 | 122.17 | 49.14 |
| 0.0313 | -10.60 | peak | 76.66 | 66.06 | 117.69 | 51.63 |
| 0.0534 | -5.52 | peak | 72.96 | 67.44 | 113.05 | 45.61 |
| 0.1063 | -13.69 | peak | 66.36 | 52.67 | 107.07 | 54.40 |

150kHz~30MHz:




| Frequency (MHz) | Reading (dBμV) | Detector | Corrected (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|----------------|----------|------------------|-----------------|----------------|-------------|
| 0.1500 | 18.63 | peak | 38.53 | 57.16 | 104.08 | 46.92 |
| 1.5827 | 16.52 | peak | 18.50 | 35.02 | 63.61 | 28.59 |
| 9.3736 | 21.01 | peak | 9.52 | 30.53 | 69.54 | 39.01 |
| 13.4631 | 25.83 | peak | 9.29 | 35.12 | 69.54 | 34.42 |
| 13.7020 | 27.51 | peak | 9.30 | 36.81 | 69.54 | 32.73 |
| 29.4030 | 18.05 | peak | 8.62 | 26.67 | 69.54 | 42.87 |

30MHz-1GHz

Horizontal:


80.0 dBuV/m



| Frequency (MHz) | Reading (dBμV) | Detector | Corrected (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|----------------|----------|------------------|-----------------|----------------|-------------|
| 30.0000 | 25.93 | peak | 1.46 | 27.39 | 40.00 | 12.61 |
| 108.5700 | 39.86 | peak | -6.86 | 33.00 | 43.50 | 10.50 |
| 202.6600 | 40.69 | peak | -5.98 | 34.71 | 43.50 | 8.79 |
| 229.8200 | 43.94 | peak | -6.38 | 37.56 | 46.00 | 8.44 |
| 243.4000 | 41.84 | peak | -5.91 | 35.93 | 46.00 | 10.07 |
| 395.6900 | 35.63 | peak | -2.21 | 33.42 | 46.00 | 12.58 |


Vertical:

80.0 dB μ V/m



| Frequency (MHz) | Reading (dB μ V) | Detector | Corrected (dB/m) | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------------|----------|------------------|-----------------------|----------------------|-------------|
| 30.9700 | 27.60 | peak | 0.74 | 28.34 | 40.00 | 11.66 |
| 108.5700 | 37.75 | peak | -6.86 | 30.89 | 43.50 | 12.61 |
| 175.5000 | 37.06 | peak | -7.00 | 30.06 | 43.50 | 13.44 |
| 229.8200 | 39.11 | peak | -6.38 | 32.73 | 46.00 | 13.27 |
| 395.6900 | 38.56 | peak | -2.21 | 36.35 | 46.00 | 9.65 |
| 623.6400 | 36.53 | peak | 1.37 | 37.90 | 46.00 | 8.10 |

Emission Mask



| No. | Frequency (MHz) | Reading (dBuV/m) | Detector | Corrected (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----|-----------------|------------------|----------|------------------|-----------------|----------------|-------------|
| 1 | 13.5618 | 70.59 | peak | 9.31 | 79.90 | 124.00 | 44.10 |

FCC§15.225(e) - FREQUENCY STABILITY

Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Procedure

Frequency Stability vs. Temperature: The adapter under test was connected to an external AC power.

The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable AC or DC power supply Source connected to the EUT or EUT adapter. Test the frequency output in the extremity voltage.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|----------------|-------------------|-----------|---------------|------------------|----------------------|
| EMCO | Passive Loop | 6512 | 9706-1206 | 2020-03-05 | 2023-03-05 |
| Sunol Sciences | Antenna | JB3 | A060611-1 | 2020-11-10 | 2023-11-10 |
| R&S | EMI Test Receiver | ESR3 | 102453 | 2020-09-12 | 2021-09-12 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0075-01 | 2020-09-05 | 2021-09-05 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0400-01 | 2020-09-05 | 2021-09-05 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-1400-01 | 2020-05-06 | 2021-05-06 |
| HP | Amplifier | 8447D | 2727A05902 | 2020-09-05 | 2021-09-05 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| | |
|---------------------------|------------|
| Temperature: | 25.2°C |
| Relative Humidity: | 45 % |
| ATM Pressure: | 102.2Pa |
| Tester: | Jalon Liu |
| Test Date: | 2020-11-26 |

Test Result: Compliance.

| f_o = 13.562 MHz | | | | |
|-----------------------------------|-----------------------|---------------------------|------------------------|--------------|
| Temperature | Voltage | Measured frequency | Frequency Error | Limit |
| °C | V_{DC} | MHz | Hz | Hz |
| -30 | 12 | 13.561792 | -208 | ±1356 |
| -20 | | 13.561775 | -225 | ±1356 |
| -10 | | 13.561699 | -301 | ±1356 |
| 0 | | 13.561769 | -231 | ±1356 |
| 10 | | 13.561807 | -193 | ±1356 |
| 20 | | 13.561795 | -205 | ±1356 |
| 25 | | 13.561884 | -116 | ±1356 |
| 30 | | 13.561901 | -99 | ±1356 |
| 40 | | 13.561856 | -144 | ±1356 |
| 50 | | 13.561808 | -192 | ±1356 |
| 20 | | 10.8 | 13.561897 | -103 |
| 20 | 13.2 | 13.561822 | -178 | ±1356 |

Note: Operation voltage range declared by manufacturer.

FCC §15.215(c) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Per FCC §15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through § 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Procedure

Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|-----------|---------------|------------------|----------------------|
| EMCO | Passive Loop | 6512 | 9706-1206 | 2020-03-05 | 2023-03-05 |
| R&S | EMI Test Receiver | ESR3 | 102453 | 2020-09-12 | 2021-09-12 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0075-01 | 2020-09-05 | 2021-09-05 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0400-01 | 2020-09-05 | 2021-09-05 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-1400-01 | 2020-05-06 | 2021-05-06 |
| HP | Amplifier | 8447D | 2727A05902 | 2020-09-05 | 2021-09-05 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| | |
|---------------------------|------------|
| Temperature: | 25.2°C |
| Relative Humidity: | 45 % |
| ATM Pressure: | 102.2Pa |
| Tester: | Jalon Liu |
| Test Date: | 2020-11-26 |


Test Mode: Transmitting

Test Result: Compliance.

Please refer to following tables and plots

| Test Frequency (MHz) | 20 dB Bandwidth (kHz) |
|----------------------|-----------------------|
| 13.562 | 1.476 |

20 dB Emission Bandwidth



Date: 29.DEC.2020 19:11:06

******* END OF REPORT *******